



Customer information packet

CDMG2310

10KW, 2500RPM, DC, 219ATC, DPFG, F2

Specifications

Armature Voltage	230 V
Base Speed	2500 rpm
Enclosure	DPFG
Field Voltage	230 V
Output Power	10.000 KW
Agency Approvals	CSA
Ambient Temperature	40 °C
Armature Current	43.5 a
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Field Winding Type	COMPOUND
Heater Indicator	No Heater
Insulation Class	F
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F2
Overall Length	24.50 IN
Service Factor	1.00
Shaft Diameter	1.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger
Thermal Device - Bearing	None

Part detail



Revision	B
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	K0002A
Layout	2056
Eff. date	02-08-2022
CD Diagram	
Poles	00
Leads	
Proprietary	False
Created date	12-12-2019

Nameplate

15405									
CAT.NO.	CDMG2310		MODEL NO.		T21S8006				
KW	10 KW	RPM	2500		FRAME		0219ATC		
ARM VOLTS	230		ARM AMPS		43.50		WOUND		COMPOUND
FIELD VOLTS	230		FIELD AMPS		1.22-.88				
FIELD CONN.			OHMS	188.5		INSUL. CLASS			F
ENCL	DPFG	DUTY		CONT		MAX AMBIENT			40
SERVICE FACTOR	1.0								
S/N			E/S	K0002A					
	-								
O.D.E. BRG.	6207	D.E. BRG.		6207	BRUSH		150986-21-1		
								QTY	2

REL S.O.	FRAME	RATING	RPM	ARM. VOLTS	ARM. AMPS
	219AT	10.0HP	2500	230	43.5
WINDING TYPE		S.F.	ENCL.	AMB °C/INSUL	DUTY
STAB. SHUNT		1.0	DPG	40/F	CONT
					230
POWER CODE	TYPE	WK ² (LB-FT ²)		HOT ARM.CIR.RES.	FLD. AMPS@25 °C
A	T	1.201		1.02	1.21
					261
ARM. CIR. IND. (mh)	FIELD IND. (H)	COOLING AIR(CFM/IN H ²⁰)			TURNS PER COIL SHUNT/SERIES
4.23	10.2	-/-			2300/11.5
LOAD PERFORMANCE					
LOAD	AMPERES	TORQUE IN OZ.-FT.	OUTPUT IN HP	RPM	% EFFICIENCY
NO LOAD	4971	0	0	4220	0
1/4	11	0	0	3978	0
2/4	22	0	0	3717	0
3/4	33	0	0	3466	0
4/4	44	0	0	3222	0
0.L.	65	0	0	2751	0
RPM VS. FIELD AMPS					
FIELD AMPS		RPM N.L.	RPM F.L.	Eg N.L. @ BASE SPEED	Eg F.L. @ BASE SPEED
.878		4219	3222	134	134
6.22		-184	2929	333	234
11.5		-34	2604	333	260
16.9		-15	2831	333	266
22.2		4219	3222	134	134
REMARKS: TYPICAL DATA					
		DR. BY E. GILLLOT CK. BY B. GRANT APP. BY R. ERICHER DATE 11-19-07		D-C MOTOR PERFORMANCE DATA DK0002A ISSUE DATE 11-19-07	

2056



	FOOT MOUNTING						D.E. SHAFT EXTENSION													DRIVE KEY		FRAME					
FRAME	BA	E	2F	G	H	J	AH	AJ	AK	^{BB} MIN.	BC	BD	^{BF} THREAD	^{DEEP}	N	N-W	U	V	W	KEY-SQ.	KEY-LONG	A	B	C	D	O	P
1810AT	2.75	3.75	11.00	.38	.406	1.50	2.125	7.250	8.500	.25	—	8.69	1/2-13	.75	2.90	2.77	1.125 ¹	2.50 ³	.13	.250	1.38	12.25	12.25	21.46	4.50 ²	9.00	9.00
219AT	3.50	4.25	11.00	.50	.406	2.00	2.50	7.250	8.500	.24	.25	8.75	1/2-13	1.00	3.00	2.75	1.375 ¹	2.50 ³	.25	.312	1.75	12.00	12.00	24.50	5.25 ²	10.47	10.44
258AT	4.25	5.00	12.50	.69	.531	2.25	3.00	7.250	8.500	.27	.25	8.75	1/2-13	.97	3.44	3.25	1.625 ¹	3.00 ³	.19	.375	2.31	12.38	14.00	26.50	6.25 ²	12.47	12.44
259AT	4.25	5.00	14.00	.69	.531	2.25	3.00	7.250	8.500	.27	.25	8.75	1/2-13	.97	3.44	3.25	1.625 ¹	3.00 ³	.19	.375	2.31	15.50	15.50	28.00	6.25 ²	12.47	12.44
288AT	4.75	5.50	14.00	.69	.531	2.50	3.50	9.000	10.500	.25	.25	10.75	1/2-13	.75	3.91	3.75	1.875 ¹	3.50 ³	.16	.500	2.50	15.62	15.62	32.00	7.00 ²	13.88	13.75
328AT	5.25	6.25	16.00	.81	.656	3.00	4.00	11.000	12.500	.25	.25	12.75	5/8-11	.88	4.40	4.25	2.125 ¹	4.00 ³	.15	.500	3.12	17.75	17.75	34.63	8.00 ²	15.94	15.88
329AT	5.25	6.25	18.00	.81	.656	3.00	4.00	11.000	12.500	.25	.25	12.75	5/8-11	.88	4.40	4.25	2.125 ¹	4.00 ³	.15	.500	3.12	19.75	19.75	36.63	8.00 ²	15.94	15.88

CONDUIT BOX							APPROXIMATE WEIGHT
FRAME	AA	AB	AC	AF	BS	XL	
1810AT	3/4NPT	INTEGRAL WITH ENDPLATE					195
219AT	3/4-1	7.91	6.44	2.44	9.38	3.81	260
258AT	1-1/4	9.35	7.72	2.94	9.75	4.94	366
259AT	1-1/4	9.35	7.72	2.94	11.25	4.94	411
288AT	1-1/4	11.88	9.25	5.00	12.64	7.88	566
328AT	2	12.94	10.32	5.00	13.68	7.88	775
329AT	2	12.94	10.32	5.00	15.68	7.88	884

- 1) SHAFT DIAMETERS TO 1.500 TOLERANCE +.0000 - .0005
SHAFT DIAMETERS ABOVE 1.500 TOLERANCE +.0000 - .0010
SHAFT DIAMETERS TO 1.625 RUNOUT .002 T.I.R. MAX.
SHAFT DIAMETERS ABOVE 1.625 RUNOUT .003 T.I.R. MAX.
- 2) 'D' DIMENSION TOLERANCE +.000 - .030
- 3) 'V' DIMENSION IS MAX. HUB LENGTH ON SHAFT
- 4) CONDUIT BOX CAN BE ROTATED IN 90° STEPS ON ITS OWN AXIS.
- 5) ALL DIMENSIONS NOT NOTED ARE NOMINAL DIMENSIONS CONSULT FACTORY FOR TOLERANCES.

MATL: —

REV: — NEW DWG. RELEASE

990Z

SCALE: —

BY: MBT

REVISED: 07/28/95

FILE: CHB00004002

TDR: 0078613

BALDOR ELECTRIC Co.

DIM SHEET, 1810ATC THRU 329ATC GENERATORS

2056

