



Customer information packet

CDP3605

5HP, 1750RPM, DC, 1810ATC, 3681P, TEFC, F1

Class - None

Division -

Specifications

Armature Voltage	180 V
Base Speed	1750 rpm
Enclosure	TEFC
Frame	1810ATC
Frame Material	Steel
Haz Area Class and Group	None
Output Power	5.000 HP
Agency Approvals	CE CSA UR
Ambient Temperature	40 °C
Armature Current	21.6 a
Armature Inertia	192.361 lb-ft ²
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
Lifting Lugs	Standard Lifting Lugs
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	2 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Mounting Arrangement	F1
Overall Length	27.83 IN
Product Family	General Purpose
Pulley End Bearing Type	Sealed Bearing
Service Factor	1.00
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding

Part detail

Revision	AG
Type	DC
Mech. spec.	36P179
Base	
Status	PRD/A
Elec. spec.	36WGZ543
Layout	36LYP179
Eff. date	11-12-2024
CD Diagram	CD0194
Poles	00
Leads	
Proprietary	False
Created date	01-01-0001

Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger

Nameplate

NP0891L					
CAT.NO.	CDP3605				
SPEC.	36P179Z543				
HP	5/3.7 KW	ENCL		TEFC	
RPM	1750 1/MIN IC411 73KG				
FRAME	1810ATC	TYPE		3688P	
ARM V	180	ARM A		21.6	
FLD V		FLD A			
INSUL	H	AMB.		40	
DUTY	CONT	SUPPLY		K	
BRG/DE	6206	BRG/ODE		6206	
BRUSHES	2/BP5027A01				
		BLANK		IP44	
SER.					
BLANK					
APRV-CE	Y	APRV-CSA	Y	APRV-UL	Y

Accessories

Part number	Description	Multiplier
TK3600PM	TACHO MOUNTING KIT FOR TK3600PM	A8

DC Motor Performance Data

Record # 1441

Typical performance - not guaranteed values

Winding: 36WGZ543-R001		Type: 3688P	Enclosure: TEFC
Nameplate Data		General Characteristics	
Rated Output (HP)	5	Armature Resistance @ 25°C	0.1532 Ω
R.P.M.	1750		
Armature Volts	180		
Armature Amps	21.6		
Field Volts		Armature Inductance	3.7192 mH
Field Amps			
Rating - Duty	40C AMB-CONT		
Power Supply Code	K		

Load Characteristics at 180 Armature Volts

Load Point	1	2	3	4	5	6	7
Armature Amps	0.88	6.23	11.5	17	22.2	27.7	33.21
R.P.M.	1875	1860	1840	1830	1812	1800	1785
Torque (LB-FT)	0	3.75	7.5	11.25	15	18.75	22.5

ABB Motors and Mechanical Inc.

WINDING # 36WGZ543

Typical performance - not guaranteed values.

5 HP DC 1750 RPM 180 V 3688P

ENCL: TEFC DUTY: CONT CL: H





