



Customer information packet

CDRXL050544

.5HP, 1740RPM, 1PH, 60HZ, 56C, 3520L, XPFC, F1

Class - CLI GP C,D

Division - Division I

Specifications

Enclosure	XPFC
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Division I
Motor Letter Type	Cap Start, Induction Run
Output @ Frequency	.500 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 208.0 V @ 60 HZ 115.0 V @ 60 HZ
Agency Approvals	CSA UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	7.000 A @ 115.0 V 3.500 A @ 230.0 V 3.450 A @ 208.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	66.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Haz Area Temp Code	T3C

Part detail

Revision	E
Type	AC
Mech. spec.	35X723
Base	
Status	PRD/A
Elec. spec.	35WGG470
Layout	35LYX723
Eff. date	08-15-2024
CD Diagram	CD0001
Poles	04
Leads	6#18
Proprietary	False
Created date	08-01-2022

Heater Indicator	No Heater
High Voltage Full Load Amps	3.5 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	X3520L
Mounting Arrangement	F1
Number of Poles	4
Overall Length	14.31 IN
Power Factor	70
Product Family	Hazardous Location Motor
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1740 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP0977XPSL												
NO.							CC					
SER.							TEMP CODE	T3C				
SPEC.	35X723G470											
CAT.NO.	CDRXL050544											
HP	.5											
VOLTS	115/208-230											
AMPS	7/3.45-3.5											
RPM	1740					MOTOR WEIGHT				43		
HERTZ	60	PH	1	CL	F	DE BRG	6205					
SER.F.	1.15	DES	N	CODE		L	ODE BRG			6203		
FRAME	56C	GREASE			POLYREX EM							
RATING	40C AMB-CONT											
				NEMA-NOM-EFF				66	PF	70		
	NEMA MG-1 PT 5,IP55											

AC Induction Motor Performance Data

Record # 94793

Typical performance - not guaranteed values

Winding: 35WGG470-R004			Type: 3520L		Enclosure: XPFC			
Nameplate Data			115 V, 60 Hz: Low Voltage Connection					
Rated Output (HP)		.5	Full Load Torque		1.511 LB-FT			
Volts		115/208-230	Start Configuration		direct on line			
Full Load Amps		7/3.45-3.5	Breakdown Torque		4.22 LB-FT			
R.P.M.		1740	Pull-up Torque		3.95 LB-FT			
Hz	60	Phase	1	Locked-rotor Torque		6.21 LB-FT		
NEMA Design Code		N	KVA Code	L	Starting Current		43.3 A	
Service Factor (S.F.)		1.15	No-load Current		5.29 A			
NEMA Nom. Eff.		66	Power Factor		70	Line-line Res. @ 25°C		1.3669 Ω A Ph 2.3003 Ω B Ph
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		62°C	
S.F. Amps		8/3.8-4	Temp. Rise @ S.F. Load		72°C			
			Locked-rotor Power Factor		98.3			

Load Characteristics 115 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	35	49	61	70	77	82	74
Efficiency	42.8	57.5	63.6	65.7	65.6	63.7	65.6
Speed	1781.1	1768.1	1752.9	1735.9	1715.7	1690.5	1724
Line amperes	5.38	5.7	6.26	7.01	8.01	9.26	7.61


ABB Motors and Mechanical Inc.


WINDING # 35WGG470

Typical performance - not guaranteed values.

0.5 HP 1 PH 60 HZ 1740 RPM 115 V 3520L

TORQUES (LB-FT): PO=4.22 PU=3.95 LR=6.21 LRA=43.3





CD0001

