



Customer information packet

CECP2276T

7.5HP, 1180RPM, 3PH, 60HZ, 254TC, 0954M, TEFC

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	254TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CCSA US CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	1.0
Current @ Voltage	25.000 A @ 208.0 V 21.400 A @ 230.0 V 10.700 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated

Part detail

Revision	Z
Type	AC
Mech. spec.	09H180
Base	
Status	PRD/A
Elec. spec.	09WGX827
Layout	09LYH180
Eff. date	09-16-2025
CD Diagram	CD0005
Poles	06
Leads	9#12
Proprietary	False
Created date	11-14-2013

Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	10.7 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0954M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	25.28 IN
Power Factor	71
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1180 rpm
Speed Code	Single Speed

Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3995ABAL													
CAT #		CECP2276T				SER				CC		010A	
SPEC		09H180X827				RATING		40C AMB-CONT					
HZ		VOLTS		AMPS		RPM		HP		CODE		SF DES PF NEMA NOM. EFF	
60		230/460		21.4/10.7		1180		7.5		J		1.15 A 71 % 91 %	
PH		3		CL F		MAX RPM		1800		MAX CORR KVAR		4.15	
IP55		FR		254TC		ENCL		TEFC		DE BRG		6309	
GREASE		POLYREX EM				MTR WT		305		LBS			
USABLE AT		50HZ 5HP 190/380V 18.6/9.3A						SF1.0					
CL I DIV 2 GRPS A,B,C,D													
CL I ZONE 2 GRPS													
IIA,IIB,IIC													
TEMP T 160 C													
1.0 SF ON PWM INVERTER		POWER		INV TEMP CL		180		C					
CHP		60-90		HZ		1.5:1		CT		1.0-60		HZ	
SPACE HEATER LEADS H1-H2:		TIE LIKE NUMBERS		TOGETHER									
V		A		W		MAX SPACE HEATER TEMP							

AC Induction Motor Performance Data

Record # 47260

Typical performance - not guaranteed values

Winding: 09WGX827-R040			Type: 0954M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		7.5	Full Load Torque		32.4 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		21.4/10.7	Breakdown Torque		99.2 LB-FT		
R.P.M.		1180	Pull-up Torque		39.4 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		57.8 LB-FT	
NEMA Design Code		A	KVA Code	J	Starting Current		69.7 A
Service Factor (S.F.)		1.15		No-load Current		5.84 A	
NEMA Nom. Eff.		91	Power Factor	71	Line-line Res. @ 25°C		0.89 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		31°C	
S.F. Amps				Temp. Rise @ S.F. Load		36°C	
				Rotor inertia		4.34 LB-FT2	

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	32	52	63	71	73	75	72
Efficiency	83	89.7	91.5	91.5	91.8	91.2	91.9
Speed	1196	1192	1189	1184	1179	1173	1181
Line amperes	6.34	7.49	8.87	10.7	12.9	15.7	12

ABB Motors and Mechanical Inc.

WINDING # 09WGX827

Typical performance - not guaranteed values.

7.5 HP 3 PH 60 HZ 1180 RPM 460 V 0954M

TORQUES (LB-FT): PO=99.2 PU=39.4 LR=57.8 LRA=69.7





