



Customer information packet

CEM2550T

100HP, 3540RPM, 3PH, 60HZ, 365TSC, OPSB, F1

Specifications

Enclosure	OPSB
Frame	365TSC
Frame Material	Steel
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	100.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	110.000 A @ 460.0 V 220.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.6 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	110.0 a
Insulation Class	F
Inverter Code	Inverter Ready

Part detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	42WGW937
Layout	42LY-000-021
Eff. date	02-12-2024
CD Diagram	CD0180
Poles	02
Leads	9#4
Proprietary	False
Created date	03-06-2020

IP Rating	NONE
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4266M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	27.81 IN
Power Factor	91
Product Family	General Purpose
Pulley Face Code	C-Face
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	3540 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2138L

CAT.NO.	CEM2550T				P/N				ENCLOSURE				OPSB				
SPEC.	42-0000-0075			CC	010A		FRAME		365TSC		S/N						
HP	100				CLASS		F		HZ		60						
RPM	3540				PH		3		DES		A						
VOLT	230/460								KVA-CODE		G		ODE BRG		6311	DE BRG	6313
AMP	220/110																
RATING	40C AMB-CONT				GREASE		POLYREX EM										
NEMA-NOM-EFF	93.6	PF	91	SER.F.		1.15											
HTR-VOLTS			HTR-AMPS														

AC Induction Motor Performance Data

Record # 38382

Typical performance - not guaranteed values

Winding: 42WGW937-R001			Type: 4266M		Enclosure: OPSB		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		100	Full Load Torque		148 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		220/110	Breakdown Torque		483 LB-FT		
R.P.M.		3540	Pull-up Torque		172 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		245 LB-FT	
NEMA Design Code		B	KVA Code	G	Starting Current		771 A
Service Factor (S.F.)		1.15	No-load Current		23.5 A		
NEMA Nom. Eff.		93.6	Power Factor	91	Line-line Res. @ 25°C		0.0539 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		45°C
S.F. Amps					Temp. Rise @ S.F. Load		55°C
					Locked-rotor Power Factor		21
					Rotor inertia		5.16 LB-FT2

Load Characteristics 460 V, 60 Hz, 100 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	72	87	90	91	91	89	91
Efficiency	91.3	93.9	94	93.6	92.7	91.6	93
Speed	3584	3568	3552	3536	3518	3496	3525
Line amperes	36.1	57.7	82.8	110	138	169	127


ABB Motors and Mechanical Inc.


WINDING # 42WGW937

Typical performance - not guaranteed values.




100 HP 3 PH 60 HZ 3540 RPM 460 V 4266M

TORQUES (LB-FT): PO=483 PU=172 LR=245 LRA=771





CD0180

LOW VOLTAGE
(2D)HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10:25:29 02/19/2019

BY: ENBRIRO

MTL: —



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1