



---

# Customer information packet

## CEM3309T-G

5HP, 1160RPM, 3PH, 60HZ, 215TC, OPSB, F1

Class - None

Division - Not Applicable

## Specifications

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Enclosure                      | OPSB                                    |
| Frame                          | 215TC                                   |
| Frame Material                 | Steel                                   |
| Frequency                      | 60.00 Hz                                |
| Haz Area Class and Group       | None                                    |
| Haz Area Division              | Not Applicable                          |
| Motor Letter Type              | Three Phase                             |
| Output @ Frequency             | 5.000 HP @ 60 HZ                        |
| Phase                          | 3                                       |
| Synchronous Speed @ Frequency  | 1200 RPM @ 60 HZ                        |
| Voltage @ Frequency            | 230.0 V @ 60 HZ<br>460.0 V @ 60 HZ      |
| Agency Approvals               | CSA<br>CSA EEV<br>NEMA PREMIUM<br>UR    |
| Ambient Temperature            | 40 °C                                   |
| Auxiliary Box                  | NO AUXILLARY BOX                        |
| Auxiliary Box Lead Termination | None                                    |
| Base Indicator                 | Rigid                                   |
| Bearing Grease Type            | Polyrex EM (-20F +300F)                 |
| Blower                         | None                                    |
| Current @ Voltage              | 7.400 A @ 460.0 V<br>14.800 A @ 230.0 V |
| Design Code                    | A                                       |
| Drip Cover                     | No Drip Cover                           |
| Duty Rating                    | CONT                                    |
| Efficiency @ 100% Load         | 89.5 %                                  |
| Electrically Isolated Bearing  | Not Electrically Isolated               |
| Feedback Device                | NO FEEDBACK                             |
| Heater Indicator               | No Heater                               |
| High Voltage Full Load Amps    | 7.4 a                                   |

## Part detail

|              |            |
|--------------|------------|
| Revision     | G          |
| Type         | AC         |
| Mech. spec.  |            |
| Base         |            |
| Status       | PRD/A      |
| Elec. spec.  | 37WGS521   |
| Layout       | 37LYK447   |
| Eff. date    | 06-11-2024 |
| CD Diagram   | CD0005     |
| Poles        | 06         |
| Leads        | 9#14       |
| Proprietary  | False      |
| Created date | 02-24-2020 |

|                                   |                       |
|-----------------------------------|-----------------------|
| <b>Insulation Class</b>           | H                     |
| <b>Inverter Code</b>              | Inverter Ready        |
| <b>IP Rating</b>                  | NONE                  |
| <b>KVA Code</b>                   | K                     |
| <b>Lifting Lugs</b>               | Standard Lifting Lugs |
| <b>Locked Bearing Indicator</b>   | Locked Bearing        |
| <b>Motor Lead Termination</b>     | Flying Leads          |
| <b>Motor Standards</b>            | NEMA                  |
| <b>Motor Type</b>                 | 3744M                 |
| <b>Mounting Arrangement</b>       | F1                    |
| <b>Number of Poles</b>            | 6                     |
| <b>Overall Length</b>             | 18.19 IN              |
| <b>Power Factor</b>               | 71                    |
| <b>Product Family</b>             | General Purpose       |
| <b>Pulley Face Code</b>           | C-Face                |
| <b>Rodent Screen</b>              | None                  |
| <b>Service Factor</b>             | 1.15                  |
| <b>Shaft Diameter</b>             | 1.375 IN              |
| <b>Shaft Ground Indicator</b>     | Shaft Grounding       |
| <b>Shaft Rotation</b>             | Reversible            |
| <b>Speed</b>                      | 1160 rpm              |
| <b>Speed Code</b>                 | Single Speed          |
| <b>Starting Method</b>            | Direct on line        |
| <b>Thermal Device - Bearing</b>   | None                  |
| <b>Thermal Device - Winding</b>   | None                  |
| <b>Vibration Sensor Indicator</b> | No Vibration Sensor   |
| <b>Winding Thermal 1</b>          | None                  |
| <b>Winding Thermal 2</b>          | None                  |

## Nameplate

## NP3553LUA

|                           |                             |      |     |      |   |       |       |
|---------------------------|-----------------------------|------|-----|------|---|-------|-------|
| CAT.NO.                   | CEM3309T-G                  |      |     |      |   |       |       |
| SPEC.                     | 37-0000-0219                |      |     |      |   |       |       |
| HP                        | 5                           |      |     |      |   |       |       |
| VOLTS                     | 230/460                     |      |     |      |   |       |       |
| AMPS                      | 14.8/7.4                    |      |     |      |   |       |       |
| RPM                       | 1160                        |      |     |      |   |       |       |
| FRAME                     | 215TC                       |      | HZ  | 60   |   | PH    | 3     |
| SF                        | 1.15                        | CODE | K   | DES  | A | CLASS | H     |
| NEMA NOM. EFF             | 89.5                        | PF   | 71  |      |   |       |       |
| RATING                    | 40C AMB-CONT                |      |     |      |   |       |       |
| CC                        | 010A                        |      |     |      |   |       |       |
| ENCL                      | OPSB                        | SN   |     |      |   |       |       |
| DE                        | 6307                        |      | ODE | 6206 |   |       |       |
| VPWM INVERTER READY       |                             |      |     |      |   |       |       |
| CT30-60(2:1) VT3-60(20:1) |                             |      |     |      |   |       |       |
| USABLE AT                 | 50HZ 5HP 190/380V 17.2/8.6A |      |     |      |   |       | SF1.0 |

**AC Induction Motor Performance Data**

Record # 62644

Typical performance - not guaranteed values

| Winding: 37WGS521-R002 |    |          | Type: 3744M                              |                     | Enclosure: OPSB  |                           |      |             |
|------------------------|----|----------|------------------------------------------|---------------------|------------------|---------------------------|------|-------------|
| Nameplate Data         |    |          | 460 V, 60 Hz:<br>High Voltage Connection |                     |                  |                           |      |             |
| Rated Output (HP)      |    | 5        | Full Load Torque                         |                     | 22.5 LB-FT       |                           |      |             |
| Volts                  |    | 230/460  | Start Configuration                      |                     | direct on line   |                           |      |             |
| Full Load Amps         |    | 14.8/7.4 | Breakdown Torque                         |                     | 77.9 LB-FT       |                           |      |             |
| R.P.M.                 |    | 1160     | Pull-up Torque                           |                     | 47.4 LB-FT       |                           |      |             |
| Hz                     | 60 | Phase    | 3                                        | Locked-rotor Torque |                  | 54.8 LB-FT                |      |             |
| NEMA Design Code       |    | A        | KVA Code                                 | K                   | Starting Current |                           | 53 A |             |
| Service Factor (S.F.)  |    | 1.15     |                                          | No-load Current     |                  | 3.84 A                    |      |             |
| NEMA Nom. Eff.         |    | 89.5     | Power Factor                             |                     | 71               | Line-line Res. @ 25°C     |      | 1.74 Ω      |
| Rating - Duty          |    | 40C      |                                          | AMB-CONT            |                  | Temp. Rise @ Rated Load   |      | 33°C        |
| S.F. Amps              |    |          |                                          |                     |                  | Temp. Rise @ S.F. Load    |      | 40°C        |
|                        |    |          |                                          |                     |                  | Locked-rotor Power Factor |      | 22.7        |
|                        |    |          |                                          |                     |                  | Rotor inertia             |      | 1.09 LB-FT2 |

**Load Characteristics 460 V, 60 Hz, 5 HP**

| % of Rated Load | 25   | 50   | 75   | 100  | 125  | 150  | S.F. |
|-----------------|------|------|------|------|------|------|------|
| Power Factor    | 33   | 53   | 65   | 71   | 75   | 76   | 73   |
| Efficiency      | 84.7 | 89.4 | 89.7 | 89.7 | 88.5 | 86.5 | 89   |
| Speed           | 1192 | 1184 | 1174 | 1165 | 1154 | 1139 | 1158 |
| Line amperes    | 4.14 | 4.95 | 6.08 | 7.36 | 8.92 | 10.7 | 8.3  |

ABB Motors and Mechanical Inc.

WINDING # 37WGS521

Typical performance - not guaranteed values.

5 HP 3 PH 60 HZ 1160 RPM 460 V 3744M

TORQUES (LB-FT): PO=77.9 PU=47.4 LR=54.8 LRA=53





