



Customer information packet

CEM3769T

7.5HP, 3515RPM, 3PH, 60HZ, 213TC, 0726M, TEFC

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	213TC
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	9.000 A @ 460.0 V 18.600 A @ 208.0 V 18.000 A @ 230.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None

Part detail

Revision	D
Type	AC
Mech. spec.	07H058
Base	
Status	PRD/A
Elec. spec.	07WGT515
Layout	07LYH058
Eff. date	10-17-2024
CD Diagram	CD0005
Poles	02
Leads	9#14
Proprietary	False
Created date	01-05-2021

Heater Indicator	No Heater
High Voltage Full Load Amps	9.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0726M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	19.20 IN
Power Factor	87
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3515 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3441LUA

CAT.NO.	CEM3769T									
SPEC	07H058T515G1									
HP	7.5									
VOLTS	230/460									
AMPS	18/9									
RPM	3515									
FRAME	213TC		HZ	60			PH	3		
SF	1.15		CODE	H	DES	B	CLASS	F		
NEMA NOM. EFF	89.5		PF	87						
RATING	40C AMB-CONT									
CC	010A									
ENCL	TEFC		SER							
DE	6307		ODE	6206						
VPWM INVERTER READY										
CT6-60H(10:1)VT3-60H(20:1										
	50HZ 7.5HP 190/380V 22.6/11.3A								SF1.0	

AC Induction Motor Performance Data

Record # 86052

Preliminary Data Sheet

Winding: 07WGT515-R001			Type: 0726M		Enclosure: TEFC		
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		7.5		Full Load Torque		11.2 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		18/9		Breakdown Torque		40.3 LB-FT	
R.P.M.		3515		Pull-up Torque		16.3 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		19.3 LB-FT	
NEMA Design Code		B		KVA Code	H	Starting Current	64.8 A
Service Factor (S.F.)		1.15		No-load Current		3.58 A	
NEMA Nom. Eff.		89.5	Power Factor	87	Line-line Res. @ 25°C		1.33 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		47°C	
S.F. Amps		20.4/10.2		Temp. Rise @ S.F. Load		62°C	
				Locked-rotor Power Factor		37.8	
				Rotor inertia		0.237 lb-ft²	

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	49	71	81	86	88	88	87
Efficiency	85.8	90.6	91.4	91.1	90.2	89	90.6
Speed	3578	3559	3536	3515	3490	3564	3500
Line amperes	4.15	5.43	7.1	9.01	11.1	13.4	10.2

ABB Motors and Mechanical Inc.

WINDING # 07WGT515

Typical performance - not guaranteed values.

7.5 HP 3 PH 60 HZ 3515 RPM 460 V 0726M

TORQUES (LB-FT): PO=40.3 PU=16.3 LR=19.3 LRA=64.8





