



Customer information packet

CESSWDM3611T-5

3HP, 1760RPM, 3PH, 60HZ, 182TC, 3636M, TEFC, F1

Class -

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	182TC
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.190 A @ 575.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	3.2 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing

Part detail

Revision	P
Type	AC
Mech. spec.	36L738
Base	
Status	PRD/A
Elec. spec.	36WGR715
Layout	36LYL738
Eff. date	11-24-2025
CD Diagram	CD0006
Poles	04
Leads	3#16
Proprietary	False
Created date	05-18-2016

Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3636M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	16.82 IN
Power Factor	76
Product Family	Wash Down All Stainless Steel
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1760 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Nameplate

NP1953B05												
CAT.NO.	CESSWDM3611T-5											
SPEC.	36L738R715G1											
HP	3											
VOLTS	575											
AMP	3.19											
RPM	1760											
FRAME	182TC			HZ		60		PH		3		
SER.F.	1.15		CODE		K	DES		B	CLASS		F	
NEMA-NOM-EFF	89.5			PF		76						
RATING	40C AMB-CONT											
CC	010A			USABLE AT 208V					N/A			
DE	6206			ODE		6205						
ENCL	TEFC	SN										
	10:1CT 20:1VT											

AC Induction Motor Performance Data

Record # 59113

Typical performance - not guaranteed values

Winding: 36WGR715-R002			Type: 3636M	Enclosure: TEFC			
Nameplate Data			575 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		3	Full Load Torque		9.05 LB-FT		
Volts		575	Start Configuration		direct on line		
Full Load Amps		3.3	Breakdown Torque		34 LB-FT		
R.P.M.		1760	Pull-up Torque		18.2 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		21.4 LB-FT	
NEMA Design Code		B	KVA Code	K	Starting Current		26.8 A
Service Factor (S.F.)			1	No-load Current		1.77 A	
NEMA Nom. Eff.		89.5	Power Factor	76	Line-line Res. @ 25°C		5.98 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		63°C	
				Locked-rotor Power Factor		41.8	
				Rotor inertia		0.335 LB-FT2	

Load Characteristics 575 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	36	57	69	76	80	83
Efficiency	82.4	88.2	89.7	89.7	88.9	88
Speed	1790	1781	1772	1761	1750	1737
Line amperes	1.93	2.26	2.74	3.32	3.95	4.66


ABB Motors and Mechanical Inc.


WINDING # 36WGR715

Typical performance - not guaranteed values.



3 HP 3 PH 60 HZ 1760 RPM 575 V 3636M

TORQUES (LB-FT): PO=34 PU=18.2 LR=21.4 LRA=26.8





CD0006



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10: 24: 49 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1