



Customer information packet

CESSWDM3711T

10HP, 3500RPM, 3PH, 60HZ, 215TC, 3744M, TEFC, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	215TC
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	23.000 A @ 208.0 V 21.200 A @ 230.0 V 10.600 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	AA
Type	AC
Mech. spec.	37J639
Base	
Status	PRD/A
Elec. spec.	37WGT383
Layout	37LYJ639
Eff. date	12-18-2024
CD Diagram	CD0005
Poles	02
Leads	9#14
Proprietary	False
Created date	07-19-2006

High Voltage Full Load Amps	10.6 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	L
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3744M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	20.16 IN
Power Factor	94
Product Family	Wash Down All Stainless Steel
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1953C01											
CAT.NO.	CESSWDM3711T										
SPEC.	37J639T383G1										
HP	10										
VOLTS	230/460										
AMP	21.2/10.6										
RPM	3500										
FRAME	215TC			HZ		60		PH		3	
SER.F.	1.15		CODE		L	DES		A	CLASS		F
NEMA-NOM-EFF	91.7			PF		94					
RATING	40C AMB-CONT										
CC	010A			USABLE AT 208V					N/A		
DE	6307			ODE		6206					
ENCL	TEFC	SN									
	4:1CT 20:1VT										

AC Induction Motor Performance Data

Record # 57397

Typical performance - not guaranteed values

Winding: 37WGT383-R007			Type: 3744M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		10	Full Load Torque		15 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		21.2/10.6	Breakdown Torque		79 LB-FT		
R.P.M.		3500	Pull-up Torque		37 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		47 LB-FT	
NEMA Design Code		A	KVA Code	L	Starting Current		115 A
Service Factor (S.F.)		1.15	No-load Current		3.4 A		
NEMA Nom. Eff.		91.7	Power Factor	94	Line-line Res. @ 25°C		0.659 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		57°C
S.F. Amps			Temp. Rise @ S.F. Load		70°C		
			Locked-rotor Power Factor		31.5		
			Rotor inertia		0.402 LB-FT2		

Load Characteristics 460 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	65	86	95	96	95	94	95
Efficiency	88.1	92	92.8	91.8	91	89.4	91.3
Speed	3578	3555	3533	3507	3479	3448	3490
Line amperes	4.2	6	8.1	10.6	13.5	16.4	12.3

ABB Motors and Mechanical Inc.

WINDING # 37WGT383

Typical performance - not guaranteed values.

10 HP 3 PH 60 HZ 3500 RPM 460 V 3744M

TORQUES (LB-FT) : PO=79 PU=37 LR=47 LRA=115





