



Customer information packet

CFSWDM3559T-5E

3HP, 3470RPM, 3PH, 60HZ, 145TC, 3546M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	145TC
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.900 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	86.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	2.9 a
Insulation Class	H
Inverter Code	Inverter Ready
KVA Code	P
Lifting Lugs	No Lifting Lugs

Part detail

Revision	J
Type	AC
Mech. spec.	35E4743
Base	
Status	PRD/A
Elec. spec.	35WGN653
Layout	35LYE4743
Eff. date	08-30-2023
CD Diagram	CD0006
Poles	02
Leads	3#18 15" lead length,0#0 dbl dip & bake,0#0 phase insulaY
Proprietary	False
Created date	03-16-2018

Locked Bearing Indicator	Locked Bearing
Motor Finish	UNPAINTED
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	@ 0 AWG 3 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3546M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	16.28 IN
Power Factor	91
Product Family	WD All SS Encapsulated
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3470 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	NONE (OLD)
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4427AAA02															
CAT #	CFSWDM3559T-5E					LBS									
SPEC	35E4743N653G2					ENCL		TEFC							
SER #						CC	010A		IP	69					
HP	3			MAG CUR			1								
VOLTS	575					NEMA NOM. EFF							86.5		
AMPS	2.9					PF		91							
RATING	40C AMB-CONT														
RPM	3470					MAX RPM		5400							
FRAME	145TC		HZ	60		CODE		P	CLASS		H				
SER.F.	1.15		SF AMP						PH	3		DES	A		
DE	6205			ODE		6205									
LUBRICATION	POLYREX EM														
ID LOGO	INVERTER TYPE			VPWM		CHP		60		TO		90		1.5:1	
ID LOGO	WK2		0.127		CT	15		TO		60		4:1			
ID LOGO	SL HZ		2.2		VT	3		TO		60		20:1			

AC Induction Motor Performance Data

Record # 40792

Typical performance - not guaranteed values

Winding: 35WGN653-R001			Type: 3546M		Enclosure: TEFC		
Nameplate Data			575 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		3	Full Load Torque		4.5 LB-FT		
Volts		575	Start Configuration		direct on line		
Full Load Amps		2.9	Breakdown Torque		17.5 LB-FT		
R.P.M.		3470	Pull-up Torque		10.7 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		17.3 LB-FT	
NEMA Design Code		A	KVA Code	P	Starting Current		39.4 A
Service Factor (S.F.)		1.15	No-load Current		1.02 A		
NEMA Nom. Eff.		86.5	Power Factor	91	Line-line Res. @ 25°C		5.41 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		63°C
S.F. Amps			Temp. Rise @ S.F. Load		74°C		
			Locked-rotor Power Factor		43		
			Rotor inertia		0.127 LB-FT2		

Load Characteristics 575 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	58	79	87	90	91	90	91
Efficiency	79.3	86.2	87	86.9	85.6	83.9	86.1
Speed	3568	3542	3511	3481	3446	3406	3460
Line amperes	1.24	1.67	2.24	2.85	3.54	4.32	3.26


ABB Motors and Mechanical Inc.


WINDING # 35WGN653

Typical performance - not guaranteed values.



3 HP 3 PH 60 HZ 3470 RPM 575 V 3546M

TORQUES (LB-FT): PO=17.5 PU=10.7 LR=17.3 LRA=39.4





CD0006



- NOTES:
- 1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
 - 2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
 - 5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: E	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\141	REVISED: 10: 24: 49 02/19/2019	BY: ENBRIRO
MTL: —		

BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1