



Customer information packet

CFSWDNM3610T-E

3HP, 3500RPM, 3PH, 60HZ, 182TC, 3646M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	182TC
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	NEMA PREMIUM CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.500 A @ 460.0 V 7.000 A @ 230.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	P
Type	AC
Mech. spec.	36R551
Base	
Status	PRD/A
Elec. spec.	36WGR690
Layout	36LYR551
Eff. date	11-18-2025
CD Diagram	CD0005
Poles	02
Leads	9#16
Proprietary	False
Created date	08-07-2017

High Voltage Full Load Amps	3.5 a
Insulation Class	H
Inverter Code	Inverter Ready
KVA Code	P
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3646M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	17.05 IN
Power Factor	92
Product Family	WD All SS Encapsulated
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2	None
--------------------------	-------------

AC Induction Motor Performance Data

Record # 72109

Typical performance - not guaranteed values

Winding: 36WGR690-R001			Type: 3646M	Enclosure: TENV			
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		3	Full Load Torque		4.536 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		7/3.5	Breakdown Torque		29.7 LB-FT		
R.P.M.		3500	Pull-up Torque		22 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		27.7 LB-FT	
NEMA Design Code		A	KVA Code	P	Starting Current		51.1 A
Service Factor (S.F.)		1.15	No-load Current		1.21 A		
NEMA Nom. Eff.		89.5	Power Factor	92	Line-line Res. @ 25°C		2.4383 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		99°C
S.F. Amps			Temp. Rise @ S.F. Load		108°C		
			Locked-rotor Power Factor		41.4		

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	62	80	87	91	93	94	92
Efficiency	76.2	85.4	88	88.8	89.5	89	89.2
Speed	3576.9	3559.8	3542	3522	3503.1	3482.1	3511
Line amperes	1.53	2.09	2.77	3.52	4.23	5.02	3.95

ABB Motors and Mechanical Inc.

WINDING # 36WGR690

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 3500 RPM 460 V 3646M

TORQUES (LB-FT): PO=29.7 PU=22 LR=27.7 LRA=51.1





