



Customer information packet

CJEWDM3545

1HP, 3450RPM, 3PH, 60HZ, 56J, 3520M, TEFC, F1, N

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56J
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ 208.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.300 A @ 208.0 V 3.200 A @ 230.0 V 1.600 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	78.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part detail

Revision	L
Type	AC
Mech. spec.	35E2234
Base	
Status	PRD/A
Elec. spec.	35WGR710
Layout	35LYE2234
Eff. date	06-27-2024
CD Diagram	CD0005
Poles	02
Leads	9#18
Proprietary	False
Created date	07-01-2015

Heater Indicator	No Heater
High Voltage Full Load Amps	1.6 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	P
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3520M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	12.72 IN
Power Factor	74
Product Family	Wash Down
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Ext Thread
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.40
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2179L											
CAT.NO.	CJEWDM3545										
SPEC.	35E2234R710G1										
HP	1										
VOLTS	208-230/460										
AMP	3.3-3.2/1.6										
RPM	3450										
FRAME	56J		HZ	60		PH	3				
SER.F.	1.40	CODE	P	DES	B	CLASS	F				
NEMA-NOM-EFF	78.5	PF	74								
RATING	40C AMB-CONT										
CC	010A										
DE	6205		ODE	6203							
ENCL	TEFC	SN									
BLANK	SFA 4.2-4/2										

AC Induction Motor Performance Data

Record # 51666

Typical performance - not guaranteed values

Winding: 35WGR710-R026			Type: 3520M		Enclosure: TEFC	
Nameplate Data			460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		1	Full Load Torque		1.48 LB-FT	
Volts		208-230/460	Start Configuration		direct on line	
Full Load Amps		3.3-3.2/1.6	Breakdown Torque		9.7 LB-FT	
R.P.M.		3450	Pull-up Torque		6.5 LB-FT	
Hz	60 Phase	3	Locked-rotor Torque		7.5 LB-FT	
NEMA Design Code		B KVA Code	P	Starting Current		16.4 A
Service Factor (S.F.)		1.4	No-load Current		0.84 A	
NEMA Nom. Eff.		78.5 Power Factor	74	Line-line Res. @ 25°C		10.6 Ω
Rating - Duty		40C AMB-CONT	Temp. Rise @ Rated Load		34°C	
S.F. Amps		4.2-4/2	Temp. Rise @ S.F. Load		45°C	
			Locked-rotor Power Factor		56.5	
			Rotor inertia		0.0548 LB-FT2	

Load Characteristics 460 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	39	57	68	74	79	81	80
Efficiency	63.3	74	78.7	80	80.9	80.5	80.7
Speed	3568	3547	3524	3498	3473	3441	3454
Line amperes	0.97	1.12	1.32	1.56	1.8	2.09	1.97

ABB Motors and Mechanical Inc.

WINDING # 35WGR710

Typical performance - not guaranteed values.

1 HP 3 PH 60 HZ 3450 RPM 460 V 3520M

TORQUES (LB-FT): PO=9.7 PU=6.5 LR=7.5 LRA=16.4





