



Customer information packet

CJEWDM3555

2HP, 3450RPM, 3PH, 60HZ, 56J, 3526M, TEFC, F1, N

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56J
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	2.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.500 A @ 460.0 V 5.000 A @ 230.0 V 5.300 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	85.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	N
Type	AC
Mech. spec.	35E2234
Base	
Status	PRD/A
Elec. spec.	35WGM774
Layout	35LYE2234
Eff. date	06-27-2024
CD Diagram	CD0005
Poles	02
Leads	9#18
Proprietary	False
Created date	07-02-2015

High Voltage Full Load Amps	2.5 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	M
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3526M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	13.72 IN
Power Factor	88
Product Family	Wash Down
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Ext Thread
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.20
Shaft Diameter	0.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP2179L									
CAT.NO.	CJEWDM3555								
SPEC.	35E2234M774G1								
HP	2								
VOLTS	230/460								
AMP	5/2.5								
RPM	3450								
FRAME	56J		HZ	60		PH	3		
SER.F.	1.20	CODE	M	DES	B	CLASS	F		
NEMA-NOM-EFF	85.5	PF	88						
RATING	40C AMB-CONT								
CC	010A								
DE	6205		ODE	6203					
ENCL	TEFC	SN							
BLANK	SFA 5.8/2.9								

AC Induction Motor Performance Data

Record # 51668

Typical performance - not guaranteed values

Winding: 35WGM774-R069				Type: 3526M		Enclosure: TEFC			
Nameplate Data				460 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		2		Full Load Torque		2.98 LB-FT			
Volts		230/460		Start Configuration		direct on line			
Full Load Amps		5/2.5		Breakdown Torque		14.2 LB-FT			
R.P.M.		3450		Pull-up Torque		6.33 LB-FT			
Hz		60 Phase		3		Locked-rotor Torque		11.2 LB-FT	
NEMA Design Code		B KVA Code		M		Starting Current		25.9 A	
Service Factor (S.F.)		1.2		No-load Current		0.912 A			
NEMA Nom. Eff.		85.5 Power Factor		88		Line-line Res. @ 25°C		6.88 Ω	
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		44°C			
S.F. Amps		5.8/2.9		Temp. Rise @ S.F. Load		55°C			
				Locked-rotor Power Factor		49.9			
				Rotor inertia		0.0719 LB-FT2			

Load Characteristics 460 V, 60 Hz, 2 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	55	75	84	88	90	91	90
Efficiency	73.4	83.6	85.8	86.3	85.8	84.7	85.9
Speed	3572	3547	3520	3492	3461	3426	3467
Line amperes	1.1	1.47	1.93	2.44	3	3.61	2.89

ABB Motors and Mechanical Inc.

WINDING # 35WGM774

Typical performance - not guaranteed values.

2 HP 3 PH 60 HZ 3450 RPM 460 V 3526M

TORQUES (LB-FT): PO=14.2 PU=6.33 LR=11.2 LRA=25.9





