



Customer information packet

CPX28266T

20HP, 1180//980RPM, 3PH, 60HZ, 286TY, XPFC, F1

Class - CLI GP C,D; CLII GP E,F,G

Division - Division I

Specifications

Enclosure	XPFC
Frame	286TY
Frame Material	Iron
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	CLI GP C,D; CLII GP E,F,G
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 50 HZ 20.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	380.0 V @ 50 HZ 230.0 V @ 60 HZ 460.0 V @ 60 HZ 190.0 V @ 50 HZ
Agency Approvals	CSA EEV UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	54.000 A @ 208.0 V 50.000 A @ 230.0 V 46.000 A @ 190.0 V 25.000 A @ 460.0 V 23.000 A @ 380.0 V
Design Code	B
Drip Cover	No Drip Cover

Part detail

Revision	J
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	10WGZ033
Layout	10LY-000-121
Eff. date	11-22-2024
CD Diagram	CD0180
Poles	06
Leads	9#10
Proprietary	False
Created date	04-25-2019

Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Enclosure Modification	Severe Duty Features
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	23.0 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	IP55
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1056M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	28.74 IN
Power Factor	78
Product Family	Chemical Process Features
Pulley Face Code	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.00
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None

Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2033XPSLEV												
NO.						CC	010A					
S/N						TEMP CODE			T3C			
SPEC.	10-0000-0753					INV.TYPE		PWM				
CAT.NO.	CPX28266T					C HP FR	60	C HP TO	90			
HP	20//15					CT HZ FROM		6	CT HZ TO		60	
VOLTS	230/460//190/380					VT HZ FROM		6	VT HZ TO		60	
AMPS	50/25//46/23				MAG CUR	21.4/10.7						
RPM	1180//980				MX RPM	1800						
HZ	60//50	PH	3	CL	F	NOM.EFF.	91.7					
SER.F.	1.00	DES	B	SL HZ	1	WK2	6.86					
FRAME	286TY	RATING		40C AMB-CONT								
BLANK	55C AMB @ 1.00 SF, 60C RISE											
	1.15SF ON SINEWAVE				NEMA MG-1 PT.5,IP55							

AC Induction Motor Performance Data

Record # 75701

Typical performance - not guaranteed values

Winding: 10WGZ033-R002			Type: 1056M		Enclosure: XPFC	
Nameplate Data			380 V, 50 Hz: High Voltage Connection			
Rated Output (HP)	20//15		Full Load Torque	80.4 LB-FT		
Volts	230/460//190/380		Start Configuration	direct on line		
Full Load Amps	50/25//46/23		Breakdown Torque	234 LB-FT		
R.P.M.	1180//980		Pull-up Torque	97.19 LB-FT		
Hz	60//50	Phase	3	Locked-rotor Torque	139 LB-FT	
NEMA Design Code	B		KVA Code	G	Starting Current	142 A
Service Factor (S.F.)	1		No-load Current	10.54 A		
NEMA Nom. Eff.	91.7	Power Factor	78	Line-line Res. @ 25°C	0.501 Ω	
Rating - Duty	40C AMB-CONT		Temp. Rise @ Rated Load	45°C		
S.F. Amps			Temp. Rise @ S.F. Load	56°C		
			Locked-rotor Power Factor	33.7		
			Rotor inertia	6.86 LB-FT ²		

Load Characteristics 380 V, 50 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	41	63	74	79	81	82
Efficiency	87.9	91.8	92.6	92.3	90.8	90.9
Speed	995	991	986	982	977	971
Line amperes	11.71	14.83	18.7	23.4	28.65	34.75


ABB Motors and Mechanical Inc.

WINDING # 10WGZ033

Typical performance - not guaranteed values.

15 HP 3 PH 50 HZ 982 RPM 380 V 1056M

TORQUES (LB-FT): PO=234 PU=97.19 LR=139 LRA=142



AC Induction Motor Performance Data

Record # 75702

Typical performance - not guaranteed values

Winding: 10WGZ033-R002			Type: 1056M		Enclosure: XPFC			
Nameplate Data			460 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		20//15	Full Load Torque		89.2 LB-FT			
Volts		230/460//190/380	Start Configuration		direct on line			
Full Load Amps		50/25//46/23	Breakdown Torque		243 LB-FT			
R.P.M.		1180//980	Pull-up Torque		94 LB-FT			
Hz		60//50	Phase		3	Locked-rotor Torque	134 LB-FT	
NEMA Design Code		B	KVA Code		G	Starting Current		146 A
Service Factor (S.F.)					1	No-load Current		10.7 A
NEMA Nom. Eff.		91.7	Power Factor		78	Line-line Res. @ 25°C		0.501 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		51°C		
S.F. Amps				Temp. Rise @ S.F. Load		63°C		
				Locked-rotor Power Factor		30.3		
				Rotor inertia		6.86 LB-FT2		

Load Characteristics 460 V, 60 Hz, 20 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	44	66	76	80	81	81
Efficiency	88.4	92.2	93.1	92.7	91.3	91.2
Speed	1194	1190	1185	1180	1174	1168
Line amperes	12.1	15.7	20.1	25.4	31.3	38.2


ABB Motors and Mechanical Inc.


WINDING # 10WGZ033

Typical performance - not guaranteed values.


20 HP 3 PH 60 HZ 1180 RPM 460 V 1056M

TORQUES (LB-FT): PO=243 PU=94 LR=134 LRA=146





CD0180

LOW VOLTAGE
(2D)HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0180

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: —

**BALDOR - RELIANCE®**

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1