



Customer information packet

CSPM3212T-G

5HP, 3490RPM, 3PH, 60HZ, 182TC, 3634M, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	182TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	NEMA PREMIUM WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	11.200 A @ 230.0 V 12.200 A @ 208.0 V 5.600 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	5.6 a

Part detail

Revision	B
Type	AC
Mech. spec.	36P497
Base	
Status	PRD/A
Elec. spec.	36WGT826
Layout	36LYP497
Eff. date	11-19-2025
CD Diagram	CD0005
Poles	02
Leads	9#16
Proprietary	False
Created date	04-03-2025

Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	L
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3634M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	14.99 IN
Power Factor	93
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3490 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L													
CAT #	CSPM3212T-G					WGT	81	LBS					
SPEC	36P497T826					ENCL	OPSB						
SER #						CC	010A	IP	23				
HP	5	MAG CUR				3.2/1.6							
VOLTS	230/460					NEMA NOM. EFF							91
AMPS	11.2/5.6						PF	93					
RATING	40C AMB-CONT												
RPM	3490					MAX RPM			5400				
FRAME	182TC	HZ	60	CODE			L	CLASS			H		
SER.F.	1.25	SF AMP	14/7				PH	3	DES	A			
DE	6206			ODE	6205								
LUBRICATION	POLYREX EM												
ID LOGO	INVERTER TYPE			VPWM		CHP	60	TO	90	1.5:1			
ID LOGO	WK2	0.15	CT	6	TO	60	10:1						
ID LOGO	SL HZ	1.8	VT	3	TO	60	20:1						
							QR						
YR													

AC Induction Motor Performance Data

Record # 112307

Preliminary Data Sheet

Winding: 36WGT826-R012			Type: 3634M		Enclosure: OPSB			
Nameplate Data				460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		5		Full Load Torque		7.6 LB-FT		
Volts		230/460		Start Configuration		direct on line		
Full Load Amps		11.2/5.6		Breakdown Torque		41.6 LB-FT		
R.P.M.		3490		Pull-up Torque		26 LB-FT		
Hz		60	Phase	3	Locked-rotor Torque		30.5 LB-FT	
NEMA Design Code		A	KVA Code		L	Starting Current		59.9 A
Service Factor (S.F.)		1.25		No-load Current		1.61 A		
NEMA Nom. Eff.		91	Power Factor		93	Line-line Res. @ 25°C		2.28 Ω
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load		24°C
S.F. Amps		14/7		Temp. Rise @ S.F. Load		33°C		
				Locked-rotor Power Factor		43.5		
				Rotor inertia		0.152 lb-ft²		

Load Characteristics 460 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	63	83	90	93	94	95	94
Efficiency	87.7	91.2	91.6	91.1	90.1	88.3	90.1
Speed	3572	3546	3518	3490	3458	3423	3458
Line amperes	2.16	3.15	4.32	5.58	6.96	8.51	6.96

ABB Motors and Mechanical Inc.

WINDING # 36WGT826

Typical performance - not guaranteed values.

5 HP 3 PH 60 HZ 3490 RPM 460 V 3634M

TORQUES (LB-FT): PO=41.6 PU=26 LR=30.5 LRA=59.9





