



Customer information packet

CSPM3219T-G

7.5HP, 3500RPM, 3PH, 60HZ, 184TC, 3646M, OPSB

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	184TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	WEEE NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	16.800 A @ 230.0 V 8.400 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	90.2 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	8.4 a
Insulation Class	F

Part detail

Revision	B
Type	AC
Mech. spec.	36P497
Base	
Status	PRD/A
Elec. spec.	36WGX419
Layout	36LYP497
Eff. date	11-19-2025
CD Diagram	CD0005
Poles	02
Leads	9#16
Proprietary	False
Created date	04-04-2025

Inverter Code	Inverter Duty
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Quantity/Wire Size	9 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3646M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	16.50 IN
Power Factor	91
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.125 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4423A01A01L													
CAT #	CSPM3219T-G					WGT	96		LBS				
SPEC	36P497X419					ENCL	OPSB						
SER #						CC	010A		IP	23			
HP	7.5			MAG CUR		4.4/2.2							
VOLTS	230/460					NEMA NOM. EFF					90.2		
AMPS	16.8/8.4						PF	91					
RATING	40C AMB-CONT												
RPM	3500					MAX RPM		5400					
FRAME	184TC		HZ	60		CODE	K		CLASS	H			
SER.F.	1.25		SF AMP	20.6/10.3			PH	3		DES	B		
DE	6206			ODE	6205								
LUBRICATION	POLYREX EM												
ID LOGO	INVERTER TYPE			VPWM		CHP	60		TO	90		1.5:1	
ID LOGO	WK2	0.207		CT	6		TO	60		101			
ID LOGO	SL HZ	1.7		VT	3		TO	60		20:1			
							QR						
YR													

AC Induction Motor Performance Data

Record # 112309

Preliminary Data Sheet

Winding: 36WGX419-R010			Type: 3646M		Enclosure: OPSB	
Nameplate Data				460 V, 60 Hz: High Voltage Connection		
Rated Output (HP)		7.5		Full Load Torque		11.2 LB-FT
Volts		230/460		Start Configuration		direct on line
Full Load Amps		16.8/8.4		Breakdown Torque		55 LB-FT
R.P.M.		3500		Pull-up Torque		40 LB-FT
Hz		60 Phase		Locked-rotor Torque		48 LB-FT
NEMA Design Code		B KVA Code		Starting Current		87 A
Service Factor (S.F.)		1.25		No-load Current		2.2 A
NEMA Nom. Eff.		90.2 Power Factor		Line-line Res. @ 25°C		1.45 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		34°C
S.F. Amps		20.6/10.3		Temp. Rise @ S.F. Load		48°C
				Locked-rotor Power Factor		44.8
				Rotor inertia		0.205 lb-ft²

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	65	84	90	91	93	93	93
Efficiency	87.9	91.3	91.6	90.9	89.9	88.6	89.9
Speed	3570	3542	3511	3478	3446	3412	3446
Line amperes	3.1	4.6	6.4	8.4	10.3	12.4	10.3

ABB Motors and Mechanical Inc.

WINDING # 36WGX419

Typical performance - not guaranteed values.

7.5 HP 3 PH 60 HZ 3500 RPM 460 V 3646M

TORQUES (LB-FT) : PO=55 PU=40 LR=48 LRA=87





