



Customer information packet

CSPM3539

.5HP, 1140RPM, 3PH, 60HZ, 56HC, 3436M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56HC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	C UR US WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	2.000 A @ 230.0 V 1.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	78.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.0 a
Insulation Class	F

Part detail

Revision	B
Type	AC
Mech. spec.	34N586
Base	
Status	PRD/A
Elec. spec.	34WGR776
Layout	34LYN586
Eff. date	01-28-2025
CD Diagram	CD0005
Poles	06
Leads	9#18
Proprietary	False
Created date	03-07-2024

Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3436M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	13.72 IN
Power Factor	61
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.25
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1140 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4558A02LL											
CAT #	CSPM3539			WGT	40	LBS					
SER #				ENCL	TEFC						
SPEC	34N586R776			CC	010A	IP	54				
HP	.5			NEMA NOM. EFF							78.5
VOLTS	230/460			PF	61						
AMPS	2/1										
RATING	40C AMB-CONT										
RPM	1140				PH	3	DES	B			
FRAME	56HC	HZ	60	CODE	K	CLASS	F				
SER.F.	1.25	SF AMP	2.2/1.1								
DE	6203		ODE	6203							
GREASE	POLYREX EM										

AC Induction Motor Performance Data

Record # 100838

Preliminary Data Sheet

Winding: 34WGR776-R002			Type: 3436M		Enclosure: TEFC		
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		.5		Full Load Torque		2.38 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		2/1		Breakdown Torque		8.4 LB-FT	
R.P.M.		1140		Pull-up Torque		5.4 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		6.5 LB-FT	
NEMA Design Code		B	KVA Code	K	Starting Current		5.4 A
Service Factor (S.F.)		1.25		No-load Current		0.73 A	
NEMA Nom. Eff.		78.5	Power Factor	61	Line-line Res. @ 25°C		25.8 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		40°C	
S.F. Amps		2.2/1.1		Temp. Rise @ S.F. Load		67°C	
				Locked-rotor Power Factor		53	
				Rotor inertia		0.0855 lb-ft²	

Load Characteristics 460 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	24	39	52	61	69	74	69
Efficiency	67	77	79.2	78.5	76.5	73.4	76.5
Speed	1185	1171	1156	1137	1117	1091	1117
Line amperes	0.75	0.8	0.89	1	1.13	1.3	1.13

ABB Motors and Mechanical Inc.

WINDING # 34WGR776

Typical performance - not guaranteed values.

0.5 HP 3 PH 60 HZ 1140 RPM 460 V 3436M

TORQUES (LB-FT): PO=8.4 PU=5.4 LR=6.5 LRA=5.4





