



Customer information packet

CSWDM3539

.5HP, 1175RPM, 3PH, 60HZ, 56C, 3522M, TENV, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TENV
Frame	56C
Frame Material	Stainless Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	208.0 V @ 60 HZ 230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	C UR US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	1.000 A @ 230.0 V 2.000 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	78.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	1.0 a
Insulation Class	F

Part detail

Revision	-
Type	AC
Mech. spec.	35S630
Base	
Status	PRD/A
Elec. spec.	35WGK346
Layout	35LYS630
Eff. date	10-31-2024
CD Diagram	CD0005
Poles	06
Leads	9#18
Proprietary	False
Created date	10-25-2024

Inverter Code	Inverter Ready
KVA Code	M
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3522M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	12.06 IN
Power Factor	57
Product Family	Wash Down Paint Free
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.25
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1175 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1496L									
CAT.NO.	CSWDM3539								
SPEC.	35S630K346G1								
HP	.5								
VOLTS	208-230/460								
AMP	2/1								
RPM	1175								
FRAME	56C		HZ	60			PH	3	
SER.F.	1.25	CODE	M	DES	B	CLASS		F	
NEMA-NOM-EFF	78.5	PF	57						
RATING	40C AMB-CONT								
CC									
DE	6205		ODE	6203					
ENCL	TENV	SN							
	SFA 2.3/1.15								

AC Induction Motor Performance Data

Record # 105557

Preliminary Data Sheet

Winding: 35WGK346-R001			Type: 3522M		Enclosure: TENV			
Nameplate Data			460 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		.5	Full Load Torque		2.24 LB-FT			
Volts		208-230/460	Start Configuration		direct on line			
Full Load Amps		2/1	Breakdown Torque		8.8 LB-FT			
R.P.M.		1175	Pull-up Torque		5.6 LB-FT			
Hz	60	Phase	3	Locked-rotor Torque		6.1 LB-FT		
NEMA Design Code		B	KVA Code	M	Starting Current		6.4 A	
Service Factor (S.F.)		1.15	No-load Current		0.79 A			
NEMA Nom. Eff.		78.5	Power Factor		57	Line-line Res. @ 25°C		30 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		73°C	
S.F. Amps		2.2/1.1	Temp. Rise @ S.F. Load		82°C			
			Locked-rotor Power Factor		53.8			
			Rotor inertia		0.16 lb-ft²			

Load Characteristics 460 V, 60 Hz, 0.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	24	37	48	57	63	68	61
Efficiency	63.4	75.5	79	81	80.9	79.8	80.9
Speed	1192	1186	1179	1172	1164	1155	1167
Line amperes	0.8	0.86	0.93	1.02	1.14	1.3	1.09

ABB Motors and Mechanical Inc.

WINDING # 35WGK346

Typical performance - not guaranteed values.

0.5 HP 3 PH 60 HZ 1175 RPM 460 V 3522M

TORQUES (LB-FT): PO=8.8 PU=5.6 LR=6.1 LRA=6.4





