



Customer information packet

CTM2276T

7.5HP, 1160RPM, 3PH, 60HZ, 254T, 0756M, TEAO, F

Class - None

Division - Not Applicable

Specifications

Enclosure	TEAO
Frame	254T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ 208.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	24.000 A @ 208.0 V 21.800 A @ 230.0 V 10.900 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part detail

Revision	G
Type	AC
Mech. spec.	07N393
Base	
Status	PRD/A
Elec. spec.	07WGX825
Layout	07LYN393
Eff. date	08-17-2023
CD Diagram	CD0005
Poles	06
Leads	9#14
Proprietary	False
Created date	08-14-2015

Heater Indicator	No Heater
High Voltage Full Load Amps	10.9 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	K
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0756M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	22.16 IN
Power Factor	72
Product Family	Chemical Processing (Not DC)
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1160 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None

Winding Thermal 2

None

Nameplate

NP1258									
CAT.NO.	CTM2276T								
SPEC.	07N393X825H1								
HP	7.5								
VOLTS	208-230/460								
AMP	24-21.8/10.9								
RPM	1160								
FRAME	254T	HZ		60		PH		3	
SER.F.	1.15	CODE		K	DES		A	CL	F
NEMA-NOM-EFF	89.5	PF		72					
RATING	40C AMB-CONT								
CC									
DE	6309		ODE		6206				
ENCL	TEAO	SN							
	1275 FPM 170 CFM								

AC Induction Motor Performance Data

Record # 52119

Typical performance - not guaranteed values

Winding: 07WGX825-R014			Type: 0756M		Enclosure: TEAO		
Nameplate Data			460 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		7.5	Full Load Torque		33.78 LB-FT		
Volts		208-230/460	Start Configuration		direct on line		
Full Load Amps		24-21.8/10.9	Breakdown Torque		151 LB-FT		
R.P.M.		1160	Pull-up Torque		76 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		99.6 LB-FT	
NEMA Design Code		A	KVA Code	K	Starting Current		82.4 A
Service Factor (S.F.)		1.15		No-load Current		5.5 A	
NEMA Nom. Eff.		89.5	Power Factor	72	Line-line Res. @ 25°C		1.0788 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		53°C	
S.F. Amps				Temp. Rise @ S.F. Load		67°C	
				Locked-rotor Power Factor		21.9	

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	35	55	66	72	75	77	74
Efficiency	85.5	89.9	90.3	89.5	88	86.2	88.6
Speed	1190	1181	1171	1160.1	1147	1132	1152
Line amperes	5.82	7.07	8.75	10.8	13.3	15.9	12.3

ABB Motors and Mechanical Inc.

WINDING # 07WGX825

Typical performance - not guaranteed values.

7.5 HP 3 PH 60 HZ 1160 RPM 460 V 0756M

TORQUES (LB-FT): PO=151 PU=76 LR=99.6 LRA=82.4





