



Customer information packet

CTM2332T

10 AIR OVERHP, 1175RPM, 3PH, 60HZ, 256T, 0946

Class - None

Division - Not Applicable

Specifications

Enclosure	TEAO
Frame	256T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	10.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	37.000 A @ 208.0 V 28.800 A @ 230.0 V 14.400 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	U
Type	AC
Mech. spec.	09L877
Base	
Status	PRD/A
Elec. spec.	09WGX829
Layout	09LYL877
Eff. date	11-14-2023
CD Diagram	CD0005
Poles	06
Leads	9#12
Proprietary	False
Created date	08-14-2015

High Voltage Full Load Amps	14.4 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	H
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0946M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	23.00 IN
Power Factor	73
Product Family	Chemical Processing (Not DC)
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1175 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1258									
CAT.NO.	CTM2332T								
SPEC.	09L877X829H2								
HP	10 AIR OVER								
VOLTS	230/460								
AMP	28.8/14.4								
RPM	1175								
FRAME	256T		HZ	60		PH		3	
SER.F.	1.15		CODE	H	DES	B	CL	F	
NEMA-NOM-EFF	89.5		PF	73					
RATING	40C AMB-CONT								
CC									
DE	6309		ODE	6208					
ENCL	TEAO		SN						
	1800 FPM @ 250CFM								

AC Induction Motor Performance Data

Record # 52111

Typical performance - not guaranteed values

Winding: 09WGX829-R030			Type: 0946M		Enclosure: TEAO		
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		10 AIR OVER		Full Load Torque		44.6 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		28.8/14.4		Breakdown Torque		139 LB-FT	
R.P.M.		1175		Pull-up Torque		53.5 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		76.4 LB-FT	
NEMA Design Code		B	KVA Code	H	Starting Current		86.1 A
Service Factor (S.F.)		1.15		No-load Current		7.04 A	
NEMA Nom. Eff.		89.5	Power Factor	73	Line-line Res. @ 25°C		0.83 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		50°C	
S.F. Amps				Temp. Rise @ S.F. Load		67°C	
				Locked-rotor Power Factor		26	
				Rotor inertia		3.7 LB-FT2	

Load Characteristics 460 V, 60 Hz, 10 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	36	56	67	72	75	75	74
Efficiency	82.9	88.6	89.9	89.9	89.2	87.1	89.5
Speed	1195	1190	1184	1178	1171	1163	1174
Line amperes	7.82	9.42	11.61	14.38	17.56	21.2	16.29

ABB Motors and Mechanical Inc.

WINDING # 09WGX829

Typical performance - not guaranteed values.

10 HP 3 PH 60 HZ 1175 RPM 460 V 0946M

TORQUES (LB-FT): PO=139 PU=53.5 LR=76.4 LRA=86.1





