



Customer information packet

CUHL3519

1/.75KWHP, 1745RPM, 1PH, 60HZ, 56C, 3526LC, TE

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	56C
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	1.000 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 208.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	C UR US CE CURUS UKCA WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	9.800 A @ 115.0 V 5.100 A @ 208.0 V 4.900 A @ 230.0 V
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	78.0 %
Electrically Isolated Bearing	Not Electrically Isolated

Part detail

Revision	H
Type	AC
Mech. spec.	35E6093
Base	
Status	PRD/A
Elec. spec.	35WGG590
Layout	35LYE6093
Eff. date	10-29-2024
CD Diagram	CD0055
Poles	04
Leads	6#18
Proprietary	False
Created date	03-01-2023

Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.9 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Finish	CLEAR COAT
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3526LC
Mounting Arrangement	F3
Number of Poles	4
Overall Length	13.23 IN
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1745 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1372L									
CAT.NO.	CUHL3519								
SPEC.	35E6093G590								
HP	1/.75KW								
VOLTS	115/208-230								
AMP	9.8/5.1-4.9								
R.P.M. (1/MIN)	1745								
FRAME	56C		HZ		60			PH	1
SER.F.	1.15	CODE		L	DES	L	CL	F	
NEMA-NOM-EFF	78	PF		90					
RATING	40C AMB-S1 CONT								
CC			IP44 KG18 IC411						
DE	6205		ODE		6203				
ENCL	TEFC	SN							
	IE2-60HZ 78(75%),73(50%)								

AC Induction Motor Performance Data

Record # 101476

Typical performance - not guaranteed values

Winding: 35WGG590-R001			Type: 3526LC		Enclosure: TEFC		
Nameplate Data			230 V, 60 Hz: High Voltage Connection				
Rated Output (HP)		1	Full Load Torque		3.061 LB-FT		
Volts		115/208-230	Start Configuration		direct on line		
Full Load Amps		9.8/5.1-4.9	Breakdown Torque		10.6 LB-FT		
R.P.M.		1745	Pull-up Torque		7.64 LB-FT		
Hz	60	Phase	1	Locked-rotor Torque		11.7 LB-FT	
NEMA Design Code		L	KVA Code		L		
Starting Current		40 A		No-load Current			2.7 A
Service Factor (S.F.)		1.15		Line-line Res. @ 25°C			2.6387 Ω A Ph 1.4489 Ω B Ph
NEMA Nom. Eff.		78	Power Factor		90		
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		53°C	
S.F. Amps		11/5.9-5.5		Temp. Rise @ S.F. Load		62°C	

Load Characteristics 230 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	52	69	79	86	89	91	88
Efficiency	58.6	73.2	78.2	79.7	79.1	77.2	79.3
Speed	1784.6	1772.8	1760	1745.1	1727.5	1707.7	1735
Line amperes	2.86	3.32	4.01	4.84	5.83	7.01	5.43


ABB Motors and Mechanical Inc.

WINDING # 35WGG590

Typical performance - not guaranteed values.

1 HP 1 PH 60 HZ 1745 RPM 230 V 3526LC

TORQUES (LB-FT): PO=10.6 PU=7.64 LR=11.7 LRA=40



AC Induction Motor Performance Data

Record # 101477

Typical performance - not guaranteed values

Winding: 35WGG590-R001			Type: 3526LC		Enclosure: TEFC			
Nameplate Data			208 V, 60 Hz: High Voltage Connection					
Rated Output (HP)		1	Full Load Torque		3.056 LB-FT			
Volts		115/208-230	Start Configuration		direct on line			
Full Load Amps		9.8/5.1-4.9	Breakdown Torque		6.76 LB-FT			
R.P.M.		1745	Pull-up Torque		5.4 LB-FT			
Hz	60	Phase	1	Locked-rotor Torque		7.69 LB-FT		
NEMA Design Code		L	KVA Code		L			
Starting Current		35.1 A		No-load Current			2.02 A	
Service Factor (S.F.)		1.15		Line-line Res. @ 25°C			2.6174 Ω A Ph 1.4374 Ω B Ph	
NEMA Nom. Eff.		78	Power Factor		90		Temp. Rise @ Rated Load	50°C
Rating - Duty		40C AMB-CONT		Temp. Rise @ S.F. Load			63°C	
S.F. Amps		11/5.9-5.5						

Load Characteristics 208 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	62	78	86	90	92	93	91
Efficiency	63.7	76.2	79.3	79.1	76.4	71.7	77.5
Speed	1782.4	1767.7	1751.1	1730.8	1705.4	1670.8	1716
Line amperes	2.34	3.04	3.95	5.04	6.38	8.09	5.84

ABB Motors and Mechanical Inc.

WINDING # 35WGG590

Typical performance - not guaranteed values.

1 HP 1 PH 60 HZ 1745 RPM 208 V 3526LC

TORQUES (LB-FT): PO=6.76 PU=5.4 LR=7.69 LRA=35.1

