



Customer information packet

CWDM3561TP

3HP, 1645RPM, 3PH, 60HZ, 143TC, 3540M, TEFC, F3

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	143TC
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	3.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	4.300 A @ 460.0 V 8.600 A @ 230.0 V 8.800 A @ 208.0 V
Design Code	D
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	81.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	4.3 a

Part detail

Revision	N
Type	AC
Mech. spec.	35E2678
Base	
Status	PRD/A
Elec. spec.	35WGG301
Layout	35LYE2678
Eff. date	03-28-2025
CD Diagram	CD0005
Poles	04
Leads	9#18
Proprietary	False
Created date	10-01-2021

Insulation Class	H
Inverter Code	Not Inverter
KVA Code	H
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3540M
Mounting Arrangement	F3
Number of Poles	4
Overall Length	15.54 IN
Power Factor	80
Product Family	Wash Down
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1645 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1496L									
CAT.NO.	CWDM3561TP								
SPEC.	35E2678G301G1								
HP	3								
VOLTS	230/460								
AMP	8.2/4.1								
RPM	1690								
FRAME	143TC		HZ	60			PH	3	
SER.F.	1.00	CODE	H	DES	D	CLASS	H		
NEMA-NOM-EFF	81.5	PF	80						
RATING	40C AMB-CONT								
CC									
DE	6205		ODE	6203					
ENCL	TEFC	SN							

AC Induction Motor Performance Data

Record # 86945

Preliminary Data Sheet

Winding: 35WGG301-R001			Type: 3540M		Enclosure: TEFC		
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		3	Full Load Torque		9.54 LB-FT		
Volts		230/460	Start Configuration		direct on line		
Full Load Amps		8.6/4.3	Breakdown Torque		34.9 LB-FT		
R.P.M.		1655	Pull-up Torque		34.8 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		39.2 LB-FT	
NEMA Design Code		D	KVA Code	H	Starting Current		26 A
Service Factor (S.F.)		1	No-load Current		2.25 A		
NEMA Nom. Eff.		81.5	Power Factor	80	Line-line Res. @ 25°C		5.66 Ω
Rating - Duty		40C	AMB-CONT		Temp. Rise @ Rated Load		105°C
					Locked-rotor Power Factor		70.6
					Rotor inertia		0.289 lb-ft²

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	37	59	72	79	84	86
Efficiency	80.2	85.1	85	82.7	79.5	75.5
Speed	1768	1736	1701	1658	1610	1553
Line amperes	2.39	2.83	3.46	4.29	5.27	6.47

ABB Motors and Mechanical Inc.

WINDING # 35WGG301

Typical performance - not guaranteed values.

3 HP 3 PH 60 HZ 1655 RPM 460 V 3540M

TORQUES (LB-FT): PO=34.9 PU=34.8 LR=39.2 LRA=26





