



Customer information packet

D2507R

7.50HP, 1750RPM, DC, 2113ATY, TEFC,

Specifications

Enclosure	TEFC
Frame	SC2113ATZ
Frame Material	Exposed Laminations
Output Power	7.500 HP
Agency Approvals	CCSA US
Ambient Temperature	40 °C
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Feedback Device	NO FEEDBACK
Field Winding Type	STAB SHUNT
Frame Prefix	SC
Heater Indicator	No Heater
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F1
Overall Length	32.19 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger

Part detail

Revision	-
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	G6313A A
Layout	609951-013
Eff. date	04-13-2015
CD Diagram	406770-001
Poles	00
Leads	
Proprietary	False
Created date	04-10-2015

Nameplate


000613006HP									
CAT.NO.	D2507R	SPEC NO.		T21S0301					
FR	SC 2113ATZ	HP	7.5		DUTY		CONT		
ENCL.	TEFC	RPM	1750/ 2300		S.F.		1.0		
ENCL MOD		VOLTS		240		INSUL		F	
MAX SAFE SPEED	4500	AMPS	27.00		AMB.		40		
FIELD DATA		SER.NO.							
WINDING	STAB SHUNT	POWER CODE		C					
VOLTS	150	D.E. BRG.		50BC03J30X					
MAX AMPS @ 25 C	3.25	O.D.E. BRG.		45BC02J30X					
HOT AMPS	2.19/ 1.58	MIN. AMB.		0		TYPE		TR	
BRUSH:419904051AB									

609951-013

INDUSTRIAL DIRECT CURRENT MOTORS
AND GENERATORS - RPM III

ENCLOSURE: TOTALLY ENCLOSED
MOUNTING: FOOT
METHOD OF DRIVE: COUPLED OR BELTED
COOLING: FAN COOLED
ACCESSORIES: PROVISION FOR
TACHOMETER MOUNTING
ONLY WHEN SPECIFIED

FRAMES SC2113ATZ THRU LC2812ATZ



DIMENSIONS ARE IN INCHES															
FRAME	A	BK (1)	E	G	H	HG	J	O	P	T	BA	K	FK	BK	FAK (6)
SC2113ATZ-LC2113ATZ	10.25	5.25	4.25	.44	.44	1.38	1.75	11.62	12.75	1.38	3.50	5.19	6.81	2.38	9.750
SC2512ATZ-LC2512ATZ	12.31	6.25	5.00	.50	.56	1.62	2.00	13.62	14.75	1.94	4.25	6.06	8.00	3.00	11.250
MC2812ATZ-LC2812ATZ	13.78	7.00	5.50	.62	.56	1.88	2.75	15.06	16.12	2.31	4.75	6.75	9.19	3.50	N/A

FRAME	C	B	BS	2F	DRIVE END SHAFT AND KEY						WT. LBS.
					N	N-V	U(2)	V	R(3)	SR	
SC2113ATZ	32.19	22.50	11.38	18.00	4.00	3.75	1.875	3.50	1.591	500	2.50 355
MC2113ATZ	33.44	23.75	12.62	18.00	4.00	3.75	1.875	3.50	1.591	500	2.50 380
LC2113ATZ	35.06	25.38	14.25	18.00	4.00	3.75	1.875	3.50	1.591	500	2.50 410
SC2512ATZ	35.94	25.06	12.06	20.00	4.50	4.25	2.125	4.00	1.845	500	3.00 555
MC2512ATZ	37.44	26.56	13.56	20.00	4.50	4.25	2.125	4.00	1.845	500	3.00 590
LC2512ATZ	38.94	28.06	15.06	20.00	4.50	4.25	2.125	4.00	1.845	500	3.00 630
MC2812ATZ	41.62	29.94	14.25	22.00	5.00	4.75	2.375	4.50	2.021	625	3.50 835
LC2812ATZ	43.88	32.19	16.50	22.00	5.00	4.75	2.375	4.50	2.021	625	3.50 900

- (1) "B" DIMENSION WILL NOT BE EXCEEDED. SHIMS UP TO .03 INCHES IN THICKNESS ARE USUALLY REQUIRED FOR COUPLED OR GEARED MACHINES.
(2) "U" VARIES----+.000 --.001
(3) "2F" VARIES----+.000 --.015
(4) TERMINAL BOX VARIES WITH H.P. FOR DIMENSIONS "AA", "AB", "AC", "AF", "X" AND "Y". SEE DRAWING NUMBER 609959-1.
(5) WALLS OR OBSTRUCTIONS MUST NOT ENCRDACH ON AIR INLET SPACE "XC".
(6) "FAK" VARIES +.005 --.000----FACE RUNOUT AND ECCENTRICITY .007 MAX. T.I.R.
(7) "FZK" VARIES +.005 --.005----FACE RUNOUT AND ECCENTRICITY .007 MAX. T.I.R.
(8) STUB SHAFT SUPPLIED ONLY WHEN SPECIFIED. KEY SIZE .188 X .188 X 1.00
(9) FOR RE-045 OR SPY PROVISIONS ON "C2812" ADD 1.00 TO "LL" DIMENSION.
TERMINAL BOX CAN BE ROTATED FOR LEAD OUTLET AT TOP, SIDES OR BOTTOM.
TERMINAL BOX LOCATED ON OPPOSITE SIDE WHEN F-2, W-1, W-4, W-5, W-7, OR C-1 MOUNTING IS SPECIFIED. BOX LOCATED ON TOP WHEN SPECIFIED.
MOTOR WEIGHT MAY VARY 15% FOR NON-STANDARD RATINGS AND/OR ACCESSORIES.
IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT FACTORY.

TACHOMETER	LL
BC-42	4.25
BC-46	
RD-11	
RD-12	
RD-51	
RD-61	3.80 1.12
RE-62	
M627, M628	
M727, M737	SEE NOTE (9)
M738	
DYNAPAR 74S	SEE NOTE (9)
RE-045	
SPY	

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.


REV. DESC: LOADED TO BUS	VERSION: 00	TDR: 000000577407
REV. LTR: -	REVISED: 11:02:01 01/26/2011	BY: CONNAS
FILE: \RGG\00015\557		
MTL: -		

BALDOR
DIMENSION DRAWING, SC2113ATZ - LC2812ATZ, TEFC, FOOT MTG
SH 1 of 1


609951-013

609959-001

INDUSTRIAL DIRECT CURRENT MOTORS
AND GENERATORS - RPM III
TERMINAL BOX DIMENSIONS
STANDARD SIZE AND ONE SIZE LARGER
FRAMES C2113ATZ THRU C2815ATZ



DIMENSIONS ARE IN INCHES



STEEL TERMINAL BOX DIMENSIONS																						
FRAME SIZE	MAX. AMPS	STANDARD SIZE					PART NUMBER		ONE SIZE LARGER					PART NUMBER								
		AB 3/4 & 1"	AC 8.97	AF 1.94	X 4.38	Y 5.00	AB 1-1/4 & 1-1/2	AC 10.03	AF 2.50	X 5.50	Y 6.12	AB 1-1/2 & 2"	AC 11.16	AF 3.19	X 7.00	Y 7.62						
C2113ATZ	40	3/4 & 1"	8.97	1.94	4.38	5.00	705028-1-R	1-1/4 & 1-1/2	10.03	8.03	2.50	5.50	6.12	705030-1-R	11.16	8.41	3.19	7.00	7.62	705030-1-R		
C2115ATZ (2)	96	1-1/4 & 1-1/2	10.03	8.03	2.50	5.50	6.12	705029-1-R	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	705030-1-R	11.16	8.41	3.19	7.00	7.62	705030-1-R	
C2514ATZ	40	3/4 & 1-1/2	11.16	8.41	3.19	7.00	7.62	705030-1-R	2" & 2-1/2	11.16	8.41	3.19	7.00	7.62	705030-1-R	11.16	8.41	3.19	7.00	7.62	705030-1-R	
C2514ATZ	96	1-1/4 & 1-1/2	10.03	8.53	1.94	4.38	5.00	7.62	705028-1-R	1-1/4 & 1-1/2	11.09	9.09	2.50	5.50	6.12	705029-1-R	11.09	9.09	2.50	5.50	6.12	705029-1-R
C2514ATZ (2)	208	1-1/2 & 2"	11.09	9.09	2.50	5.50	6.12	705029-1-R	2" & 2-1/2	12.22	9.47	3.19	7.00	7.62	705030-1-R	12.22	9.47	3.19	7.00	7.62	705030-1-R	
C2815ATZ	155	2"	14.03	10.53	4.23	8.44	7.23	748747-1-R	2" & 2-1/2	14.47	11.22	4.23	8.44	7.23	748748-1-R	14.47	11.22	4.23	8.44	7.23	748748-1-R	
C2815ATZ (2)	259	3"	14.47	11.22	4.23	8.44	7.23	748747-2-R	3"	15.91	11.84	5.38	10.56	9.00	702508-3-R	15.91	11.84	5.38	10.56	9.00	702508-3-R	
C2815ATZ (2)	259	4"	15.91	11.84	5.38	10.56	9.00	702508-3-R	4"	16.72	13.47	7.00	12.75	15.00	702509-1-C	16.72	13.47	7.00	12.75	15.00	702509-1-C	

CAST IRON TERMINAL BOX DIMENSIONS															
FRAME SIZE	MAX. AMPS	STANDARD SIZE					PART NUMBER			ONE SIZE LARGER			PART NUMBER		
		AA3/4	AB	AC	AF	X	Y	Z	AA3/4	AB	AC	AF	X	Y	Z
C2113ATZ	18	3/4	10.03	8.03	2.50	5.00	5.75	705028-2-S	1	10.03	8.03	2.50	5.00	5.75	705028-2-T
C2115ATZ	40	1"	10.03	8.03	2.50	5.00	5.75	705028-2-T	1	10.97	8.53	3.00	6.00	7.00	705029-2-R
C2115ATZ	96	1-1/2	10.97	8.53	3.00	6.00	7.00	705029-2-R	2"	10.97	8.53	3.00	6.00	7.00	705029-2-S
C2115ATZ	208	1-1/2	10.97	8.53	3.00	6.00	7.00	705029-2-S	2"	12.66	8.91	3.62	7.88	9.25	705030-2-R
C2512ATZ	18	3/4	11.09	9.09	2.50	5.00	5.75	705028-2-T	1	11.09	9.09	2.50	5.00	5.75	705028-2-T
C2512ATZ	40	1"	11.09	9.09	2.50	5.00	5.75	705028-2-T	1	12.03	9.59	3.00	6.00	7.00	705029-2-R
C2514ATZ	96	1-1/2	12.03	9.59	3.00	6.00	7.00	705029-2-R	2"	12.03	9.59	3.00	6.00	7.00	705029-2-S
C2514ATZ	208	2"	12.03	9.59	3.00	6.00	7.00	705029-2-S	2-1/2	13.72	9.97	3.62	7.88	9.25	705030-2-R
C2812ATZ	128	2"	12.78	10.34	3.00	6.00	7.00	705030-1	3"	14.47	10.72	3.62	7.88	9.25	767000-R8
C2812ATZ	185	3"	14.47	10.72	3.62	7.88	9.25	767000-R8	4"	14.47	10.72	3.62	7.88	9.25	767000-R8
C2813ATZ	259	4"	15.78	11.59	4.12	9.50	10.50	767000-R8	5" (4)	18.59	13.34	7.00	12.75	15.00	766700-S

CONDUIT BOX DIMENSIONS WITH TERMINAL BOARDS (IEC TYPE BOX)										
FRAME SIZE	AMPS	STANDARD SIZE					PART NUMBER	PART NUMBER		
		AB	AC	AF	X	AA			Y	
C210	100	10.71	8.98	2.72	7.48	---	7.48	706310-56-A	706310-225-R	
	200	11.26	9.25	3.35	8.82	---	8.82	706310-56-B	706310-226-R	
	100	11.30	9.57	2.72	7.48	---	7.48	706310-56-A	706310-225-R	
C250	200	11.85	9.84	3.35	8.82	---	8.82	706310-56-B	706310-226-R	
	400	17.48	12.75	6.20	14.39	---	14.39	706310-63-B & 706310-636	706310-63-B & 706310-636	
	800	17.48	12.75	6.20	14.39	---	14.39	706310-63-B & 706310-636	706310-63-B & 706310-636	
C280	200	12.60	10.59	3.76	8.82	---	8.82	706310-56-B	706310-226-R	
	400	18.27	13.54	6.20	14.39	---	14.39	706310-63-B & 706310-636	706310-63-B & 706310-636	
	800	18.27	13.54	6.20	14.39	---	14.39	706310-63-B & 706310-636	706310-63-B & 706310-636	
	1600	18.27	13.54	7.68	15.35	---	15.35	706310-63-C	706310-63-C	

OPTIONAL AUXILIARY CONDUIT BOX DIMENSIONS (MAXIMUM)											
FRAME SIZE	XAB	XY	PART NUMBER	FRAME SIZE	XAB	XY	PART NUMBER	FRAME SIZE	XAB	XY	PART NUMBER
C210	7.38	4.25	602007-26-A	C210	10.88	8.00	706310-3-B	C210	10.88	8.00	706310-3-B
C250	8.44	4.25	602007-26-A	C250	11.88	8.00	706310-3-B	C250	11.88	8.00	706310-3-B
C280	9.12	4.25	602007-26-A	C280	12.62	8.00	706310-3-B	C280	12.62	8.00	706310-3-B

(1) 1/4" CONDUIT.
(2) RACES PROVIDED WITH DOUBLE KNOCKOUT.
(3) 1/4" PIPE TAP.

(4) TERMINAL BOX 76870-S AND 76870-98 EXTENDS BELOW MOTOR FEET.
TERMINAL BOX 76870-S AND 76870-98 EXTENDS BELOW MOTOR FEET.
DR - C-1 MOUNTING IS SPECIFIED. BOX LOCATED IN TOP WHEN SPECIFIED.
FOR "X"/PARTIAL BOX DIMENSIONS SEE 609959-2.
FOR MILL TYPE TERMINAL BOX DIMENSIONS SEE 609959-3.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: ADD 706310-63G C/BOX TO C250 AND C280 FRAMES

REV. LTR: A

VERSION: 01

TDR: 000000816512

FILE: \RGG\00021\153

REVISED: 03: 09: 09 09/06/2013

MTL: -

BY: RGGWT

BALDOR


DIMENSION SHEET

SH 1 of 1

609959-001

406770-001

CONNECTION DIAGRAM D-C MOTOR - STAB. SHUNT



ARMATURE AND FIELD EXTERNAL CONNECTIONS

WARNING- SEE NOTE 8 FOR GROUNDING INSTRUCTIONS



ROTATION FACING COMMUTATOR END

1. CAUTION — ARMATURE AND SERIES FIELD MAY HAVE MULTIPLE LEADS. CONNECT ALL LUGS WITH THE SAME MARKING TOGETHER.
2. OPTIONAL SERIES FIELD IS MARKED S3 AND S4. FOR CUMULATIVE SERIES FIELD, CONNECT S3 TO S2 AND CONNECT S4 TO NEGATIVE. FOR DIFFERENTIAL SERIES FIELD CONNECT S4 TO S2 AND S3 TO NEGATIVE.
3. OPTIONAL CONTROL SIGNAL LEAD IS MARKED AX2. ALWAYS TAKE INTERPOLE DROP BETWEEN A2 AND AX2. NOTE: NEMA DESIGNATION FOR AX2 IS LETTER C.
4. SPACE HEATERS, WHEN PROVIDED, WILL HAVE LEADS MARKED H1 AND H2, H3, H4, ETC.
5. THERMAL PROTECTOR, WHEN PROVIDED, WILL HAVE LEADS MARKED P1 AND P2, P3, P4, ETC.
6. WINDING RTD'S, WHEN PROVIDED, WILL HAVE LEADS MARKED TD1, TD2, & TD3.
7. BRUSH WEAR SENSOR, WHEN PROVIDED, WILL HAVE LEAD MARKED W1.
8. WARNING — MOTOR MUST BE GROUNDED TO PREVENT SERIOUS INJURIES TO PERSONNEL. GROUND THE MOTOR PER IEC, NATIONAL ELECTRICAL CODE AND ANY APPLICABLE LOCAL ELECTRICAL CODES. A TAPPED HOLE IS PROVIDED IN THE CONDUIT BOX, ON THE FOOT. FRAME BRACE OR OPPOSITE DRIVE END BRACKET, ADJACENT TO THE TERMINAL BOX FOR MOTOR GROUNDING. GROUND LEAD, WHEN PROVIDED, WILL BE GREEN.

CUSTOMER _____ CUSTOMER RELIANCE
ORDER NO. _____ S.D. NO. _____

406770-001

BALDOR

D-C MOTOR CONNECTION DIAGRAM STAB. SHUNT

SH 1 of 1

REV. DESC: DELETED DUPLICATE WORDS FROM NOTE 8

REV. LTR: A

VERSION: 01

TDR: 000000970330

FILE: \RSN\00026\422

REVISÉ: 10:19:12 03/11/2016

BY: RAGTBM

MTL: —