



Customer information packet

D50250P2-BV

250HP, 1750/1900RPM, DC, 504-6AT, DPBV, F1, N

Specifications

Armature Voltage	500 V
Base Speed	1750 rpm
Enclosure	DPBV
Field Voltage	150 V
	300 V
Frame	504AT
Frame Material	Steel
Output Power	250.000 HP
Agency Approvals	CSA
Ambient Temperature	40 °C
Armature Current	405.0 a
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Field Winding Type	STR. SHUNT
Heater Indicator	No Heater
Insulation Class	F
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F1
Overall Length	45.75 IN
Service Factor	1.00
Shaft Diameter	3.249 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger


Part detail

Revision	D
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	K0112A A
Layout	2339-4
Eff. date	03-22-2022
CD Diagram	15209
Poles	00
Leads	
Proprietary	False
Created date	04-09-2015

Nameplate

NP1734									
CAT.NO.	D50250P2-BV		MODEL		T50R8003				
HP	250	RPM	1750/1900		FRAME		504-6AT		
ARM V	500		ARM A		405.00	WOUND		STR. SHUNT	
FLD V	150/300	FLD A	14.58-9.70/7.29-4.85						
CONN			OHMS				CL	F	
ENCL	DPBV	DUTY	CONT				MX AMB	40	
P CODE	C	CTSR					SER.F.	1.0	
S/N			E/S		K0112A A				
	BRUSH:50034-2								
O.D.E. BRG.	6216	D.E. BRG.	6218	BRUSH				QTY	

2339-4



.1245 DIA.	FOOT MOUNTING							D.E. SHAFT EXTENSION					DRIVE KEY		FRAME						
	FRAME	BA	E	504 2F	506 2F	G	H	J	N	N-W	U	V	W	KEY-SQ.	KEY-LONG	A	B	C	D	O	P
	504-6AT	8.50	10.00	16.00	20.00	1.18	1.188	4.50	6.76	6.57	3.250 ¹	6.32 ⁴	.19	.750	5.25	24.88	22.88	45.75	12.50 ³	24.91	24.81

	CONDUIT BOX							BLOWER								APPROXIMATE WEIGHT	
FRAME	AA	AB	AC	AF	BS	XL	XN	SIZE	XB	XD	XE	XH	XM	XJ	XK		XS
504—6AT	3	20.65	16.81	2.62	13.25	11.63	7.76	9	25.50	28.31	20.94	10.75	5.50	12.38	15.25	3.75	1957


- 1) SHAFT DIAMETERS ABOVE 1.500 TOLERANCE +.0000 - .0010
- 2) SHAFT DIAMETERS ABOVE 1.625 RUNOUT .003 T.I.R. MAX.
- 3) 'D' DIMENSION TOLERANCE +.000 - .060
- 4) 'V' DIMENSION IS MAX. HUB LENGTH ON SHAFT
- 5) CONDUIT BOX CAN BE ROTATED IN 90° STEPS ON ITS OWN AXIS.
- 6) ALL DIMENSIONS NOT NOTED ARE NOMINAL DIMENSIONS CONSULT FACTORY FOR TOLERANCES.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT MOTOR PERFORMANCE IS SUITABLE IN THE APPLICATION.

REV. DESC: NEW				BALDOR ELECTRIC Co.			
REV. LTR: -	BY: MBT	REVISED: 08:49:51 04/08/2004	TDR: 328876				
4-6222		FILE: CHB00011581	REF: 2339-4				
MTL: -				DIM SHEET, 504-6AT, DPBV, 504/506 MTG, LM9 BLOWER			

2339-4

15209



NOTE:
MATERIAL .005 MINIMUM FULL HARD ALUMINUM DULL FINISH.
TEMP. RANGE -20°C TO +125°C MAXIMUM.
FOR INDOOR AND OUTDOOR MOUNTING BACK.
METAL, PRESSURE SENSITIVE BACK. MUST MEET CSA STANDARD.
THE CSA IDENTIFYING MARK OF THE LABEL MANUFACTURER MUST APPEAR IN THE UPPER RIGHT HAND CORNER AS INDICATED.

UNLESS OTHERWISE SPECIFIED,
BREAK ALL SHARP EDGES .010/.020.
REMOVE ALL BURRS.

TOLERANCES

.X ±.015	FRACTIONS ±1/32
.XX ±.010	RADI ±1/16
.XXX ±.005	ANGLES ±1°

MATL: NOTED			
REV:	G	CHANGE ALL "NAMEPLATE" TEXT TO "LABEL"	
60Z91		SCALE: —	BY: BKW
		FILE: CHB00002485	REVISED: 02/19/97
		TDR: 0115147	

BALDOR ELECTRIC Co.

LABEL, CONNECTIONS AND TERMINAL MARKINGS DC

15209