



Customer information packet

DMG2310

10KW, 2500RPM, DC, 219AT, DPFG, F2

Specifications

Armature Voltage	230 V
Base Speed	2500 rpm
Enclosure	DPFG
Field Voltage	230 V
Frame Material	Steel
Output Power	10.000 KW
Agency Approvals	CSA
Ambient Temperature	40 °C
Armature Current	43.5 a
Bearing Grease Type	Polyrex EM (-20F +300F)
Drip Cover	No Drip Cover
Duty Rating	CONT
Feedback Device	NO FEEDBACK
Field Winding Type	COMPOUND
Heater Indicator	No Heater
Insulation Class	F
Lifting Lugs	Standard Lifting Lugs
Motor Standards	NEMA
Mounting Arrangement	F2
Overall Length	24.50 IN
Service Factor	1.00
Shaft Diameter	1.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Slinger Indicator	No Slinger
Thermal Device - Bearing	None

Part detail

Revision	B
Type	DC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	K0002A
Layout	1486
Eff. date	08-18-2022
CD Diagram	
Poles	00
Leads	
Proprietary	False
Created date	12-12-2019



Nameplate

15405										
CAT.NO.	DMG2310		MODEL NO.		T21S8001					
KW	10 KW	RPM	2500		FRAME		0219AT			
ARM VOLTS	230		ARM AMPS	43.50	WOUND		COMPOUND			
FIELD VOLTS	230		FIELD AMPS	.81						
FIELD CONN.		OHMS	188.5		INSUL. CLASS				F	
ENCL	DPFG	DUTY	CONT		MAX AMBIENT			40		
SERVICE FACTOR	1.0									
S/N			E/S	K0002A						
	-									
O.D.E. BRG.	6207	D.E. BRG.	6207	BRUSH		150986-21-1			QTY	2

Accessories

Part number	Description	Multiplier
91EP5000A01	C-FACE CONVERSION KIT FOR STOCK MTR,FR 2	P1

REL S.O.	FRAME	RATING	RPM	ARM. VOLTS	ARM. AMPS
	219AT	10.0HP	2500	230	43.5
WINDING TYPE		S.F.	ENCL.	AMB °C/INSUL	DUTY
STAB. SHUNT		1.0	DPG	40/F	CONT
					230
POWER CODE	TYPE	WK ² (LB-FT ²)		HOT ARM.CIR.RES.	FLD. AMPS@25 °C
A	T	1.201		1.02	1.21
					261
ARM. CIR. IND. (mh)	FIELD IND. (H)	COOLING AIR(CFM/IN H ²⁰)			TURNS PER COIL SHUNT/SERIES
4.23	10.2	-/-			2300/11.5
LOAD PERFORMANCE					
LOAD	AMPERES	TORQUE IN OZ.-FT.	OUTPUT IN HP	RPM	% EFFICIENCY
NO LOAD	4971	0	0	4220	0
1/4	11	0	0	3978	0
2/4	22	0	0	3717	0
3/4	33	0	0	3466	0
4/4	44	0	0	3222	0
0.L.	65	0	0	2751	0
RPM VS. FIELD AMPS					
FIELD AMPS	RPM N.L.	RPM F.L.	Eg N.L. @ BASE SPEED	Eg F.L. @ BASE SPEED	
.878	4219	3222	134	134	
6.22	-184	2929	333	234	
11.5	-34	2604	333	260	
16.9	-15	2831	333	266	
22.2	4219	3222	134	134	
REMARKS: TYPICAL DATA					
		DR. BY E. GILLLOT CK. BY B. GRANT APP. BY R. ERICHER DATE 11-19-07		D-C MOTOR PERFORMANCE DATA DK0002A ISSUE DATE 11-19-07	



1486

FOOT MOUNTING							D.E. SHAFT EXTENSION					DRIVE KEY		FRAME					
FRAME	BA	E	2F	G	H	J	N	N-W	U	V	W	KEY-SQ.	KEY-LONG	A	B	C	D	O	P
1810AT	2.75	3.75	11.00	.38	.406	1.50	2.90	2.77	1.125 ¹	2.50 ³	.13	.250	1.38	8.75	12.25	21.46	4.50 ²	9.00	9.00
219AT	3.50	4.25	11.00	.50	.406	2.00	3.00	2.75	1.375 ¹	2.50 ³	.25	.312	1.75	10.38	12.00	24.50	5.25 ²	10.47	10.44
258AT	4.25	5.00	12.50	.69	.531	2.25	3.44	3.25	1.625 ¹	3.00 ³	.19	.375	2.31	12.38	14.00	26.50	6.25 ²	12.47	12.44
259AT	4.25	5.00	14.00	.69	.531	2.25	3.44	3.25	1.625 ¹	3.00 ³	.19	.375	2.31	12.38	15.50	28.00	6.25 ²	12.47	12.44
288AT	4.75	5.50	14.00	.69	.531	2.50	3.91	3.75	1.875 ¹	3.50 ³	.16	.500	2.50	13.81	15.62	32.00	7.00 ²	13.88	13.75
328AT	5.25	6.25	16.00	.81	.656	3.00	4.40	4.25	2.125 ¹	4.00 ³	.15	.500	3.12	15.88	17.75	34.63	8.00 ²	15.94	15.88
329AT	5.25	6.25	18.00	.81	.656	3.00	4.40	4.25	2.125 ¹	4.00 ³	.15	.500	3.12	15.88	19.75	36.63	8.00 ²	15.94	15.88

CONDUIT BOX								APPROXIMATE WEIGHT
FRAME	AA	AB	AC	AF	BS	XL	XN	
1810AT	3/4NPT	INTEGRAL WITH ENDPLATE						195
219AT	3/4-1	7.91	6.44	2.44	9.38	3.81	3.12	260
258AT	1-1/4	9.35	7.72	2.94	9.75	4.94	4.00	366
259AT	1-1/4	9.35	7.72	2.94	11.25	4.94	4.00	411
288AT	1-1/4	11.88	9.25	5.00	12.64	7.88	5.25	566
328AT	2	12.94	10.32	5.00	13.68	7.88	5.25	775
329AT	2	12.94	10.32	5.00	15.68	7.88	5.25	884

- 1) SHAFT DIAMETERS TO 1.500 TOLERANCE $+.0000 - .0005$
SHAFT DIAMETERS ABOVE 1.500 TOLERANCE $+.0000 - .0010$
SHAFT DIAMETERS TO 1.625 RUNOUT .002 T.I.R. MAX.
SHAFT DIAMETERS ABOVE 1.625 RUNOUT .003 T.I.R. MAX.
- 2) 'D' DIMENSION TOLERANCE $+.000 - .030$
- 3) 'V' DIMENSION IS MAX. HUB LENGTH ON SHAFT
- 4) CONDUIT BOX CAN BE ROTATED IN 90° STEPS ON ITS OWN AXIS.
- 5) ALL DIMENSIONS NOT NOTED ARE NOMINAL DIMENSIONS CONSULT FACTORY FOR TOLERANCES.

FOR F1 OR F2 CONDUIT BOX
LOCATION SEE SALES ORDER

MATL: -

REV: C CORRECTED "A" DIMENSIONS

9871

SCALE: 0.08

BY: TBM

REVISED: 09/10/96

FILE: CHB00003091

TDR: 0104915

BALDOR ELECTRIC Co.

DIM SHEET, 1810AT THRU 329AT GENERATORS

1486

