



Customer information packet

DRX14124T

1HP, 3450//2875RPM, 3PH, 60HZ, 143T, XPFC, F1

Class - CLI GP C,D

Division - Division I

Specifications

Enclosure	XPFC
Frame	143T
Frame Material	Steel
Frequency	50.00 Hz 60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	1.000 HP @ 60 HZ .750 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 190.0 V @ 50 HZ 230.0 V @ 60 HZ 380.0 V @ 50 HZ
Agency Approvals	UL CSA EEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	1.300 A @ 380.0 V 1.400 A @ 460.0 V 2.600 A @ 190.0 V 2.800 A @ 230.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT

Part detail

Revision	A
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	35WGS921
Layout	35LYX081
Eff. date	06-15-2020
CD Diagram	CD0005
Poles	02
Leads	9#18
Proprietary	False
Created date	06-20-2019

Efficiency @ 100% Load	84.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	1.3 a
Insulation Class	F
Inverter Code	Inverter Duty
IP Rating	NONE
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3516M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	14.22 IN
Power Factor	82
Product Family	General Purpose
Pulley Face Code	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.00
Shaft Diameter	0.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	3450 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1401XPSLEV												
NO.						CC	010A					
S/N						TEMP CODE	T3C					
SPEC.	35-0000-0192					INV.TYPE	PWM					
CAT.NO.	DRX14124T					C HP FR	60	C HP TO	90			
HP	1//.75					CT HZ FROM	6	CT HZ TO	60			
VOLTS	230/460//190/380					VT HZ FROM	6	VT HZ TO	60			
AMPS	2.8/1.4//2.6/1.3				MAG CUR	1.4/.7						
RPM	3450//2875				MX RPM	5400						
HZ	60//50	PH	3	CL	F	NOM.EFF.	84					
SER.F.	1.00	DES	B	SL HZ	2	WK2	0.036					
FRAME	143T	RATING		40C AMB-CONT								
	55C AMB @ 1.0SF											
	1.15 SF SINEWAVE				NEMA MG-1 PT 5,IP55							

AC Induction Motor Performance Data

Record # 76574

Typical performance - not guaranteed values

Winding: 35WGS921-R013		Type: 3516M	Enclosure: XPFC	
Nameplate Data		460 V, 60 Hz: High Voltage Connection		
Rated Output (HP)	1	Full Load Torque	1.5 LB-FT	
Volts	230/460//190/380	Start Configuration	direct on line	
Full Load Amps	2.8/1.4//2.6/1.3	Breakdown Torque	6.5 LB-FT	
R.P.M.	3450//2875	Pull-up Torque	4.8 LB-FT	
Hz	60//50 Phase	Locked-rotor Torque	5.7 LB-FT	
NEMA Design Code	B KVA Code	Starting Current	12.1 A	
Service Factor (S.F.)	1	No-load Current	0.68 A	
NEMA Nom. Eff.	84 Power Factor	Line-line Res. @ 25°C	15.2 Ω	
Rating - Duty	40C AMB-CONT	Temp. Rise @ Rated Load	33°C	
		Locked-rotor Power Factor	56.1	
		Rotor inertia	0.0443 LB-FT2	

Load Characteristics 460 V, 60 Hz, 1 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	45	65	77	83	87	87
Efficiency	70.3	80.5	83.9	84.6	84.6	83.7
Speed	3567	3539	3510	3479	3446	3410
Line amperes	0.75	0.9	1.09	1.33	1.56	1.88


ABB Motors and Mechanical Inc.

WINDING # 35WGS921

Typical performance - not guaranteed values.

1 HP 3 PH 60 HZ 3479 RPM 460 V 3516M

TORQUES (LB-FT): PO=6.5 PU=4.8 LR=5.7 LRA=12.1



AC Induction Motor Performance Data

Record # 76575

Typical performance - not guaranteed values

Winding: 35WGS921-R013		Type: 3516M	Enclosure: XPFC		
Nameplate Data		380 V, 50 Hz: High Voltage Connection			
Rated Output (HP)	1	Full Load Torque	1.36 LB-FT		
Volts	230/460//190/380	Start Configuration	direct on line		
Full Load Amps	2.8/1.4//2.6/1.3	Breakdown Torque	5.94 LB-FT		
R.P.M.	3450//2875	Pull-up Torque	4.9 LB-FT		
Hz	60//50	Phase	3	Locked-rotor Torque	5.82 LB-FT
NEMA Design Code	B	KVA Code	L	Starting Current	11.24 A
Service Factor (S.F.)			1	No-load Current	0.669 A
NEMA Nom. Eff.	84	Power Factor	82	Line-line Res. @ 25°C	15.2 Ω
Rating - Duty	40C AMB-CONT		Temp. Rise @ Rated Load		30°C
			Locked-rotor Power Factor		62.7
			Rotor inertia		0.0443 LB-FT2

Load Characteristics 380 V, 50 Hz, 0.75 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	45	65	76	82	87	87
Efficiency	65.3	76.9	80.7	82.1	82.1	81.4
Speed	2968	2942	2916	2887	2857	2824
Line amperes	0.731	0.867	1.04	1.26	1.46	1.76

ABB Motors and Mechanical Inc.

WINDING # 35WGS921

Typical performance - not guaranteed values.

0.75 HP 3 PH 50 HZ 2887 RPM 380 V 3516M

TORQUES (LB-FT): PO=5.94 PU=4.9 LR=5.82 LRA=11.24

