



Customer information packet

DRX32424T-5

40HP, 3540RPM, 3PH, 60HZ, 324TS, XPFC, F1

Class - CLI GP C,D

Division - Division I

Specifications

Enclosure	XPFC
Frame	324TS
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CLI GP C,D
Haz Area Division	Division I
Motor Letter Type	Three Phase
Output @ Frequency	40.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CSA EEV UL
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	6
Current @ Voltage	36.000 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	92.4 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	36.0 a
Insulation Class	F
Inverter Code	Inverter Duty

Part detail

Revision	E
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	12WGY734
Layout	12LYT060
Eff. date	12-10-2024
CD Diagram	CD0006
Poles	02
Leads	3#10
Proprietary	False
Created date	07-16-2019

IP Rating	NONE
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1252M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	30.50 IN
Power Factor	88
Product Family	Hazardous Location Motor
Pulley Face Code	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.00
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	3540 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	Normally Closed Thermostat
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1401XPSLEV													
NO.						CC	010A						
S/N						TEMP CODE			T3C				
SPEC.	12-0000-0856					INV.TYPE			PWM				
CAT.NO.	DRX32424T-5					C HP FR		60	C HP TO		90		
HP	40					CT HZ FROM			6	CT HZ TO		60	
VOLTS	575					VT HZ FROM			6	VT HZ TO		60	
AMPS	36				MAG CUR		9.1						
RPM	3540				MX RPM		5400						
HZ	60	PH	3	CL	F	NOM.EFF.		92.4					
SER.F.	1.00	DES	A	SL HZ	1	WK2		4.07					
FRAME	324TS	RATING		40C AMB-CONT									
	55C AMB @ 1.0 SF, 60C RISE												
	1.15SF ON SINEWAVE				NEMA MG-1 PT.5,IP55								

AC Induction Motor Performance Data

Record # 77603

Typical performance - not guaranteed values

Winding: 12WGY734-R002			Type: 1252M		Enclosure: XPFC	
Nameplate Data				575 V, 60 Hz: Single Voltage Motor		
Rated Output (HP)		40		Full Load Torque		59.3 LB-FT
Volts		575		Start Configuration		direct on line
Full Load Amps		36		Breakdown Torque		244 LB-FT
R.P.M.		3540		Pull-up Torque		83.5 LB-FT
Hz	60	Phase	3	Locked-rotor Torque		115 LB-FT
NEMA Design Code		A		KVA Code	H	
Service Factor (S.F.)		1		Starting Current		253 A
NEMA Nom. Eff.		92.4		Power Factor	88	
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load
S.F. Amps						Temp. Rise @ S.F. Load
						Locked-rotor Power Factor
						Rotor inertia

Load Characteristics 575 V, 60 Hz, 40 HP

% of Rated Load	25	50	75	100	125	150
Power Factor	68	84	89	91	91	91
Efficiency	84.6	90.4	91.8	92.6	92	91.4
Speed	3587	3574	3560	3547	3532	3516
Line amperes	12.9	19.6	27.4	35.7	44.7	54


ABB Motors and Mechanical Inc.


WINDING # 12WGY734

Typical performance - not guaranteed values.

40 HP 3 PH 60 HZ 3540 RPM 575 V 1252M


TORQUES (LB-FT): PO=244 PU=83.5 LR=115 LRA=253






CD0006

TYPICAL WYE-CONNECTED MOTOR



TYPICAL DELTA-CONNECTED MOTOR



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10:24:49 02/19/2019

BY: ENBRIRO

MTL: —

**BALDOR - RELIANCE®**

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1