



Customer information packet

ECP2276T-4

7.5HP, 1180RPM, 3PH, 60HZ, 254T, 0954M, TEFC, F

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	254T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR CCSA US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	1.0
Current @ Voltage	10.700 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.0 %
Electrically Isolated Bearing	Not Electrically Isolated
Enclosure Modification	Severe Duty Features
Feedback Device	NO FEEDBACK
Front Face Code	Standard

Part detail

Revision	AZ
Type	AC
Mech. spec.	09J371
Base	
Status	PRD/A
Elec. spec.	09WGY237
Layout	09LYJ371
Eff. date	09-16-2025
CD Diagram	CD0006
Poles	06
Leads	3#12
Proprietary	False
Created date	08-29-2010

Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	10.7 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	J
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	1800 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0954M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	24.78 IN
Power Factor	71
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1180 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None

Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3995ABBL													
CAT #		ECP2276T-4				SER				CC		010A	
SPEC		09J371Y237				RATING		40C AMB-CONT					
HZ		VOLTS		AMPS		RPM		HP		CODE		SF DES	
60		460		10.7		1180		7.5		J		1.15 A	
												PF	
												71 %	
												91 %	
PH		3		CL		F		MAX RPM		1800		MAX CORR KVAR	
												4.1	
												USABLE AT 208V	
												N/A	
IP55		FR		254T		ENCL		TEFC		DE BRG		6309	
												ODE BRG	
												6309	
GREASE		POLYREX EM						MTR WT		337		LBS	
USABLE AT		50HZ 5HP 380V 9.3A						SF1.0					
CL I DIV 2 GRPS A,B,C,D				CL I ZONE 2 GRPS				IIA,IIB,IIC				TEMP T	
												160 C	
1.0 SF ON PWM INVERTER				POWER		INV TEMP CL		180		C			
CHP		60-90		HZ		1.5:1		CT		1.0-60		HZ	
												60:1	
												VT	
												0-60	
												HZ	
												1000:1	
SPACE HEATER LEADS H1-H2:				TIE LIKE NUMBERS				TOGETHER					
V				A				W				MAX SPACE HEATER TEMP	

Accessories

Part number	Description	Multiplier
09-1309	C FACE KIT	A8
RB3001A01	MACH RETAINER RING 309/211 BRG	

AC Induction Motor Performance Data

Record # 47267

Typical performance - not guaranteed values

Winding: 09WGY237-R028			Type: 0954M		Enclosure: TEFC	
Nameplate Data				460 V, 60 Hz: Single Voltage Motor		
Rated Output (HP)		7.5		Full Load Torque		33.3 LB-FT
Volts		460		Start Configuration		direct on line
Full Load Amps		10.7		Breakdown Torque		99.5 LB-FT
R.P.M.		1180		Pull-up Torque		39.7 LB-FT
Hz	60	Phase	3	Locked-rotor Torque		58.4 LB-FT
NEMA Design Code		B		KVA Code	J	
Service Factor (S.F.)		1.15		No-load Current		5.52 A
NEMA Nom. Eff.		91		Power Factor	71	
Rating - Duty		40C		AMB-CONT		
S.F. Amps				Temp. Rise @ Rated Load		32°C
				Temp. Rise @ S.F. Load		42°C
				Rotor inertia		4.34 LB-FT2

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	33	53	65	71	74	75	73
Efficiency	84.9	90.6	91.8	91.4	91.4	90.5	91.6
Speed	1196	1192	1188	1183	1178	1173	1180
Line amperes	6.25	7.28	8.82	10.72	12.91	15.5	12.03


ABB Motors and Mechanical Inc.


WINDING # 09WGY237

Typical performance - not guaranteed values.




7.5 HP 3 PH 60 HZ 1180 RPM 460 V 0954M

TORQUES (LB-FT): PO=99.5 PU=39.7 LR=58.4 LRA=70.1





CD0006



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10: 24: 49 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1