



Customer information packet

ECP4104T-5

30HP, 1770RPM, 3PH, 60HZ, 286T, 1060M, TEFC, F1

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	286T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	30.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CCSA US CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	0.8
Current @ Voltage	29.000 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	93.6 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part detail

Revision	AJ
Type	AC
Mech. spec.	10H292
Base	
Status	PRD/A
Elec. spec.	10WGX453
Layout	10LYH292
Eff. date	09-29-2025
CD Diagram	CD0006
Poles	04
Leads	3#10
Proprietary	False
Created date	01-09-2013

Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	29.0 a
Insulation Class	F
Inverter Code	Inverter Duty
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	2700 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1060M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	28.00 IN
Power Factor	83
Product Family	Super-E Chemical Processing
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1770 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3241

CAT.NO.	ECP4104T-5	P/N					ENCLOSURE	TEFC		
SPEC.	10H292X453	CC	010A	FRAME	286T	S/N				
HP	30	CLASS	F	HZ	60	DES	A			
RPM	1770	RPM MAX	2700	PH	3	KVA-CODE	H			
VOLT	575	MOTOR WEIGHT	485							
AMP	29	SER.F.	1.15	PF	83	ODE BRG	6311	DE BRG	6311	
RATING	40C AMB-CONT	NEMA-NOM-EFF	93.6	GREASE	POLYREX EM					
					INV.TYPE	PWM				
TEMP CODE	T3C	INVERTER-TEMP-CODE	180							
TEMP =	160	C HP FR	60	C HP TO	90					
CT HZ FROM	0.8	CT HZ TO	60							
HTR-VOLTS	HTR-AMPS	HTR-WATTS	MAX. SPACE HEATER TEMP.				VT HZ FROM	O	VT HZ TO	60

Accessories

Part number	Description	Multiplier
10-1305ECP	C FACE KIT (C-FACE SWAP FOR ECP MOTOR)	A8

AC Induction Motor Performance Data

Record # 47184

Typical performance - not guaranteed values

Winding: 10WGX453-R018				Type: 1060M		Enclosure: TEFC		
Nameplate Data				575 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		30		Full Load Torque		89 LB-FT		
Volts		575		Start Configuration		direct on line		
Full Load Amps		29		Breakdown Torque		284 LB-FT		
R.P.M.		1770		Pull-up Torque		135 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		154 LB-FT		
NEMA Design Code		A		KVA Code	H		Starting Current	197 A
Service Factor (S.F.)		1.15		No-load Current		12.8 A		
NEMA Nom. Eff.		93.6		Power Factor	83		Line-line Res. @ 25°C	0.317 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		55°C		
S.F. Amps				Temp. Rise @ S.F. Load		67°C		
				Locked-rotor Power Factor		31.9		
				Rotor inertia		4.77 LB-FT2		

Load Characteristics 575 V, 60 Hz, 30 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	44	66	75	83	83	83	83
Efficiency	90.7	93.8	94.4	94.3	93.8	93.1	94
Speed	1794	1788	1782	1775	1768	1759	1771
Line amperes	14.4	18.4	24	28.8	36	43.2	33.1


ABB Motors and Mechanical Inc.


WINDING # 10WGX453

Typical performance - not guaranteed values.



30 HP 3 PH 60 HZ 1770 RPM 575 V 1060M

TORQUES (LB-FT): PO=284 PU=135 LR=154 LRA=197





CD0006



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10: 24: 49 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1