



Customer information packet

ECP44352T-4

350HP, 3575RPM, 3PH, 60HZ, 449TS, A44144M, TEF

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	449TS
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	350.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSAUSEEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Constant Torque Speed Range	30-60
Current @ Voltage	370.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.8 %
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T2C
Heater Indicator	No Heater
High Voltage Full Load Amps	370.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	G
Lifting Lugs	No Lifting Lugs
Motor Lead Quantity/Wire Size	6 @ 2/0 AWG
Motor Standards	NEMA

Part detail

Revision	F
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG6769
Layout	617427-006
Eff. date	01-15-2025
CD Diagram	416820-036
Poles	02
Leads	3#2/0 (02 per group)
Proprietary	False
Created date	09-11-2023

Motor Type	A44144M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	49.71 IN
Power Factor	93
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	2.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3575 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Nameplate


NP3238													
CAT NO	ECP44352T-4			SPEC NO.		P44G9709							
HP	350	AMPS	370		VOLTS		460		DESIGN	B			
FRAME	449TS	RPM	3575	HZ	60	AMB	40	SF	1.15				
D.E. BRG.DATA	6313		O.D.E. BRG.DATA			6313		PH	3	DUTY	CONT	INSUL.CLASS	F
D.E. BRG.	65BC03J30X			TYPE	P	ENCL	TEFC	CODE	G				
O.D.E. BRG.	65BC03J30X			POWER FACTOR			93	NEMA NOM EFFICIENCY			95.8		
3/4 LOAD EFF.	96.1		MAX CORR KVAR			18		GUARANTEED EFFICIENCY			95		
TEMP CODE	T2C	TEMP =		230									
CHP HZ	60-75	CT HZ	30-60		VT HZ	0-60							
INVERTER-TEMP-CODE	T2C												
SER.NO.				MOTOR WEIGHT									

S/O	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	449TS	350	P	3/60	3575	460
AMPS	DUTY	AMB °C/ INSUL	S.F.	NEMA DESIGN	CODE LETTER	ENCLOSURE
370	CONT	40/F	1.15	B	G	TEFC
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
-	418143004YE	---	---	.00661		
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	74.2	3600	8.41	0	
1/4	87.5	132	3593	67.1	92.4	
2/4	175	204	3587	84.4	95.2	
3/4	263	283	3580	90.6	95.8	
4/4	350	370	3573	92.3	95.8	
5/4	437	464	3566	92.2	95.6	
SPEED TORQUE						
		RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES	
LOCKED ROTOR	0	193	991	2741		
PULL UP	1620	132	678	2490		
BREAKDOWN	3463	295	1519	1339		
FULL LOAD	3573	100	514	370		
AMPERES SHOWN FOR 460 VOLT CONNECTION. IF OTHER CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.						
TYPICAL DATA NEMA NOM. EFF. - 95.8%						
ABB		DRAWN BY: W.L. SMITH CHECKED BY: C.E. JAMISON APPROVED BY: W.L. SMITH DATE: 01/08/25		AC MOTOR PERFORMANCE DATA	A44WG6769-R001 DATE ISSUED 01/08/25	

USCH/AM

Printed on 04/17/2025 7:40 AM

REL.S.O.	FRAME 449TS	RPM 3575	S.F. 1.15	ROTOR 418143004YE
HP 350	VOLTS 460	AMPS 370	NEMA DESIGN B	TEST S.O. TYPICAL DATA
TYPE P	DUTY CONT	CODE LETTER G	ENCLOSURE TEF	TEST DATE --
PHASE/ HERTZ 3/60	AMB °C/ INSUL. 40/F	E/S -	STATOR RES. @ 25°C .00661	STATOR RES. @ 25°C .00661
			OHMS (BETWEEN LINES)	



AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.



DRAWN BY: W.L. SMITH
CHECKED BY: C.E. JAMISON
APPROVED BY: W.L. SMITH
DATE: 01/08/25


AC MOTOR
PERFORMANCE
DATA


A44WG6769-R001

ISSUE DATE 01/08/25

USCH/AM


Printed on 04/17/2025 7:40 AM





416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)

416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1