



Customer information packet

ECP83583T-4

1.5HP, 3450RPM, 3PH, 60HZ, 143, T, 0524M, TEFC

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	143T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	1.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSA US CSA CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	1.7
Current @ Voltage	2.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	85.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Enclosure Modification	841
Feedback Device	NO FEEDBACK

Part detail

Revision	BL
Type	AC
Mech. spec.	05E811
Base	
Status	PRD/A
Elec. spec.	05WGW176
Layout	05LYE811
Eff. date	10-01-2025
CD Diagram	CD0006
Poles	02
Leads	3#18 See spl instr.,0#0 Dbl Dip & Bake,0#0 Phase InsulatY
Proprietary	False
Created date	11-18-2005

Front Face Code	Standard
Front Shaft Indicator	None
Haz Area Temp Code	T3C
Heater Indicator	No Heater
High Voltage Full Load Amps	2.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	M
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Max Speed	5400 rpm
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	@ 0 AWG 3 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0524M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	12.87 IN
Power Factor	83
Product Family	Chem Process S/P 32-8 IEEE 841
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	0.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3450 rpm

Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP4328									
CAT.NO.	ECP83583T-4								
SPEC.	05E811W176								
HP	1.5 TE				IP	56			
VOLTS	460								
AMPS	2								
R.P.M.	3450								
FRAME	143T		HZ		60		PH	3	
SER.F.	1.15	CODE	M	DES.	B	CLASS	F		
RATING	40C AMB-CONT								
SN									
DE	6205		ODE		6205				
NEMA NOM. EFF.	85.5		P.F.		83				
GUAR. MIN. EFF.	82.5		CC	010A					
T. CODE	T3C		TEMP=		160				

NP3186

SPEC.	05E811W176				
ABMA DE BRG	25BC02X30X				
ABMA ODE BRG	25BC02X30X				
GREASE	POLYREX EM				
MOTOR WEIGHT	69	ROTOR BARS	20	STATOR BARS	24
MAX. R.P.M.	5400	MAX. KVAR	.25		
INV.TYPE	PWM				
T=	160				
CHP	60	TO	90		
CT	1.7	TO	60		
VT	0-	TO	60		
HTR-VOLTS	N/A	HTR-AMPS	N/A		
HTR-WATTS	N/A	MAX. SPACE HEATER TEMP.			N/A

AC Induction Motor Performance Data

Record # 92447

Typical performance - not guaranteed values

Winding: 05WGW176-R028			Type: 0524M		Enclosure: TEFC		
Nameplate Data			460 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		1.5	Full Load Torque		2.236 LB-FT		
Volts		460	Start Configuration		direct on line		
Full Load Amps		2	Breakdown Torque		11.1 LB-FT		
R.P.M.		3450	Pull-up Torque		7.77 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		9.67 LB-FT	
NEMA Design Code		B	KVA Code	M	Starting Current		20 A
Service Factor (S.F.)		1.15	No-load Current		0.905 A		
NEMA Nom. Eff.		85.5	Power Factor	83	Line-line Res. @ 25°C		8.4759 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		34°C	
S.F. Amps				Temp. Rise @ S.F. Load		38°C	
				Locked-rotor Power Factor		50.3	

Load Characteristics 460 V, 60 Hz, 1.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	46	67	78	84	88	90	86
Efficiency	74.4	83.4	86	85.5	86.2	85.4	85.9
Speed	3573.7	3552.1	3528.4	3504	3477.8	3449.4	3488
Line amperes	1.02	1.25	1.57	1.92	2.31	2.75	2.15


ABB Motors and Mechanical Inc.


WINDING # 05WGW176

Typical performance - not guaranteed values.



1.5 HP 3 PH 60 HZ 3450 RPM 460 V 0524M

TORQUES (LB-FT): PO=11.1 PU=7.77 LR=9.67 LRA=20





CD0006



- NOTES:
- 1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
 - 2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
 - 5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: E	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\141	REVISED: 10: 24: 49 02/19/2019	BY: ENBRIRO
MTL: —		

BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1