



Customer information packet

ECP84310T-4

60HP, 3560RPM, 3PH, 60HZ, 364TS, A36056M, TEFC

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	364TS
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	60.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSAUSEEV NEMA PREMIUM NEMA_PREMIUM UR CCSA US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Constant Torque Speed Range	0.7-60
Current @ Voltage	65.100 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.0 %
Enclosure Modification	841
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3
Heater Indicator	No Heater
High Voltage Full Load Amps	65.1 a
Insulation Class	F

Part detail


Revision	Q
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A36WG0130
Layout	617428-510
Eff. date	08-26-2024
CD Diagram	416820-036
Poles	02
Leads	3#4
Proprietary	False
Created date	11-27-2018

Inverter Code	Inverter Ready
IP Rating	IP56
KVA Code	F
Lifting Lugs	No Lifting Lugs
Max Speed	4500 rpm
Motor Lead Quantity/Wire Size	3 @ 4 AWG
Motor Standards	NEMA
Motor Type	A36056M
Mounting Arrangement	F1
No Load Current	14.1 a
Number of Poles	2
Overall Length	31.37 IN
Power Factor	90
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Phase Seq-Std Rot (CCWODE)
Shaft Slinger Indicator	No Slinger
Speed	3560 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Nameplate

NP4388																
CAT #	ECP84310T-4						FR	364TS			IP56					
SPEC	A36-6000-0130						ENCL	TEFC			DES	B				
HZ	60	PH	3	CL	F	HP	60	SF	1.15	PF	90	%	CODE	F		
VOLTS	460					AMPS	65.1									
RPM	3560		MAX RPM		4500		SER									
NEMA NOM. EFF	95	%		RATING		40C AMB-CONT										
GUAR MIN. EFF	94.1	%		BRG DE		6313			BRG ODE		6313					
CL I DIV 2 GRPS A,B,C,D				CL I ZONE 2 GRPS					IIA,IIB,IIC			TEMP T		3-200	C	
CT HZ	0.7-60		VT HZ		0-60											
CHP HZ	60-75		INV TEMP CL				200	C								
								MTR WT		959	LBS					

REL.S.O.	FRAME 364	HP 60	TYPE P	PHASE / HERTZ 3/60	RPM 3560	VOLTS 460	AMPS 65.1	DUTY CONT	AMB °C / INSUL. 40/F	S.F. 1.15	NEMA DESIGN B	CODE LETTER G	ENCLOSURE TEFC	ROTOR 418141005XE	TEST S.O. TYPICAL DATA	TEST DATE ---	STATOR RES. @ 25°C .101	OHMS (BETWEEN LINES)
----------	-----------	-------	--------	--------------------	----------	-----------	-----------	-----------	----------------------	-----------	---------------	---------------	----------------	-------------------	------------------------	---------------	-------------------------	----------------------




AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

	DRAWN BY: G. R. WEBB	AC MOTOR	A36WG0130-R006
	CHECKED BY: J.J. HARRISON APPROVED BY: E.J. CHRISTIAN DATE: 07/31/02	PERFORMANCE DATA	

USERCHRI

Printed on 05/13/2021 8:46 AM

REL.S.O.	RPM 3560	S.F. 1.15	ROTOR 418141005XE
FRAME 364	VOLTS 460	NEMA DESIGN B	TEST S.O. TYPICAL DATA
HP 60	AMPS 65.1	CODE LETTER G	TEST DATE --
TYPE P	DUTY CONT	ENCLOSURE TEFC	STATOR RES. @ 25°C .101
PHASE / HERTZ 3/60	AMB °C / INSUL 40/F	E/S 491282	OHMS (BETWEEN LINES)




THE THERMAL LIMIT CURVE
FOR THIS MOTOR-NEMA NOM. EFF. 95.0 %

AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

	DRAWN BY: G. R. WEBB CHECKED BY: J. J. HARRISON APPROVED BY: E. J. CHRISTIAN DATE: 07/31/02	AC MOTOR PERFORMANCE DATA	A36WG0130-R006 ISSUE DATE 05/13/21
--	--	---------------------------------	---------------------------------------


USERCHRI

Printed on 05/13/2021 8:46 AM



416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1

416820-036