



Customer information packet

ECP84409TR-4

100HP, 1190RPM, 3PH, 60HZ, 0444T, TEFC, F1

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	444T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	100.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	UR CCSA US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Mobil SHC 220 (Athens Only)
Constant Torque Speed Range	15-60
Current @ Voltage	119.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.0 %
Enclosure Modification	841
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3
Heater Indicator	No Heater
High Voltage Full Load Amps	119.0 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	IP56
KVA Code	G

Part detail

Revision	J
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG3905
Layout	617434-660
Eff. date	12-10-2025
CD Diagram	416820-036
Poles	06
Leads	3#2
Proprietary	False
Created date	08-06-2019

Lifting Lugs	Standard Lifting Lugs
Motor Lead Quantity/Wire Size	3 @ 2 AWG
Motor Standards	None
Motor Type	A44064M
Mounting Arrangement	F1
No Load Current	39.4 a
Number of Poles	6
Overall Length	44.97 IN
Power Factor	82
Pulley End Bearing Type	Roller
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	3.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1190 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Nameplate

NP4566													
CAT NO	ECP84409TR-4			SPEC NO.		A44-9012-3905							
HP	100	AMPS	119		VOLTS		460		DESIGN	B			
FRAME SIZE	444T	RPM	1190		HZ	60	AMB	40	SF	1.15			
D.E. BRG.DATA	NU222		O.D.E. BRG.DATA			6318		PH	3	DUTY	CONT	INSUL.CLASS	F
D.E. BRG.	110RU02M30X			TYPE	ENCL	TEFC	CODE	G					
O.D.E. BRG.	90BC03J30X			POWER FACTOR			82		NEMA-NOM-EFFICIENCY			95	
3/4 LOAD EFF.	95.3	IP	56	MAX CORR KVAR			27		GUARANTEED EFFICIENCY			94.1	
TEMP CODE	T3	TEMP =	200										
CHP HZ	60-90	CT HZ	15-60		VT HZ	0-60							
INVERTER-TEMP-CODE	T3												
SER.NO.				MOTOR WEIGHT									

000613007EX


CAT NO	ECP84409TR-4	SPEC NO.	A44-9012-3905	
NO. ROTOR BARS	71	GREASE TYPE	MOBIL SHC 220	
NO. SLOTS	90	NL AMPS AT RATED VOLTAGE		39.4
5 YEAR WARRANTY		WINDING RES @25 C	.05474	OHMS
MFG. DATE		SER.NO		
	SFA 132			

S/O	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	444T	100	P	3/60	1190	460
AMPS	DUTY	AMB °C/ INSUL	S.F.	NEMA DESIGN	CODE LETTER	ENCLOSURE
119	CONT	40/F	1.15	B	G	TEFC
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
497780	418143098VE	---	---	.0547		
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	39.9	1200	4.01	0	
1/4	25.0	55.8	1197	45.5	92.5	
2/4	50.0	72.5	1194	68.0	95.0	
3/4	75.0	94.3	1191	78.0	95.3	
4/4	100	119	1188	82.5	95.0	
5/4	125	147	1184	84.3	94.4	
SPEED TORQUE						
		RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES	
LOCKED ROTOR		0	142	627	730	
PULL UP		168	126	558	717	
BREAKDOWN		1146	266	1175	438	
FULL LOAD		1188	100	442	119	
AMPERES SHOWN FOR 460 VOLT CONNECTION. IF OTHER CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.						
TYPICAL DATA NEMA NOMINAL EFFICIENCY = 95.0 PCT.						
		DRAWN BY: W.L. SMITH CHECKED BY: J.J. HARRISON APPROVED BY: W.L. SMITH DATE: 12/06/10		AC MOTOR PERFORMANCE DATA	A44WG3905-R001 DATE ISSUED 08/09/19	

USERCHRI

Printed on 06/04/2020 1:33 PM

REL.S.O.	FRAME 444T	RPM 1190	S.F. 1.15	ROTOR 418143098YE
HP 100	VOLTS 460	AMPS 119	NEMA DESIGN B	TEST S.O. TYPICAL DATA
TYPE P	DUTY CONT	CODE LETTER G	ENCLOSURE TEFC	TEST DATE --
PHASE / HERTZ 3/60	AMB °C / INSUL. 40/F	E/S 497780		STATOR RES. @ 25°C .0547
				OHMS (BETWEEN LINES)



AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.



DRAWN BY: W.L. SMITH
CHECKED BY: J.J. HARRISON
APPROVED BY: W.L. SMITH
DATE: 12/06/10

AC MOTOR
PERFORMANCE
DATA


A44WCG3905-R001

ISSUE DATE 08/09/19

USERCHRI

Printed on 06/04/2020 1:33 PM

REL.S.O.	RPM 1190	S.F. 1.15	ROTOR 418143098YE
FRAME 444T	VOLTS 460	NEMA DESIGN B	TEST S.O. TYPICAL DATA
HP 100	AMPS 119	CODE LETTER G	TEST DATE ---
TYPE P	DUTY CONT	ENCLOSURE TEFC	STATOR RES. @ 25°C .0547
PHASE / HERTZ 3/60	AMB °C / INSUL 40/F	E/S 497780	OHMS (BETWEEN LINES)




Thermal Limit Curve
NEMA Nominal Efficiency = 95.0 PCT.


AMPERES SHOWN FOR 460 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

	DRAWN BY: W.L. SMITH CHECKED BY: J.J. HARRISON APPROVED BY: W.L. SMITH DATE: 12/06/10	AC MOTOR PERFORMANCE DATA	A44WCG3905-R001 ISSUE DATE 08/09/19
--	--	---------------------------------	--

USERCHRI

Printed on 06/04/2020 1:33 PM





416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)

416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1