



Customer information packet

ECP84410T-5

125HP, 1785RPM, 3PH, 60HZ, 444T, A44076M, TEFC

Class - CLI GP A,B,C,D

Division - Division II

Specifications

Enclosure	TEFC
Frame	444T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	125.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CCSA US UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Constant Torque Speed Range	10-60
Current @ Voltage	115.000 A @ 575.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.4 %
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3
Heater Indicator	No Heater
High Voltage Full Load Amps	115.0 a
Insulation Class	F
Inverter Code	Not Inverter
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Motor Lead Quantity/Wire Size	3 @ 1 AWG

Part detail

Revision	B
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG3904
Layout	617434-660
Eff. date	12-10-2025
CD Diagram	416820-036
Poles	04
Leads	3#1
Proprietary	False
Created date	03-10-2022

Motor Standards	None
Motor Type	A44076M
Mounting Arrangement	F1
No Load Current	36.6 a
Number of Poles	4
Overall Length	44.97 IN
Power Factor	85
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	3.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Phase Seq-Std Rot (CCWODE)
Shaft Slinger Indicator	No Slinger
Speed	1785 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None

Nameplate

NP4566

CAT NO	ECP84410T-5			SPEC NO.		A44-0000-3904							
HP	125	AMPS	115		VOLTS		575		DESIGN	B			
FRAME SIZE	444T	RPM	1785		HZ	60	AMB	40	SF	1.15			
D.E. BRG.DATA	6318		O.D.E. BRG.DATA			6318		PH	3	DUTY	CONT	INSUL.CLASS	F
D.E. BRG.	90BC03J30X			TYPE	P	ENCL	TEFC	CODE	G				
O.D.E. BRG.	90BC03J30X			POWER FACTOR			85		NEMA-NOM-EFFICIENCY			95.4	
3/4 LOAD EFF.	95.7	IP	56	MAX CORR KVAR			27		GUARANTEED EFFICIENCY			94.5	
TEMP CODE	T3	TEMP =		200									
CHP HZ	60-90	CT HZ	10-60		VT HZ	0-60							
INVERTER-TEMP-CODE	T3												
SER.NO.				MOTOR WEIGHT									


000613007EX				
CAT NO	ECP84410T-5	SPEC NO.	A44-0000-3904	
NO. ROTOR BARS	58	GREASE TYPE	POLYREX EM	
NO. SLOTS	72	NL AMPS AT RATED VOLTAGE		36.6
5 YEAR WARRANTY		WINDING RES @25 C	0.0593	OHMS
MFG. DATE		SER.NO		

S/O	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	445	125	P	3/60	1785	575
AMPS	DUTY	AMB °C/ INSUL	S.F.	NEMA DESIGN	CODE LETTER	ENCLOSURE
I15	CONT	40/F	1.15	B	G	TEFC
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
498874	418143052KE	---	---	.0599		
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	35.8	1800	4.44	0	
1/4	31.3	49.4	1796	51.1	92.8	
2/4	62.5	67.3	1792	73.0	95.3	
3/4	93.7	89.8	1788	81.7	95.7	
4/4	125	115	1784	85.3	95.5	
5/4	156	142	1780	86.6	95.1	
SPEED TORQUE						
		RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES	
LOCKED ROTOR		0	133	489	713	
PULL UP		270	114	420	700	
BREAKDOWN		1729	290	1067	400	
FULL LOAD		1784	100	368	115	
AMPERES SHOWN FOR 575 VOLT CONNECTION. IF OTHER CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.						
CALCULATED DATA NEMA NOMINAL EFFICIENCY = 95.4PCT.						
		DRAWN BY: C. JAMISON CHECKED BY: W. SMITH APPROVED BY: W. SMITH DATE: 04/09/12		AC MOTOR PERFORMANCE DATA	A44WG3904-R001 DATE ISSUED 04/09/12	

USERCHRI

Printed on 06/09/2020 10:58 AM

REL.S.O.	FRAME 445	RPM 1785	S.F. 1.15	ROTOR 418143052KE
HP 125	VOLTS 575	AMPS 115	NEMA DESIGN B	TEST S.O. CALCULATED DATA
TYPE P	DUTY CONT	CODE LETTER G	ENCLOSURE TEFC	TEST DATE --
PHASE / HERTZ 3/60	AMB °C / INSUL. 40/F	E/S 498874	STATOR RES. @ 25°C .0599	OHMS (BETWEEN LINES)



AMPERES SHOWN FOR 575 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.



DRAWN BY: C.JAMISON
CHECKED BY: W.SMITH
APPROVED BY: W.SMITH
DATE: 04/09/12

AC MOTOR
PERFORMANCE
DATA


A44WCG3904-R001

ISSUE DATE 04/09/12

USERCHRI

Printed on 06/09/2020 10:58 AM

REL.S.O.	FRAME 445	RPM 1785	S.F. 1.15	ROTOR 418143052KE
HP 125	VOLTS 575	AMPS 115	NEMA DESIGN B	TEST S.O. CALCULATED DATA
TYPE P	DUTY CONT	CODE LETTER G	ENCLOSURE TEFC	TEST DATE ---
PHASE / HERTZ 3/60	AMB °C / INSUL 40/F	E/S 498874	STATOR RES. @ 25°C .0599	OHMS (BETWEEN LINES)




Thermal Limit Curve
NEMA Nominal Efficiency = 95.4PCT.


AMPERES SHOWN FOR 575 VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

	DRAWN BY: C.JAMISON CHECKED BY: W.SMITH APPROVED BY: W.SMITH DATE: 04/09/12	AC MOTOR PERFORMANCE DATA	A44WCG3904-R001 ISSUE DATE 04/09/12
--	--	---------------------------------	--

USERCHRI

Printed on 06/09/2020 10:58 AM





416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)

416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1