



Customer information packet

ECP844156TR-4

150HP, 1190RPM, 3PH, 60HZ, 447T, TEFC, FOOT,
Class - CLI GP A,B,C,D
Division - Division II

Specifications

Enclosure	TEFC
Frame	447T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	CL I GP A,B,C,D
Haz Area Division	Division II
Motor Letter Type	Three Phase
Output @ Frequency	150.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	UR CCSA US
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Mobil SHC 220 (Athens Only)
Constant Torque Speed Range	15-60
Current @ Voltage	170.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	95.8 %
Enclosure Modification	841
Feedback Device	NO FEEDBACK
Haz Area Temp Code	T3
Heater Indicator	No Heater
High Voltage Full Load Amps	170.0 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	IP56
KVA Code	F

Part detail

Revision	E
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG1496
Layout	617434-663
Eff. date	12-11-2023
CD Diagram	416820-036
Poles	06
Leads	3#1/0
Proprietary	False
Created date	12-11-2018

Lifting Lugs	No Lifting Lugs
Motor Lead Quantity/Wire Size	3 @ 1/0 AWG
Motor Standards	Other
Motor Type	A44120M
Mounting Arrangement	F1
No Load Current	38.6 a
Number of Poles	6
Overall Length	48.46 IN
Power Factor	86
Pulley End Bearing Type	Roller
Pulley Face Code	C-Face
Service Factor	1.15
Shaft Diameter	3.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Phase Seq-Std Rot (CCWODE)
Shaft Slinger Indicator	No Slinger
Speed	1190 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None


Nameplate

NP4566														
CAT NO	ECP844156TR-4			SPEC NO.		A44-8391-1496								
HP	150	AMPS		170		VOLTS		460		DESIGN		B		
FRAME SIZE	447T	RPM		1190		HZ		60	AMB		40	SF		1.15
D.E. BRG.DATA	NU222		O.D.E. BRG.DATA			6318		PH		3	DUTY		CONT	INSUL.CLASS
D.E. BRG.	110RU02M30X			TYPE		ENCL		TEFC		CODE		F		
O.D.E. BRG.	90BC03J30X			POWER FACTOR			86		NEMA-NOM-EFFICIENCY			95.8		
3/4 LOAD EFF.	96.2	IP		56	MAX CORR KVAR			25.0		GUARANTEED EFFICIENCY			95	
TEMP CODE	T3	TEMP =		200										
CHP HZ	60-90	CT HZ		15-60	VT HZ		0-60							
INVERTER-TEMP-CODE	T3													
SER.NO.				MOTOR WEIGHT										

000613007EX				
CAT NO	ECP844156TR-4	SPEC NO.	A44-8391-1496	
NO. ROTOR BARS	71	GREASE TYPE	MOBIL SHC 220	
NO. SLOTS	90	NL AMPS AT RATED VOLTAGE		38.6
5 YEAR WARRANTY		WINDING RES @25 C	.03239	OHMS
MFG. DATE		SER.NO		

NP2496L	
MOBIL SHC -220 GREASE	

REL. S.O.	FRAME	HP	TYPE	PHASE/ HERTZ	RPM	VOLTS
	447T	150	P	3/60	1190	460
AMPS	DUTY	AMB °C/ INSUL.	S.F.	NEMA DESIGN	CODE LETTER	ENCL.
170	CONT	40/F	1.15	B	F	TEFC
E/S	ROTOR	TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)		
833241	418143080ME	---	---	.0324		
PERFORMANCE						
LOAD	HP	AMPERES	RPM	% POWER FACTOR	% EFFICIENCY	
NO LOAD	0	42.5	1200	3.70	0	
1/4	37.6	65.5	1197	56.6	94.9	
2/4	75.1	94.9	1194	76.9	96.3	
3/4	112	130	1191	83.9	96.2	
4/4	150	170	1188	86.3	95.8	
5/4	188	213	1184	86.8	95.1	
SPEED TORQUE						
LOCKED ROTOR	0		121		799	1025
PULL UP	180		97.2		644	1002
BREAKDOWN	1150		236		1563	592
FULL LOAD	1188		100		663	170
AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE						
REMARKS: TYPICAL DATA NEMA NOMINAL EFFICIENCY = 95.4 PCT.						
			DR. BY W. L. SMITH CK. BY J. J. HARRISON APP. BY W. L. SMITH DATE 04/27/10		A-C MOTOR PERFORMANCE DATA A44WG1496-R001 ISSUE DATE 12/18/10	



REL. S.O. FRAME 447T HP 150 TYPE P PHASE/HERTZ 3/60

RPM 1190 VOLTS 460 AMPS 170 DUTY CONT AMB C/INSUL 40/F E/S 833241

S.F. 1.15 NEMA DESIGN B CODE LETTER F ENCLOSURE TEFC STATOR RES. @ 25 °C .0324 OHMS (BETWEEN LINES)

ROTOR 418143080ME TEST S.O. TYPICAL DATA TEST DATE ---

10.00
9
8
7
6
5
4
3
2
1.00
9
8
7
6
5
4
3
2
1

0100200300400500600700

1.0
9
8
7
6
5
4
3
2
1

TIME IN SEC.

OVERLOAD
119C FOR OVERLOAD AND ACC.
119 C FOR LOCKED-ROTOR
LOCKED-ROTOR, 40 C
LOCKED-ROTOR
ACCELERATION
LOCKED-ROTOR

% FULL LOAD CURRENT

AMPERES SHOWN FOR 460
AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE.

VOLT CONNECTION, IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE


DR. BY W. L. SMITH
CK. BY J. J. HARRISON
APP. BY W. L. SMITH
DATE 04/27/10


A-C MOTOR
PERFORMANCE CURVES
A44WG1496-R001
ISSUE DATE 12/8/10

REMARKS:

NEMA NOMINAL EFFICIENCY = 95.4 PCT.


THERMAL LIMIT CURVE





416820-036

A-C MOTOR
CONNECTION DIAGRAM
STANDARD 3 LEAD CONNECTED



(N.P. 1575-BA)

416820-036

REV. DESC: LOADED TO BUS, C/R 335225		
REV. LTR: -	VERSION: 00	TDR: 000000538207
FILE: \MGA\00000\682		REVISED: 11: 54: 06 04/30/2010
MTL: -		BY: RAGRA

BALDOR

CONN DIAG - STANDARD 3 LEAD
SH 1 of 1