



Customer information packet

ECR583506-PPN

M3BN 587MLB 6P B4 350HP

ABB Oy**PERFORMANCE DATA OF MOTOR**

Classifying code or document type

Motors & Generators

Department/Author	Date of Issue	Lang.	Rev. date	Our ref.	Pages
MLA000/TISA	11.10.2018	EN		3GZF021035-1235	
Customer ref.	Saving Ident			Rev./Changed by	
	TMAA-ASUG9J-TISA35			A	1/3

Driven Motor:

Catalog Number	ECR583506-PPN				
Motor type code	M3BN 587 MLB 6K				
Motor product code	3GBN983420-ADKBA03				
Motor type	Squirrel cage Motor				
Mounting designation	IM 1001 (B3)				
Protected by enclosure	IP66				
Method of cooling	TEFC				
Insulation	Class F (Shock Resistant)				
Service factor	SF1.15 TEMP RISE CLASS F				
Standards	NEMA				
International efficiency classification (IEC 60034-30)	IE3				
Ambient temperature, max.	40 °C				
Altitude, max.	3280 ft.a.s.l.				
Duty type	Continuous				
Temp. rise	Class B				
Connection of stator winding	Delta				
Rated output	350 HP				
Voltage	460 V				
Frequency	60 Hz				
Speed	1194 r/min				
Current	407 Amps				
Locked rotor Amps	700 %				
Locked rotor torque	210 %				
Breakdown torque	250 %				
No load current	144 Amps				
Rated torque	1539 lb-ft				
Load characteristics	Load %	Current Amps	Efficiency %	Power Factor	
	100	407	95,8	0,84	
	75	320	96,1	0,80	
	50	237	95,8	0,72	

Typical calculated values to NEMA. –
-NEMA Nominal Efficiency 95.8%

Motors & Generators Visiting Address
Strömbergin puistotie 5 A
VAASA
FINLAND

ABB Oy
Postal Address
P.O.Box 633
FI-65101 VAASA
FINLAND

Telephone
+358 10 222 000


Telefax
+358 10 224 7372

Department/Author	Date of Issue	Lang.	Rev. date	Our ref.	Rev./Changed by	Pages
MLA000/TISA	11.10.2018	EN		3GZF021035-1235		
Customer ref.	Saving Ident			TMAA-ASUG9J-TISA35	A	2/3

Motor type code: M3BN 587 MLB 6K

Rated output	350 HP	Power Factor	0,84
Voltage	460 V	Rated torque	1539 lb-ft
Frequency	60 Hz	Locked rotor Amps	700 %
Speed	1194 r/min	Locked rotor torque	210 %
Current	407 Amps	Breakdown torque	250 %

Torque and Current vs. Speed



Motors & Generators Visiting Address
Strömbergin puistotie 5 A
VAASA
FINLAND

ABB Oy
Postal Address
P.O. Box 633
FI-65101 VAASA
FINLAND

Telephone +358 10 222 000
Telefax +358 10 224 7372

ABB Oy**Motors & Generators****PERFORMANCE DATA OF MOTOR**

Department/Author	Date of Issue	Lang.	Rev. date	Our ref.	Rev./Changed by	Pages
MLA000/TISA	11.10.2018	EN		3GZF021035-1235		
Customer ref.	Saving Ident			TMAA-ASUG9J-TISA35	A	3/3

PWM

Switch. freq. 3KHz

FWP 460VD 60Hz

VSD-duty: Temp. rise class F

Drive1

Rated power	87,5 HP
Rated voltage	117 V
Nominal frequency	15,3 Hz
Type of connection	Delta
Rated torque	1532 lb-ft
Speed	300 rpm
Current	415 Amps

Drive2

Rated power	350 HP
Rated voltage	460 V
Nominal frequency	60,4 Hz
Type of connection	Delta
Rated torque	1531 lb-ft
Speed	1200 rpm
Current	442 Amps

Constant torque 300 – 1200rpm

Motors & Generators Visiting Address

Strömbergin puistotie 5 A

VAASA

FINLAND

ABB Oy

Postal Address

P.O.Box 633

FI-65101 VAASA

FINLAND

Telephone

+358 10 222 000

Telefax

+358 10 224 7372




Document No:
3GZF321100-1 E

Approved by: Jari Raittila

Customer Reference:





11TB1...11TB2	BIMETAL DETECTORS, TYPE NCC BIMETALL-THERMOSCHALTER, TYP NCC SONDES BIMETALLIQUES, TYPE NCC
---------------	---


Motor No
Maschine Nr
Moteur No

ABB Oy, Electrical Machines LV Motors	3GZF321200-35 B
--	-----------------

Accessory Connection Diagram

Document No:
3GZF321200-35 B

Description:	BIMETAL DETECTORS
--------------	-------------------



Unit: Electrical Machines, LV Motors

Issued by: **K. Högvist**

Replaces:

Date: 16.01.2002

Approved by: M. Prusi

Replaced by:

Customer Reference:

ABB Oy



