



Customer information packet

ECS101A8K1P5DC4

1.5KW, 1500RPM, 3PH, 50HZ, D90C, 3524B, TEFC, B

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	D90C
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Brushless Wound Field PM Rotor
Output @ Frequency	1.500 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	230.0 V @ 50 HZ
Agency Approvals	CE CULUS UKCA WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	5
Current @ Voltage	3.400 A @ 230.0 V
Design Code	-
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	90.6 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Frame Prefix	D
Heater Indicator	No Heater
High Voltage Full Load Amps	3.4 a

Part detail

Revision	B
Type	AC
Mech. spec.	35EE439
Base	
Status	PRD/A
Elec. spec.	35WGG964
Layout	35LYEE439
Eff. date	11-15-2024
CD Diagram	CD0006B03
Poles	04
Leads	3#16 13" LONG LEADS Y
Proprietary	False
Created date	04-29-2024

Insulation Class	F
Inverter Code	03
KVA Code	-
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	3 @ 16 AWG
Motor Lead Termination	Flying Leads
Motor Standards	IEC
Motor Type	3524B
Mounting Arrangement	B14
Number of Poles	4
Overall Length	17.18 IN
Power Factor	93
Product Family	General Purpose
Pulley Face Code	C-Face
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	0.945 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Speed	1500 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3968B01A01												
CAT.NO.	ECS101A8K1P5DC4											
SPEC.	35EE439G964					YR						
FRAME	D90C			IP	55	WT.	45					
KW	1.5	HZ	50	PH	3	DUTY-IPM	CONT					
INS CL	F	CLASS RISE					AMB-C	40				
EFF. CL	IE5	EFF	90.6			COSO	93					
VOLTS	230			FLA	3.4							
1/MIN	1500			1/MIN MAX				3000				
BEMF (V)	123			RS (OHMS)				2.94				
LD (MH)	22.1				LQ (MH)				97.1			
VPWM	CP =	50			TO	133						
CT	5	TO	50	VT	5	TO	50					
MATCHED INV	ECIN8A7P0											
DE	6206			ODE	6203							
SERIAL #												

NP3978A00					
PART NO.	ECIN8A7P0				
U1	240	PH	1	HZ	50
I1	5.3	W/EXT. CHOKE			5.1
SERIAL #					

Volts	230	Max RPM	3000	Conn Diag.	CD0006B03	Leads	3
Amps	3.4	Max Amps		Cs Diagram	CS1127	BEMF	123
KW	1.5	VFD#	ECIN8A7P0			LD	22.1
RPM	1500	S.F.	1.00			LQ	97.1
Phase/Hz	3/50	Rating	40C AMB-CONT			Rs	2.9307
							Meas. L-L

60034-2-3 Motor Performance at Standardized Operating Points

	RPM	% Speed	LB-FT	% Torque	KW	Efficiency	Loss (% FL)	Watts Loss (W)
P1	1360	90%	7.0	100%	1.8	89.6	10.41%	158
P2	751	50%	7.0	100%	1.0	84.8	8.88%	135
P3	366	25%	7.0	100%	0.5	76.0	7.63%	116
P4	1353	90%	3.5	50%	0.9	90.7	4.57%	69
P5	751	50%	3.5	50%	0.5	88.1	3.36%	51
P6	751	50%	1.8	25%	0.3	87.9	1.70%	26
P7	366	25%	1.8	25%	0.1	82.9	1.24%	19


61800-9-2 PDS Performance at Reference Operating Points

	RPM	% Speed	LB-FT	% Torque	KW	System Efficiency	Loss (% FL)	Watts Loss (W)
P1	1508	100%	7.0	100%	2.0	86.2	15.88%	241
P2	751	50%	7.0	100%	1.0	80.8	11.75%	178
P3	246	17%	7.0	100%	0.3	62.3	9.83%	149
P4	1488	100%	3.5	50%	1.0	87.9	6.72%	102
P5	751	50%	3.5	50%	0.5	83.4	4.91%	74
P6	246	17%	3.5	50%	0.2	66.6	4.07%	62
P7	751	50%	1.8	25%	0.3	82.0	2.71%	41
P8	246	17%	1.8	25%	0.1	66.5	2.04%	31

Points not taken in certified order.

BALDOR • RELIANCE	DR By: <u>R & D</u> CK By: <u>USGAHL</u> App By: Date: <u>04/09/2025</u>	AC MOTOR PERFORMANCE CURVES	35WGG964 35EE436G964 Test - 112228
--------------------------	---	------------------------------------	---

Volts	230	Max RPM	3000	Conn Diag.	CD0006B03	Leads	3
Amps	3.4	Max Amps		Cs Diagram	CS1127	BEMF	123
KW	1.5	VFD #	ECIN8A7P0			LD	22.1
RPM	1500	S.F.	1.00			LQ	97.1
Phase/Hz	3/50	Rating	40C AMB-CONT			Rs	2.9307
						Meas L-L	



BALDOR • RELIANCE	DR By: <u>R & D</u> CK By: <u>USGAHL</u> APP By: Date: <u>04/09/2025</u>	AC MOTOR PERFORMANCE CURVES	35WGG964 35EE436G964 Test - 112228
--------------------------	---	--	---

