



Customer information packet

ECS101M0K2P2EC4

2KW, 1500RPM, 3PH, 50HZ, D112C, 3624B, TEFC

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	D112C
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Brushless Wound Field PM Rotor
Output @ Frequency	2.200 KW @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	190.0 V @ 50 HZ 380.0 V @ 50 HZ
Agency Approvals	CE WEEE UKCA CULUS
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	No Mounting
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Constant Torque Speed Range	5
Current @ Voltage	4.300 A @ 380.0 V 8.600 A @ 190.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	S1
Efficiency @ 100% Load	91.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Frame Prefix	D

Part detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	36WGA0019
Layout	36LY-000-292
Eff. date	05-08-2024
CD Diagram	CD0005A25
Poles	04
Leads	9#14
Proprietary	False
Created date	01-11-2023

Heater Indicator	No Heater
High Voltage Full Load Amps	4.3 a
Insulation Class	F
Inverter Code	Inverter Duty
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Termination	Terminal Block
Motor Standards	IEC
Motor Type	3624B
Mounting Arrangement	B14
Number of Poles	4
Overall Length	15.88 IN
Power Factor	97
Product Family	General Purpose
Pulley Face Code	C-Face
Rodent Screen	None
Service Factor	1.00
Shaft Diameter	1.103 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Speed	1500 rpm
Speed Code	Single Speed
Starting Method	INVERTER SPECIAL
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3968B01A01												
CAT.NO.	ECS101M0K2P2EC4											
SPEC.	36-0000-3644						YR					
FRAME	D112C			IP	55	WT.	84					
KW	2.2	HZ	50	PH	3	DUTY-IPM	S1					
INS CL	F	CLASS RISE					AMB-C	40				
EFF. CL	IE5	EFF	91.5			COSØ	97					
VOLTS	190/380			FLA	8.6/4.3							
1/MIN	1500				1/MIN MAX			3000				
BEMF (V)	88/176				RS (OHMS)			0.97/3.88				
LD (MH)	14.4/57.7				LQ (MH)			54.4/217.7				
VPWM	CP =	50			TO	100						
CT	5	TO	50	VT	1	TO	50					
MATCHED INV	ACS380-04XX-12A2-1 / 07A2-4											
DE	6206			ODE								
SERIAL #												

Volts	190/380	Max RPM	3000	Conn Diag.	CD0005A25	Leads	9
Amps	8.6/4.3	Max Amps		Cs Diagram	CS0576	BEMF	0
KW	2.2	VFD#	ACS380-040S-05			LD	0
RPM	1500	S.F.	1.00			LQ	0
Phase/Hz	3/50	Rating	40C AMB-S1			Rs	3.7855 Meas. L-L

60034-2-3 Motor Performance at Standardized Operating Points

	RPM	% Speed	LB-FT	% Torque	KW	Efficiency	Loss (% FL)	Watts Loss (W)
P1	1350	90%	10.3	100%	2.7	91.4	8.56%	188
P2	750	50%	10.3	100%	1.5	87.5	7.16%	157
P3	375	25%	10.3	100%	0.7	80.1	6.23%	137
P4	1350	90%	5.2	50%	1.3	91.8	4.06%	89
P5	750	50%	5.2	50%	0.7	89.1	3.07%	68
P6	750	50%	2.6	25%	0.4	88.8	1.58%	35
P7	375	25%	2.6	25%	0.2	85.0	1.11%	24


61800-9-2 PDS Performance at Reference Operating Points

	RPM	% Speed	LB-FT	% Torque	KW	System Efficiency	Loss (% FL)	Watts Loss (W)
P1	1500	100%	10.3	100%	2.9	89.7	11.52%	253
P2	750	50%	10.3	100%	1.5	83.9	9.55%	210
P3	255	17%	10.3	100%	0.5	67.5	8.17%	180
P4	1500	100%	5.2	50%	1.5	89.4	5.92%	130
P5	750	50%	5.2	50%	0.7	84.2	4.68%	103
P6	255	17%	5.2	50%	0.3	69.1	3.79%	83
P7	750	50%	2.6	25%	0.4	81.5	2.83%	62
P8	255	17%	2.6	25%	0.1	66.0	2.19%	48

Points not taken in certified order.

BALDOR • RELIANCE	DR By: <u>R & D</u> CK By: <u>USJORAD2</u> APP By: <u>USJAROB1</u> Date: <u>01/15/2025</u>	AC MOTOR PERFORMANCE CURVES	36WGA0019 36-0000-3637 Test - 111800
--------------------------	---	------------------------------------	---

Volts	190/380	Max RPM	3000	Conn Diag.	CD0005A25	Leads	9
Amps	8.6/4.3	Max Amps		Cs Diagram	CS0576	BEMF	0
KW	2.2	VFD #	ACCS380-040S-05			LD	0
RPM	1500	S.F.	1.00			LQ	0
Phase/Hz	3/50	Rating	40C AMB-S1			Rs	3.7855
						Meas L-L	



BALDOR • RELIANCE

DR By: R & D


CK By: USJDRAD2

APP By: USJAROB1



Date: 01/15/2025

**AC MOTOR
PERFORMANCE
CURVES**

36WGA0019
36-0000-3637
Test - 111800



CD0005A25

LOW VOLTAGE
(2Y)

U V W

INVERTER

HIGH VOLTAGE
(1Y)

U V W

INVERTER

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: NEW

REV. LTR: -

VERSION: 00

TDR: 000001135746

FILE: \AAA\00253\082

REVISED: 01:10:57 03/30/2020

BY: ENMARSO

MTL: -



BALDOR - RELIANCE®

3PH, DV, 9 LEADS, ECS

SH 1 of 1

CD0005A25

