



Customer information packet

ECTM3768T-5G

5HP, 1160RPM, 3PH, 60HZ, 215T, 0746M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	215T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	5.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	6.100 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	Heater Included, 115 V
High Voltage Full Load Amps	6.1 a
Insulation Class	F

Part detail

Revision	B
Type	AC
Mech. spec.	07D718
Base	
Status	PRD/A
Elec. spec.	07WGY332
Layout	07LYD718
Eff. date	06-08-2023
CD Diagram	CD0006
Poles	06
Leads	3#14
Proprietary	False
Created date	04-20-2022

Inverter Code	Inverter Ready
KVA Code	K
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	3 @ 14 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	0746M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	19.58 IN
Power Factor	69
Product Family	Chemical Processing (Not DC)
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.375 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1160 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1260									
CAT.NO.	ECTM3768T-5G								
SPEC.	07D718Y332G1								
HP	5								
VOLTS	575								
AMP	6.1								
RPM	1160								
FRAME	215T		HZ	60		PH	3		
SER.F.	1.15		CODE	K	DES	A	CL	F	
NEMA-NOM-EFF	89.5		PF	69					
RATING	40C AMB-CONT								
CC									
DE	6307		ODE	6206					
ENCL	TEFC		SN						
	INV DUTY 20:1 VT								

AC Induction Motor Performance Data

Record # 38796

Typical performance - not guaranteed values

Winding: 07WGY332-R001				Type: 0746M		Enclosure: TEFC					
Nameplate Data				575 V, 60 Hz: Single Voltage Motor							
Rated Output (HP)		5		Full Load Torque		22.7 LB-FT					
Volts		575		Start Configuration		direct on line					
Full Load Amps		6.1		Breakdown Torque		83 LB-FT					
R.P.M.		1160		Pull-up Torque		51.4 LB-FT					
Hz		60 Phase		3		Locked-rotor Torque		61.7 LB-FT			
NEMA Design Code		A		KVA Code		K		Starting Current		45.1 A	
Service Factor (S.F.)		1.15		No-load Current		3.35 A					
NEMA Nom. Eff.		89.5		Power Factor		69		Line-line Res. @ 25°C		2.55 Ω	
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		52°C					
S.F. Amps				Temp. Rise @ S.F. Load		63°C					

Load Characteristics 575 V, 60 Hz, 5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	31	50	62	69	73	76	71
Efficiency	84.3	89.4	90.3	89.9	88.9	87.7	89.3
Speed	1190	1182	1174	1165	1154	1142	1158
Line amperes	3.58	4.16	4.98	6.06	7.19	8.45	6.74


ABB Motors and Mechanical Inc.


WINDING # 07WGY332

Typical performance - not guaranteed values.

5 HP 3 PH 60 HZ 1160 RPM 575 V 0746M

TORQUES (LB-FT): PO=83 PU=51.4 LR=61.7 LRA=45.1





CD0006



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10: 24: 49 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1