



Customer information packet

ECTM4100T-5G

15HP, 1175RPM, 3PH, 60HZ, 284T, 1046M, TEFC, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	TEFC
Frame	284T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1200 RPM @ 60 HZ
Voltage @ Frequency	575.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	16.000 A @ 575.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	Tapped & Key
Heater Indicator	Heater Included, 115 V
High Voltage Full Load Amps	16.0 a
Insulation Class	F

Part detail

Revision	G
Type	AC
Mech. spec.	10T010
Base	
Status	PRD/A
Elec. spec.	10WGY949
Layout	10LYT010
Eff. date	11-03-2025
CD Diagram	CD0006
Poles	06
Leads	3#12
Proprietary	False
Created date	04-13-2022

Inverter Code	Not Inverter
KVA Code	G
Lifting Lugs	Vertical Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	3 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1046M
Mounting Arrangement	F1
Number of Poles	6
Overall Length	27.57 IN
Power Factor	76
Product Family	Chemical Processing (Not DC)
Pulley End Bearing Type	Sealed Bearing
Pulley Face Code	Standard
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	None
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	1175 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1260													
CAT.NO.	ECTM4100T-5G												
SPEC.	10T010Y949G1												
HP	15												
VOLTS	575												
AMP	16												
RPM	1175												
FRAME	284T		HZ	60		PH		3					
SER.F.	1.15		CODE	G	DES	A		CL	F				
NEMA-NOM-EFF	91.7		PF	76									
RATING	40C AMB-CONT												
CC	010A												
DE	6311		ODE	6309									
ENCL	TEFC		SN										
	INV DUTY 20:1VT												

AC Induction Motor Performance Data

Record # 35011

Typical performance - not guaranteed values

Winding: 10WGY949-R001			Type: 1046M		Enclosure: TEFC		
Nameplate Data			575 V, 60 Hz: Single Voltage Motor				
Rated Output (HP)		15	Full Load Torque		66.7 LB-FT		
Volts		575	Start Configuration		direct on line		
Full Load Amps		16	Breakdown Torque		201 LB-FT		
R.P.M.		1175	Pull-up Torque		87.8 LB-FT		
Hz	60	Phase	3	Locked-rotor Torque		107 LB-FT	
NEMA Design Code		A	KVA Code	G	Starting Current		109 A
Service Factor (S.F.)		1.15	No-load Current		8.97 A		
NEMA Nom. Eff.		91.7	Power Factor	76	Line-line Res. @ 25°C		0.868 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		43°C	
S.F. Amps				Temp. Rise @ S.F. Load		52°C	
				Locked-rotor Power Factor		33.5	
				Rotor inertia		5.63 LB-FT2	

Load Characteristics 575 V, 60 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	35	55	68	75	78	80	78
Efficiency	83.5	89.7	91.3	91.6	91.3	90.6	91.6
Speed	1196	1192	1189	1185	1180	1176	1180
Line amperes	9.64	11.25	13.58	16.41	19.7	23.25	18.1


ABB Motors and Mechanical Inc.


WINDING # 10WGY949

Typical performance - not guaranteed values.




15 HP 3 PH 60 HZ 1175 RPM 575 V 1046M

TORQUES (LB-FT): PO=201 PU=87.8 LR=107 LRA=109





CD0006



NOTES:

1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007

REV. LTR: E

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\141

REVISED: 10: 24: 49 02/19/2019

BY: ENBRIRO

MTL: -



BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1