



Customer information packet

EHM2543T-8

50HP, 1775RPM, 3PH, 60HZ, 326T, 4256M, OPSB, F1

Specifications

Enclosure	OPSB
Frame	326T
Frame Material	Steel
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	50.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	200.0 V @ 60 HZ
Agency Approvals	CSA UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	132.000 A @ 200.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	94.5 %
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	132.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing

Part detail

Revision	V
Type	AC
Mech. spec.	42H068
Base	
Status	PRD/A
Elec. spec.	42WGW707
Layout	42LYH068
Eff. date	07-10-2024
CD Diagram	CD0006
Poles	04
Leads	3#2
Proprietary	False
Created date	10-07-2010

Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	3 @ 2 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4256M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	27.69 IN
Power Factor	87
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	2.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	Mounting Provisions Only
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1775 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2094E06B03									
CAT.NO.	EHM2543T-8								
SPEC.	42H068W707G1								
HP	50								
VOLTS	200								
AMPS	132								
RPM	1775								
FRAME	326T		HZ	60		PH	3		
SER.F.	1.15	CODE	G	DES	B	CL	F		
NEMA-NOM-EFF	94.5	PF	87						
RATING	40C AMB-CONT								
CC	010A		USABLE AT 208V				N/A		
DE	6312		ODE	6311					
AUTO		MANUAL		NONE					
ENCL	OPSB	SN							
BLANK									

AC Induction Motor Performance Data

Record # 35578

Typical performance - not guaranteed values

Winding: 42WGW707-R001		Type: 4256M	Enclosure: OPSB
Nameplate Data		200 V, 60 Hz: Single Voltage Motor	
Rated Output (HP)	50	Full Load Torque	148 LB-FT
Volts	200	Start Configuration	direct on line
Full Load Amps	132	Breakdown Torque	425 LB-FT
R.P.M.	1775	Pull-up Torque	225 LB-FT
Hz	60 Phase	Locked-rotor Torque	284 LB-FT
NEMA Design Code	B KVA Code	Starting Current	881 A
Service Factor (S.F.)	1.15	No-load Current	48 A
NEMA Nom. Eff.	94.5 Power Factor	Line-line Res. @ 25°C	0.0234 Ω
Rating - Duty	40C AMB-CONT	Temp. Rise @ Rated Load	36°C
S.F. Amps		Temp. Rise @ S.F. Load	43°C
		Locked-rotor Power Factor	27
		Rotor inertia	7.46 LB-FT ²

Load Characteristics 200 V, 60 Hz, 50 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	47	69	79	87	86	86	86
Efficiency	89.8	93.4	94.2	94.5	94.2	93.8	94.3
Speed	1795	1790	1785	1780	1774	1768	1776
Line amperes	65	84	109	132	167	200	153


ABB Motors and Mechanical Inc.


WINDING # 42WGW707

Typical performance - not guaranteed values.




50 HP 3 PH 60 HZ 1775 RPM 200 V 4256M

TORQUES (LB-FT): PO=425 PU=225 LR=284 LRA=881





CD0006



- NOTES:
- 1. THREE LEAD MOTOR MAY BE EITHER WYE CONNECTED OR DELTA CONNECTED.
 - 2. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
 - 3. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
 - 4. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY VARY.
 - 5. LEAD COLORS ARE OPTIONAL. LEADS MUST BE NUMBERED AS SHOWN.

CD0006

REV. DESC: ADD CLASS CONN00000007		
REV. LTR: E	VERSION: 01	TDR: 000001099922
FILE: \AAA\00005\141	REVISED: 10: 24: 49 02/19/2019	BY: ENBRIRO
MTL: —		

BALDOR - RELIANCE®

3PH, SV, 3 LEADS, WYE OR DELTA CONNECTED

SH 1 of 1