



Customer information packet

EJMM2534T-G

40M 2P OPSB HOR 284JM SE

Specifications

Enclosure	OPSB
Frame	284JM
Frame Material	Steel
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	30.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	UR NEMA PREMIUM CSA EEV CSA
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	35.000 A @ 460.0 V 70.000 A @ 230.0 V 76.000 A @ 208.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.7 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	35.0 a

Part detail

Revision	F
Type	AC
Mech. spec.	40E283
Base	
Status	PRD/A
Elec. spec.	40WGX193
Layout	40LYE283
Eff. date	12-11-2025
CD Diagram	CD0180
Poles	02
Leads	9#8
Proprietary	False
Created date	04-03-2019

Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	IP23
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Quantity/Wire Size	9 @ 8 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4040M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	24.69 IN
Power Factor	87
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	C-Face
Pulley Shaft Indicator	Tapped & Key
Rodent Screen	Included
Service Factor	1.15
Shaft Diameter	1.250 IN
Shaft Ground Indicator	Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	Shaft Slinger
Speed	3530 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3554LUA											
CAT.NO.	EJMM2534T-G			P/N						ENCL	OPSB
SPEC.	40E283X193G1	CC	010A	FRAME	284JM	SER.NO.					
HP	30		CLASS	H	HZ	60					
RPM	3530		PH	3	DES	A					
VOLTS	230/460			CODE	H	ODE BRG	6309	DE BRG	6312		
AMPS	70/35										
RATING	40C AMB-CONT		NEMA-NOM-EFF			91.7	GREASE	POLYREX EM			
PF	87	SER.F.	1.15		CT30-60(2:1) VT3-60(20:1)						
USABLE AT	50HZ 30HP 190/380V 84/42A			SF1.0							
HTR-VOLTS	HTR-AMPS				MAX. SPACE HEATER TEMP.						

AC Induction Motor Performance Data

Record # 53042

Typical performance - not guaranteed values

Winding: 40WGX193-R007				Type: 4040M		Enclosure: OPSB				
Nameplate Data				460 V, 60 Hz: High Voltage Connection						
Rated Output (HP)		30		Full Load Torque		44.7 LB-FT				
Volts		230/460		Start Configuration		direct on line				
Full Load Amps		70/35		Breakdown Torque		175 LB-FT				
R.P.M.		3530		Pull-up Torque		59.3 LB-FT				
Hz		60 Phase		3		Locked-rotor Torque		78.3 LB-FT		
NEMA Design Code		A		KVA Code		H		Starting Current	240 A	
Service Factor (S.F.)		1.15		No-load Current		11.2 A				
NEMA Nom. Eff.		91.7		Power Factor		87			Line-line Res. @ 25°C	0.21802 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		23°C				
S.F. Amps				Temp. Rise @ S.F. Load		28°C				
				Locked-rotor Power Factor		24				
				Rotor inertia		1.72 LB-FT2				

Load Characteristics 460 V, 60 Hz, 30 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	58	77	84	87	88	89	88
Efficiency	89.3	92.8	93.4	93.2	92.6	91.8	92.8
Speed	3582.7	3568.7	3554.6	3538.7	3522.3	3504.1	3529
Line amperes	14.4	20.3	27.2	35.1	43.4	52.1	40.1


ABB Motors and Mechanical Inc.


WINDING # 40WGX193

Typical performance - not guaranteed values.




30 HP 3 PH 60 HZ 3530 RPM 460 V 4040M

TORQUES (LB-FT): PO=175 PU=59.3 LR=78.3 LRA=240





CD0180

LOW VOLTAGE
(2D)HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: —

**BALDOR - RELIANCE®**

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1

CD0180