



Customer information packet

EJPM2539T

40HP, 1770RPM, 3PH, 60HZ, 324JP, 4064M, OPSB, F

Specifications

Enclosure	OPSB
Frame	324JP
Frame Material	Steel
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	40.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	CSA CSA EEV NEMA PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	49.000 A @ 460.0 V 98.000 A @ 230.0 V 99.000 A @ 208.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	94.1 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	49.0 a
Insulation Class	F

Part detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	40WGX166
Layout	40LY-000-066
Eff. date	01-30-2024
CD Diagram	CD0005
Poles	04
Leads	9#8
Proprietary	False
Created date	01-15-2021

Inverter Code	Inverter Duty
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4064M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	30.32 IN
Power Factor	82
Product Family	General Purpose
Pulley Face Code	C-Face
Rodent Screen	Included
Service Factor	1.15
Shaft Diameter	1.250 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Speed	1770 rpm
Speed Code	Single Speed
Starting Method	Full Voltage
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2138LUA												
CAT.NO.	EJPM2539T			P/N					ENCLOSURE		OPSB	
SPEC.	40-0000-0191		CC	010A	FRAME		324JP		S/N			
HP	40			CLASS		F	HZ		60			
RPM	1770			PH	3	DES		A				
VOLT	230/460			KVA-CODE			H		ODE BRG	6309	DE BRG	6312
AMP	98/49											
RATING	40C AMB-CONT				GREASE		POLYREX EM					
NEMA-NOM-EFF	94.1	PF	82	SER.F.	1.15							
	50HZ 40HP 190/380V 114/57A						S.F. 1.0					
HTR-VOLTS	HTR-AMPS											

AC Induction Motor Performance Data

Record # 98961

Typical performance - not guaranteed values

Winding: 40WGX166-R001				Type: 4064M		Enclosure: OPSB					
Nameplate Data				460 V, 60 Hz: High Voltage Connection							
Rated Output (HP)		40		Full Load Torque		119.5 LB-FT					
Volts		230/460		Start Configuration		direct on line					
Full Load Amps		98/49		Breakdown Torque		427 LB-FT					
R.P.M.		1770		Pull-up Torque		187 LB-FT					
Hz		60 Phase		3		Locked-rotor Torque		246 LB-FT			
NEMA Design Code		A		KVA Code		H		Starting Current		330 A	
Service Factor (S.F.)		1.15		No-load Current		21.1 A					
NEMA Nom. Eff.		94.1		Power Factor		82		Line-line Res. @ 25°C		0.16236 Ω	
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		41°C					
S.F. Amps				Temp. Rise @ S.F. Load		51°C					
				Locked-rotor Power Factor		31.7					
				Rotor inertia		5.09 lb-ft²					

Load Characteristics 460 V, 60 Hz, 40 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	43	65	76	82	85	85	84
Efficiency	91.1	94	94.4	94.2	93.6	92.7	93.8
Speed	1792.4	1785	1777.8	1770.2	1762.1	1752.8	1765
Line amperes	24.1	30.7	39.2	48.7	59.3	71.3	55.1

ABB Motors and Mechanical Inc.

WINDING # 40WGX166

Typical performance - not guaranteed values.

40 HP 3 PH 60 HZ 1770 RPM 460 V 4064M

TORQUES (LB-FT): PO=427 PU=187 LR=246 LRA=330





