



Customer information packet

EL11307M

.75HP, 1760RPM, 1PH, 60HZ, 56, 3528LC, OPEN, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	56
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Cap Start, Cap Run
Output @ Frequency	.750 HP @ 60 HZ
Phase	1
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	115.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	CURUSEEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	3.100 A @ 230.0 V 6.200 A @ 115.0 V
Design Code	N
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	81.8 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	3.1 a
Insulation Class	F
Inverter Code	Not Inverter

Part detail

Revision	D
Type	AC
Mech. spec.	35M497
Base	
Status	PRD/A
Elec. spec.	35WGK910
Layout	35LYM497
Eff. date	07-10-2025
CD Diagram	CD0320
Poles	04
Leads	6#18,1#14 #4TH
Proprietary	False
Created date	11-15-2024

IP Rating	NONE
KVA Code	L
Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Quantity/Wire Size	6 @ 18 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3528LC
Mounting Arrangement	F1
Number of Poles	4
Overall Length	12.07 IN
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.25
Shaft Diameter	0.625 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1760 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Manual Thermal Overload
Winding Thermal 1 Location	SB
Winding Thermal 2	None

Nameplate

NP3273L											
CAT.NO.	EL11307M										
SPEC.	35M497K910G1										
HP	.75										
VOLTS	115/230										
AMP	6.2/3.1										
RPM	1760										
FRAME	56		HZ	60		PH	1				
SER.F.	1.25		CODE	L	DES	N	CL	F			
F.L. AVG. EFF.	81.8		PF	90							
RATING	40C AMB-CONT										
CC											
DE	6205		ODE	6203							
ENCL	OPEN		SN								
	SFA 7.3/3.65										

AC Induction Motor Performance Data

Record # 112809

Typical performance - not guaranteed values

Winding: 35WGK910-R001				Type: 3528LC		Enclosure: OPEN	
Nameplate Data				115 V, 60 Hz: Low Voltage Connection			
Rated Output (HP)		.75		Full Load Torque		2.231 LB-FT	
Volts		115/230		Start Configuration		direct on line	
Full Load Amps		6.2/3.1		Breakdown Torque		6.83 LB-FT	
R.P.M.		1760		Pull-up Torque		6.06 LB-FT	
Hz	60	Phase	1	Locked-rotor Torque		8.25 LB-FT	
NEMA Design Code		N	KVA Code	Starting Current		64.7 A	
Service Factor (S.F.)		1.25		No-load Current		1.91 A	
NEMA Nom. Eff.		81.8	Power Factor	90	Line-line Res. @ 25°C		0.77061 Ω A Ph 2.5181 Ω B Ph
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		12°C	
S.F. Amps		7.8/3.9		Temp. Rise @ S.F. Load		15°C	

Load Characteristics 115 V, 60 Hz, 0.75 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	74	86	90	93	94	94	94
Efficiency	64.6	77.9	82.3	83.8	83.5	82.2	83.5
Speed	1789.5	1781	1771.4	1760.8	1749.1	1735.4	1749
Line amperes	2.54	3.61	4.85	6.24	7.74	9.4	7.74


ABB Motors and Mechanical Inc.


WINDING # 35WGK910

Typical performance - not guaranteed values.


0.75 HP 1 PH 60 HZ 1760 RPM 115 V 3528LC

TORQUES (LB-FT): PO=6.83 PU=6.06 LR=8.25 LRA=64.7





CD0320



	LINE A	LINE B	JOIN	JOIN
HIGH STD	1,8	4	2,3,5	J
HIGH OPP	1,5	4	2,3,8	J
LOW STD	1,3,8	4	—	2,J,5
LOW OPP	1,3,5	4	—	2,J,8

- NOTES:
- 1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
 - 2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
 - 3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

CD0320

REV. DESC: ADD INTERNAL CONNECTION TO HELP MANUFACTURING		
REV. LTR: G	VERSION: 01	TDR: 000000941594
FILE: \AAA\00007\422	REVISED: 02: 21:00 08/28/2015	BY: ENALEMO
MTL: —	© □	

BALDOR

TYPE LC, DV, REV, THERMAL, B PH AMPS THRU HTR HVC, 7 LEAD
SH 1 of 1