



Customer information packet

EM2508T

7.5HP, 880RPM, 3PH, 60HZ, 256T, 3962M, OPSB, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	256T
Frame Material	Steel
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	7.500 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	900 RPM @ 60 HZ
Voltage @ Frequency	230.0 V @ 60 HZ 460.0 V @ 60 HZ
Agency Approvals	NEMA PREMIUM CURUSEEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	11.700 A @ 460.0 V 23.400 A @ 230.0 V 24.400 A @ 208.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	89.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater

Part detail

Revision	U
Type	AC
Mech. spec.	39K57
Base	
Status	PRD/A
Elec. spec.	39WGX910
Layout	39LYK057
Eff. date	12-12-2025
CD Diagram	CD0005
Poles	08
Leads	9#12
Proprietary	False
Created date	04-24-2015

High Voltage Full Load Amps	11.7 a
Insulation Class	F
Inverter Code	Not Inverter
IP Rating	NONE
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3962M
Mounting Arrangement	F1
Number of Poles	8
Overall Length	24.19 IN
Power Factor	67
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
RoHS Status	ROHS NON-COMPLIANT
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	880 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP1259L											
CAT.NO.	EM2508T										
SPEC.	39K057X910										
HP	7.5										
VOLTS	230/460										
AMP	23.4/11.7										
RPM	880										
FRAME	256T		HZ	60			PH	3			
SER.F.	1.15	CODE	G	DES	B	CL	F				
NEMA-NOM-EFF	89.5	PF	67								
RATING	40C AMB-CONT										
CC	010A										
DE	6309		ODE	6208							
ENCL	OPSB	SN									

AC Induction Motor Performance Data

Record # 51733

Typical performance - not guaranteed values

Winding: 39WGX910-R001			Type: 3962M		Enclosure: OPSB	
Nameplate Data				460 V, 60 Hz: High Voltage Connection		
Rated Output (HP)		7.5		Full Load Torque		45 LB-FT
Volts		230/460		Start Configuration		direct on line
Full Load Amps		23.4/11.7		Breakdown Torque		113 LB-FT
R.P.M.		880		Pull-up Torque		74.6 LB-FT
Hz		60 Phase		Locked-rotor Torque		94.2 LB-FT
NEMA Design Code		B KVA Code		Starting Current		57.1 A
Service Factor (S.F.)		1.15		No-load Current		6.56 A
NEMA Nom. Eff.		89.5 Power Factor		Line-line Res. @ 25°C		1.2778 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		26°C
S.F. Amps				Temp. Rise @ S.F. Load		32°C

Load Characteristics 460 V, 60 Hz, 7.5 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	30	48	60	67	70	72	69
Efficiency	83.7	89.2	90.3	90.1	89.1	87.6	89.5
Speed	895.5	891.1	886.3	881.3	875.1	867.5	878
Line amperes	7.07	8.19	9.81	11.7	14.1	16.9	13.1

ABB Motors and Mechanical Inc.

WINDING # 39WGX910

Typical performance - not guaranteed values.

7.5 HP 3 PH 60 HZ 880 RPM 460 V 3962M

TORQUES (LB-FT): PO=113 PU=74.6 LR=94.2 LRA=57.1





