



Customer information packet

EM2513T-58

15HP, 1470RPM, 3PH, 50HZ, 254T, 3942M, OPSB, F3

Class - None

Division - Not Applicable

Specifications

Enclosure	OPSB
Frame	254T
Frame Material	Steel
Frequency	50.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	15.000 HP @ 50 HZ
Phase	3
Synchronous Speed @ Frequency	1500 RPM @ 50 HZ
Voltage @ Frequency	400.0 V @ 50 HZ
Agency Approvals	C UR US CE CURUS IE3 UKCA WEEE
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	21.400 A @ 400.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	91.4 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None

Part detail

Revision	R
Type	AC
Mech. spec.	39E318
Base	
Status	PRD/A
Elec. spec.	39WGX907
Layout	39LYE318
Eff. date	12-15-2025
CD Diagram	CD0382
Poles	04
Leads	6#12
Proprietary	False
Created date	04-03-2015

Heater Indicator	No Heater
High Voltage Full Load Amps	21.4 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 12 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3942M
Mounting Arrangement	F3
Number of Poles	4
Overall Length	21.69 IN
Power Factor	82
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	Included
RoHS Status	ROHS COMPLIANT
Service Factor	1.15
Shaft Diameter	1.625 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1465 rpm
Speed Code	Single Speed
Starting Method	Wye Start - Delta Run
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2716L									
CAT NO	EM2513T-58								
SPEC.	39E318X907G1								
HP	15HP/11KW					PH	3		
VOLTS	400								
AMP	21.4								
R.P.M. (1/MIN)	1465								
FRAME	254T		HZ	50		I.P.	23		
SER.F.	1.15	CODE	H	DES	B	CL	F		
NOM.EFF.	91.4		% (100%)						
PF	82								
RATING	40C AMB-S1 CONT				CC				
DE BRG	6309		ODE	6208					
ENCL	OPSB	SN							
BLANK	IE3-92.2(75%)91.7(50%)								
	IC411								
	102 KG								

AC Induction Motor Performance Data

Record # 49905

Typical performance - not guaranteed values

Winding: 39WGX907-R001				Type: 3942M		Enclosure: OPSB	
Nameplate Data				400 V, 50 Hz: Single Voltage Motor			
Rated Output (HP)		15		Full Load Torque		53.6 LB-FT	
Volts		400		Start Configuration		direct on line	
Full Load Amps		22		Breakdown Torque		204 LB-FT	
R.P.M.		1465		Pull-up Torque		94.8 LB-FT	
Hz		50		Phase		3	
NEMA Design Code		B		KVA Code		G	
Service Factor (S.F.)		1.15		No-load Current		9.18 A	
NEMA Nom. Eff.		91.4		Power Factor		81	
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load	
S.F. Amps						Temp. Rise @ S.F. Load	
						Locked-rotor Power Factor	
						Rotor inertia	

Load Characteristics 400 V, 50 Hz, 15 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	44	66	77	81	84	83	81
Efficiency	86.6	90.8	91.7	91.6	90.7	89.5	91.2
Speed	1493	1484	1477	1469	1460	1449	1465
Line amperes	10.7	13.5	17.3	21.8	26.3	32.1	24.8

ABB Motors and Mechanical Inc.

WINDING # 39WGX907

Typical performance - not guaranteed values.

15 HP 3 PH 50 HZ 1465 RPM 400 V 3942M

TORQUES (LB-FT): PO=204 PU=94.8 LR=104 LRA=135





