



Customer information packet

EM251402T-4

400HP, 3570RPM, 3PH, 60HZ, 449TS, A44112M, DP

Class - None

Division - Not Applicable

Specifications

Enclosure	DP
Frame	449TS
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	400.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CCSAUSEEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Current @ Voltage	431.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	96.2 %
Feedback Device	NO FEEDBACK
Heater Indicator	No Heater
High Voltage Full Load Amps	431.0 a
Insulation Class	F
Inverter Code	Inverter Ready
IP Rating	NONE
KVA Code	F
Lifting Lugs	Standard Lifting Lugs
Motor Lead Quantity/Wire Size	6 @ 2/0 AWG
Motor Standards	NEMA
Motor Type	A44112M

Part detail

Revision	D
Type	AC
Mech. spec.	
Base	
Status	PRD/A
Elec. spec.	A44WG2659
Layout	604989-664
Eff. date	09-25-2025
CD Diagram	416820-008
Poles	02
Leads	6#2/0
Proprietary	False
Created date	01-22-2015

Mounting Arrangement	F1
Number of Poles	2
Overall Length	44.31 IN
Power Factor	90
Product Family	General Industrial
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Service Factor	1.15
Shaft Diameter	2.375 IN
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3570 rpm
Speed Code	Single Speed
Starting Method	Wye Start - Delta Run
Thermal Device - Bearing	None
Thermal Device - Winding	None


Nameplate

NP2496L	
MOBIL POLYREX EM	


NP2349L

SPEC NO.	A44-6803-2659			CAT.NO.	EM251402T-4					FRAME	449TS		
HP	400	VOLTS	460		PHASE	3	DESIGN	B	TYPE	P			
RPM	3570	AMPS	431		HZ	60	AMB	40	SF	1.15			
DRIVE END BEARING	65BC03J30X		DUTY	CONT	INSUL.CLASS			F					
OPP D.E. BEARING	65BC03J30X		ENCL	DP	CODE	F							
SER.NO.				POWER FACTOR		90	NEMA-NOM-EFFICIENCY				96.2		
						MAX CORR KVAR			50	GUARANTEED EFFICIENCY		95.4	
						NEMA NOM/CSA QUOTED EFF							
										MOTOR WEIGHT		2075	

REL. S.O.	FRAME	HP	TYPE	PHASE/HERTZ	RPM	VOLTS
	449T	400	P	3/60	3570	460
AMPS	DUTY	AMB °C/INSUL.	S.F.	NEMA DESIGN	CODE LETTER	ENCL.
431	CONT	40/F	1.15	B	F	PRXE
E/S	ROTOR		TEST S.O.	TEST DATE	STATOR RES. @25 °C OHMS (BETWEEN LINES)	
433472	418143013KE		---	---	.00865	
PERFORMANCE						
LOAD	HP	AMPERES	RPM	POWER % FACTOR	% EFFICIENCY	
NO LOAD	0	89.7	3600	5.37	0	
1/4	100	136	3593	72.7	94.6	
2/4	200	222	3586	87.5	96.4	
3/4	300	324	3579	89.9	96.6	
4/4	400	431	3571	90.0	96.4	
5/4	500	541	3562	90.1	95.9	
SPEED TORQUE						
		RPM	TORQUE % FULL LOAD	TORQUE LB.-FT.	AMPERES	
LOCKED ROTOR		0	174	1022	2555	
PULL UP		2550	136	800	1885	
BREAKDOWN		3474	209	1231	1235	
FULL LOAD		3571	100	588	431	
AMPERES SHOWN FOR 460. VOLT CONNECTION. IF OTHER VOLTAGE CONNECTIONS ARE AVAILABLE, THE AMPERES WILL VARY INVERSELY WITH THE RATED VOLTAGE						
REMARKS: TYPICAL DATA XE MOTOR-NEMA NOM. EFF. 96.2%						
BALDOR			DR. BY D. M. BYRD CR. BY C. E. JAMISON APP. BY D. M. BYRD DATE 05/14/02		A-C MOTOR PERFORMANCE DATA A44WG2659-R002 ISSUE DATE 05/14/02	
A MEMBER OF THE ABB GROUP						





Printed on 2/9/15 8:22 @ ragsun



416820-008

A-C MOTOR
CONNECTION DIAGRAM

STANDARD 6 LEAD Y START – DELTA RUN



< N. P. 1767-DC >

REV. DESC: ADDED T4 TO Y CONNECT DIAGRAM		
REV. LTR: D	VERSION: 04	TDR: 000000847713
FILE: \RAG\00001\808	REVISED: 10: 41: 26 04/08/2014	BY: RAGJSS1
MTL: -	© □	

BALDOR

CONNECT DIAGRAM STD 6 LEAD Y START DELTA RUN
SH 1 of 1

416820-008