



Customer information packet

EM2535T-CI

30HP, 1775RPM, 3PH, 60HZ, 286T, 1052M, OPEN, F1

Class - None

Division - Not Applicable

Specifications

Enclosure	OPEN
Frame	286T
Frame Material	Iron
Frequency	60.00 Hz
Haz Area Class and Group	None
Haz Area Division	Not Applicable
Motor Letter Type	Three Phase
Output @ Frequency	30.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ 230.0 V @ 60 HZ
Agency Approvals	NEMA PREMIUM NEMA_PREMIUM UR CSA EEV
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	76.000 A @ 208.0 V 76.000 A @ 230.0 V 38.000 A @ 460.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	94.1 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard

Part detail

Revision	K
Type	AC
Mech. spec.	10D01
Base	
Status	PRD/A
Elec. spec.	10WGZ654
Layout	10LYD001
Eff. date	06-27-2024
CD Diagram	CD0180
Poles	04
Leads	9#10
Proprietary	False
Created date	06-30-2017

Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	38.0 a
Insulation Class	F
Inverter Code	Inverter Ready
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	9 @ 10 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	1052M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	24.94 IN
Power Factor	77
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	1.875 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1775 rpm
Speed Code	Single Speed
Starting Method	Direct on line
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor

Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3554LUA											
CAT.NO.	EM2535T-CI			P/N						ENCL	OPEN
SPEC.	10D001Z654G1	CC	010A	FRAME		286T	SER.NO.				
HP	30	CLASS		F	HZ	60					
RPM	1775	PH	3	DES		A					
VOLTS	230/460			CODE	H	ODE BRG	6309	DE BRG	6310		
AMPS	76/38										
RATING	40C AMB-CONT		NEMA-NOM-EFF			94.1	GREASE	POLYREX EM			
PF	77	SER.F.	1.15	CT30-60(2:1) VT3-60(20:1)							
USABLE AT	50HZ 30HP 190/380V 88/44A			SF 1.0							
HTR-VOLTS	HTR-AMPS	MAX. SPACE HEATER TEMP.									

AC Induction Motor Performance Data

Record # 66162

Typical performance - not guaranteed values

Winding: 10WGZ654-R001				Type: 1052M		Enclosure: OPEN	
Nameplate Data				460 V, 60 Hz: High Voltage Connection			
Rated Output (HP)		30		Full Load Torque		88.57 LB-FT	
Volts		230/460		Start Configuration		direct on line	
Full Load Amps		78/39		Breakdown Torque		302 LB-FT	
R.P.M.		1770		Pull-up Torque		128 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		166 LB-FT	
NEMA Design Code		A	KVA Code	H	Starting Current		254 A
Service Factor (S.F.)		1.15		No-load Current		19.1 A	
NEMA Nom. Eff.		94.1	Power Factor	77	Line-line Res. @ 25°C		0.22704 Ω
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load		33°C	
S.F. Amps				Temp. Rise @ S.F. Load		39°C	
				Locked-rotor Power Factor		32.4	

Load Characteristics 460 V, 60 Hz, 30 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	38	60	72	78	82	83	80
Efficiency	89.4	93.3	94.2	94.2	93.9	93.3	94
Speed	1794	1789.1	1783.8	1778.2	1772.3	1765.7	1775
Line amperes	20.9	25.2	31.1	38	45.8	54.3	42.7


ABB Motors and Mechanical Inc.


WINDING # 10WGZ654

Typical performance - not guaranteed values.



30 HP 3 PH 60 HZ 1770 RPM 460 V 1052M

TORQUES (LB-FT): PO=302 PU=128 LR=166 LRA=254





CD0180

LOW VOLTAGE
(2D)HIGH VOLTAGE
(1D)

NOTES:

1. INTERCHANGE ANY TWO LINE LEADS TO REVERSE ROTATION.
2. OPTIONAL THERMOSTATS ARE PROVIDED WHEN SPECIFIED.
3. ACTUAL NUMBER OF INTERNAL PARALLEL CIRCUITS MAY BE A MULTIPLE OF THOSE SHOWN ABOVE.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

REV. DESC: ADD CLASS CONN00000007

REV. LTR: D

VERSION: 01

TDR: 000001099922

FILE: \AAA\00005\148

REVISED: 10: 25: 29 02/19/2019

BY: ENBRIRO

MTL: —

**BALDOR - RELIANCE®**

3PH, DV, 9 LEADS, DELTA CONNECTION

SH 1 of 1

CD0180