



Customer information packet

EM2543T-8

50HP, 1775RPM, 3PH, 60HZ, 326T, 4256M, OPSB, F1

Specifications

Enclosure	OPSB
Frame	326T
Frame Material	Steel
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	50.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	1800 RPM @ 60 HZ
Voltage @ Frequency	200.0 V @ 60 HZ
Agency Approvals	CSA EEV NEMA PREMIUM NEMA_PREMIUM UR
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	131.000 A @ 208.0 V 132.000 A @ 200.0 V
Design Code	A
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	94.5 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	132.0 a
Insulation Class	F

Part detail

Revision	AG
Type	AC
Mech. spec.	42F56
Base	
Status	PRD/A
Elec. spec.	42WGW479
Layout	42LYF056
Eff. date	06-27-2024
CD Diagram	CD0695
Poles	04
Leads	6#6
Proprietary	False
Created date	01-01-0001

Inverter Code	Inverter Ready
KVA Code	G
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	No Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 6 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4256M
Mounting Arrangement	F1
Number of Poles	4
Overall Length	27.69 IN
Power Factor	87
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	2.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1775 rpm
Speed Code	Single Speed
Starting Method	Part Winding
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP3554L

CAT.NO.	EM2543T-8			P/N					ENCL	OPSB	
SPEC.	42F056W479	CC	010A	FRAME	326T	SER.NO.					
HP	50		CLASS	F	HZ	60					
RPM	1775		PH	3	DES	A					
VOLTS	200			CODE	G	ODE BRG	6311	DE BRG	6312		
AMPS	132										
RATING	40C AMB-CONT		NEMA-NOM-EFF			94.5	GREASE	POLYREX EM			
PF	87	SER.F.	1.15	VPWM INVERTER READY							
HTR-VOLTS	HTR-AMPS	MAX. SPACE HEATER TEMP.									

Accessories

Part number	Description	Multiplier
42-1300	C FACE KIT	A8
42EP1601A01	SP'L D-FLANGE MTD. PU. E.P. MDL.42 W/BFL	

AC Induction Motor Performance Data

Record # 13698

Typical performance - not guaranteed values

Winding: 42WGW479-R001			Type: 4256M		Enclosure: OPSB		
Nameplate Data				200 V, 60 Hz: Single Voltage Motor			
Rated Output (HP)		50		Full Load Torque		148 LB-FT	
Volts		200		Start Configuration		direct on line	
Full Load Amps		132		Breakdown Torque		423 LB-FT	
R.P.M.		1775		Pull-up Torque		234 LB-FT	
Hz	60	Phase	3	Locked-rotor Torque		283 LB-FT	
NEMA Design Code		A		KVA Code	G		
Starting Current		877 A		No-load Current			48 A
Service Factor (S.F.)		1.15		Line-line Res. @ 25°C			0.0235 Ω
NEMA Nom. Eff.		94.5		Power Factor		87	
Rating - Duty		40C AMB-CONT		Temp. Rise @ Rated Load			36°C
S.F. Amps				Temp. Rise @ S.F. Load			43°C
				Locked-rotor Power Factor			27
				Rotor inertia			7.46 LB-FT ²

Load Characteristics 200 V, 60 Hz, 50 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	47	70	80	87	86	86	86
Efficiency	90	93.6	94.4	94.5	94.1	94	94.3
Speed	1795	1790	1785	1779	1774	1768	1776
Line amperes	64	83	108	132	166	200	152.4

ABB Motors and Mechanical Inc.

WINDING # 42WGW479

Typical performance - not guaranteed values.

50 HP 3 PH 60 HZ 1775 RPM 200 V 4256M

TORQUES (LB-FT): PO=423 PU=234 LR=283 LRA=877





