



Customer information packet

EM2556T-4

150HP, 3540RPM, 3PH, 60HZ, 405TS, 4464M, OPSB

Specifications

Enclosure	OPSB
Frame	405TS
Frame Material	Steel
Frequency	60.00 Hz
Motor Letter Type	Three Phase
Output @ Frequency	150.000 HP @ 60 HZ
Phase	3
Synchronous Speed @ Frequency	3600 RPM @ 60 HZ
Voltage @ Frequency	460.0 V @ 60 HZ
Agency Approvals	CSA EEV UR NEMA_PREMIUM NEMA PREMIUM
Ambient Temperature	40 °C
Auxiliary Box	NO AUXILLARY BOX
Auxiliary Box Lead Termination	None
Base Indicator	Rigid
Bearing Grease Type	Polyrex EM (-20F +300F)
Blower	None
Current @ Voltage	166.000 A @ 460.0 V
Design Code	B
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	94.1 %
Electrically Isolated Bearing	Not Electrically Isolated
Feedback Device	NO FEEDBACK
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No Heater
High Voltage Full Load Amps	166.0 a
Insulation Class	F
Inverter Code	Not Inverter

Part detail

Revision	S
Type	AC
Mech. spec.	44E194
Base	
Status	PRD/A
Elec. spec.	44WGW254
Layout	44LYE194
Eff. date	09-29-2025
CD Diagram	CD0382
Poles	02
Leads	6#2
Proprietary	False
Created date	05-15-2012

IP Rating	NONE
KVA Code	H
Lifting Lugs	Standard Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	Ko Box
Motor Lead Quantity/Wire Size	6 @ 2 AWG
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	4464M
Mounting Arrangement	F1
Number of Poles	2
Overall Length	31.85 IN
Power Factor	91
Product Family	General Purpose
Pulley End Bearing Type	Ball
Pulley Face Code	Standard
Pulley Shaft Indicator	Standard
Rodent Screen	None
Service Factor	1.15
Shaft Diameter	2.125 IN
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	3540 rpm
Speed Code	Single Speed
Starting Method	Wye Start - Delta Run
Thermal Device - Bearing	None
Thermal Device - Winding	None
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	None
Winding Thermal 2	None

Nameplate

NP2138LUA													
CAT.NO.	EM2556T-4				P/N					ENCLOSURE		OPSB	
SPEC.	44E194W254G1		CC	010A	FRAME		405TS		S/N				
HP	150				CLASS		F	HZ	60				
RPM	3540				PH	3	DES		B				
VOLT	460				KVA-CODE			H	ODE BRG		6312	DE BRG	6312
AMP	166												
RATING	40C AMB-CONT				GREASE			POLYREX EM					
NEMA-NOM-EFF	94.1	PF	91	SER.F.	1.15								
	50HZ 140HP 380V 187A							SF1.0					
HTR-VOLTS	HTR-AMPS												

Accessories

Part number	Description	Multiplier
44-1403A	C FACE KIT 44/404 USC TSC 6312 BRG	A8

AC Induction Motor Performance Data

Record # 38383

Typical performance - not guaranteed values

Winding: 44WGW254-R003				Type: 4464M		Enclosure: OPSB	
Nameplate Data				460 V, 60 Hz: Single Voltage Motor			
Rated Output (HP)		150		Full Load Torque		224 LB-FT	
Volts		460		Start Configuration		direct on line	
Full Load Amps		166		Breakdown Torque		758 LB-FT	
R.P.M.		3540		Pull-up Torque		264 LB-FT	
Hz		60		Phase		3	
NEMA Design Code		B		KVA Code		H	
Service Factor (S.F.)		1.15		No-load Current		37.6 A	
NEMA Nom. Eff.		94.1		Power Factor		91	
Rating - Duty		40C		AMB-CONT		Temp. Rise @ Rated Load	
S.F. Amps						Temp. Rise @ S.F. Load	
						Locked-rotor Power Factor	
						Rotor inertia	

Load Characteristics 460 V, 60 Hz, 150 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	70	86	90	91	91	91	91
Efficiency	90.6	93.8	94.3	94	93.4	93.4	93.6
Speed	3589	3576	3565	3549	3532	3519	3539
Line amperes	56.5	89.2	126	166	210	247	192

ABB Motors and Mechanical Inc.

WINDING # 44WG254

Typical performance - not guaranteed values.

150 HP 3 PH 60 HZ 3540 RPM 460 V 4464M

TORQUES (LB-FT): PO=758 PU=264 LR=315 LRA=1225





